



NORAM 65E TURBO



January 2015

NLP01501

STANDARD EQUIPMENT

ACCELERATOR-DECELERATOR

Foot or Hand Operated

AIR CLEANER

Dry Type with Service Indicator

Secondary Element

Automatic Dust Ejector

ALTERNATOR, 120 Amp

ANTI-FREEZE

AXLES

Hi-Clearance Welded Steel Truss

Heavy Duty Spindles

Transport Lock

Limited Slip Differential

BACK-UP ALARM

BATTERY, 12 volt

BRAKES

Wet Disc Type

Four Wheel, Self-Adjusting

Dual, Tandem by Tandem System

Power Assist

CIRCLE

360 Degree Rotation

Circle Turn Gears Operating in Oil

CONTROLS

Adjustable Control Console

Low Effort Hydraulic Controls

Articulation

Blade Lift Controls (2)

Blade Side Shift

Circle Shift

Circle Turn

Wheel Lean

Provision for Four Attachments

DRAWBAR

ELECTRICAL SYSTEM & STARTING

12 Volt

Battery Disconnect Switch

ENGINE

Cummins QSF 3.8 Tier 4 Final

Turbocharged, Direct Injection

In-Line, 4 Cylinder

120 Horsepower (prelim) at 2200 RPM

ENGINE SIDE PANELS

FAN, Pusher Type

GAUGES, Electronic

Engine Coolant Temperature

Engine Oil Pressure

Fuel Level

Hourmeter

Tachometer

Transmission Oil Temperature

Voltmeter

HORN, Electric

HYDRAULIC, Open Center System

8 Station Stack Type Valve

LIGHT PACKAGE

(2) Front Headlights (Hi-Lo Beam)

(2) Front Worklights

Stop and Tail Lights

Turn Signals

MAIN FRAME, Welded Construction

Articulated

MOLDBOARD

10 ft. x 21 in. x 5/8 in.

Hydraulic Shift

Roll-away Involute Curve

Interchangeable End Bits

MUFFLER, Horizontal, Under Hood

PARKING BRAKE, Mechanical

ROPS CANOPY with Headliner

Domelight

Floormat

Glove Box

Inside Mirror

SEAT, Deluxe Air-Ride Suspension

Adjustable Arm Rests

SEAT BELT

STEERING, Power, Hydraulic

STEPS, Right and Left

TIRES - Tubeless

15.00 x 19.5 (8 Ply) G2

TORQUE CONVERTER

TRANSMISSION - Full Powershift

6 Forward and 2 Reverse

Electronic Shift Control

LCD Message Center

TRANSPORT TIE-DOWN GROUP

VANDALISM PROTECTION

F.O.B. Knoxville, Iowa	CATALOG NUMBER	WEIGHT LBS	LIST PRICE
			(US \$)
65E TURBO MOTOR GRADER	65ET-011	16,785	\$ 163,520



NORAM 65E TURBO



January 2015

NLP01501

FACTORY INSTALLED OPTIONS

	CATALOG NUMBER	WEIGHT LBS	LIST PRICE (US \$)
BANK SLOPE SADDLE	65E-206	224	6,895
BLADE FRONT MOUNTED - Hyd., 8 ft. x 24 in. with Skid Plates	65E-302	495	3,045
Requires:			
* Front Attachment Group & Piping	65E-300	480	4,465
* Availability for Float Control Valve			
CAB - Includes:			
Fabric Seat, Dome Light, Inside Mirror, Floormat, Front & Rear Windshield Wipers, Front & Rear Windshield Washers, Heater, Defroster Fans, Glove Box, Sound Suppression and Tinted Glass ..	65E-100	175	11,300
CAB AIR CONDITIONING GROUP	65E-114	65	6,890
FLOAT CONTROL VALVES - (2) Moldboard & (1) Front Attachment .	65E-500	2	1,130
FLOODLIGHT GROUP			
(2) Front & (2) Rear - Canopy or Cab Mounted	65E-101	6	920
MIRRORS - Rear View, (2) External	65E-102	22	465
MOLDBOARD PITCH - Hydraulic	65E-200	30	2,250
12 FT. MOLDBOARD - In lieu of Standard 10 ft.	65E-202		1,895
RADIO GROUP - Includes AM, FM, CD, with (2) Speakers.....	65E-111	20	990
RIPPER REAR MOUNTED - Hyd., 75 in., Includes 3 Shanks	65E-330	890	9,220
Requires:			
* Piping and Control Kit		Please Contact NorAm	
SCARIFIER FRONT MOUNTED - Hyd., 41 in., Includes 9 Teeth	65E-301	245	2,310
Requires:			
* Front Attachment Group & Piping	65E-300	480	4,465
* Availability for Float Control Valve			
STROBE LIGHT, ENGINE COOLANT HEATER, ETC.....		Please Contact NorAm	

Prices F.O.B. Knoxville, Iowa

Prices and specifications subject to change without notice



NORAM 65E TURBO



January 2015

NLP01501

FIELD INSTALLED OPTIONS

	<u>CATALOG NUMBER</u>	<u>WEIGHT LBS</u>	<u>LIST PRICE (US \$)</u>
BLADE FRONT MOUNTED - Hyd., 8 ft. x 24 in. with Skid Plates	4508	495	2,960
Requires:			
* Front Attachment Group & Piping	4506	480	4,135
* Availability for Float Control Valve			
FLOODLIGHT GROUP			
(2) Front & (2) Rear - Canopy or Cab Mounted	4500	6	785
MIRRORS - Rear View, (2) External	4501	22	455
RIPPER REAR MOUNTED - Hyd., 75 in., Includes 3 Shanks	4570	890	7,825
Requires:			
* Piping and Control Kit		Please Contact NorAm	
SCARIFIER FRONT MOUNTED - Hyd., 41 in., Includes 9 Teeth	4507	245	2,115
Requires:			
* Front Attachment Group & Piping	4506	480	4,135
* Availability for Float Control Valve			
SPARE TIRE & RIM			
15.00 x 19.5 (8 Ply) G-2 Tubeless	65E-900	150	1,540

Prices F.O.B. Knoxville, Iowa

PLEASE CONTACT NORAM FOR APPLICABLE DISCOUNTS AND AVAILABILITY

Prices and specifications subject to change without notice