

TAKEUCHI®

2015 MACHINE PRICE LIST

519 Bonnie Valentine Way, Pendergrass, GA 30567

e-mail sales@takeuchi-us.com
www.takeuchi-us.com

Prices and specifications
subject to change without notice

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2015



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB216

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 3,902 lbs.	ROPS/TOPS/FOPS 4 post canopy
Width: 38.6" / 51.2"	LCD gauge panel with multi-functional operator information center
Maximum Dig Depth: 7' 9.1"	Hydraulically retractable track frame
Bucket Digging Force: 4,250 lbs.	Travel alarm
Horsepower / RPM: 15 / 2,400	Two-speed travel with automatic down shift
Travel Speed: 1.4 / 2.6 mph	Control pattern selector valve
Auxiliary Flow: 8.9 gpm	Pilot operated joystick controls with safety lock out
Boom swing: Left 80° / Right 50°	Cast iron, wrap around counterweight
9" wide rubber tracks	Adjustable suspension seat with 2" retractable seat belt
Long Arm w/ integrated thumb mount	Two-way auxiliary hydraulic circuit routed to the end of the arm
	Variable displacement axial piston main hydraulic pumps
	Adjustable width dozer blade
	Electronic engine monitoring system

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB216	TB216 Equipped with ROPS/TOPS/FOPS canopy, Rubber tracks	\$31,579

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB01608	8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity	\$465
BTB01612	12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity	\$480
BTB01618	18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity	\$557
BTB01624	24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity	\$650
BQC01600	Quick Coupler	\$785
BQC01612	12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity	\$480
BQC01618	18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity	\$557
BQC01624	24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity	\$650
BQC01624D	24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity	\$882
BTH216I	INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets)	\$2,025

FIELD INSTALLED OPTIONS

1914199048	3" Non-retractable seat belt in lieu of standard 2"	\$68
BTH216K	Hydraulic thumb (Only compatible with 12" and larger buckets)	\$1,680



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB230

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 6,607 lbs.	TOPS/ROPS/FOPS 4 post canopy
Width: 4' 9"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 10' 2"	High back adjustable suspension seat
Bucket Digging Force: 6,471 lbs.	Pilot operated joystick control with control pattern change valve
Horsepower / RPM: 24.4 / 2,400	EPA Final Tier 4 compliant engine with engine monitoring system
Travel Speed: 1.7 / 3.0 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 13.4 gpm	High capacity radiator and hydraulic oil cooler
Boom Swing: Left 80° / Right 60°	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system,
Track Width: 11.8"	proportional slide switch, one-way mode and continuous detent mode
Two speed travel with automatic shift down	Safety features include: TOPS/ROPS/FOPS 4 post canopy, travel alarm, retractable
Reinforced arm w/ Integrated thumb mount	seat belt, control lockout, pilot accumulator, mirrors and lights
Heavy duty dozer blade with float	Variable displacement axial piston pump
	Auto Idle

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB230	TB230 Canopy Equipped with Rubber or Steel Tracks	\$40,900
TB230A (w/Angle Blade)	TB230 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$43,650

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB12512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$650
BTB12518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$675
BTB12524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC12500	Quick Coupler	\$785
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$650
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$675
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$675
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,015
BTH125I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$1,920

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH125K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$1,575
1914053691	Bolt on rubber pads (order Qty 2) for TB230 steel track unit	\$1,424



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB240

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 8,289 lbs.	TOPS/ROPS/FOPS 4 post canopy
Width: 5' 8.5"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 11' 6"	High back adjustable suspension seat
Bucket Digging Force: 9,959 lbs.	Pilot operated joystick control with control pattern change valve
Horsepower / RPM: 35.8 / 2,200	EPA Final Tier 4 compliant engine with DPF and engine monitoring system
Travel Speed: 1.7 / 3.0 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 17.1 gpm	Side by side industrial type radiator and hydraulic oil cooler
Boom Swing: Left 76° / Right 58°	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode
Track width: 13.8"	Safety features include: TOPS/ROPS/FOPS 4 post canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, mirrors and lights
Two speed travel with automatic shift down	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Heavy duty dozer blade with float	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB240	TB240 Canopy Equipped with Rubber or Steel Tracks	\$52,760
TB240A (w/Angle Blade)	TB240 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$55,760
TB240C	TB240 Cab Equipped with Rubber or Steel Tracks TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 5.7" color monitor, 12v power outlet	\$60,100
TB240CA (w/ Angle Blade)	TB240 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$63,100

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB13512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$650
BTB13518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$675
BTB13524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC13500	Quick Coupler	\$785
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$650
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$675
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$675
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,015
BTH135I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$1,920

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH135K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$1,575
1914054391	Bolt on rubber pads (order Qty 2) for TB240 steel track unit	\$1,740



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB260

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 12,180 lbs.	TOPS/ROPS/FOPS 4 post canopy
Width: 6' 6.7"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 12' 9.4"	Adjustable high back suspension seat
Bucket Digging Force: 12,756 lbs.	Pilot operated joystick control with control pattern change valve
Horsepower / RPM: 47.6 / 2,400	Proportional slide switch control auxiliary hydraulics
Travel Speed: 1.7 / 3.0 mph	EPA Final Tier 4 Turbocharged engine with DPF and engine monitoring system
Primary Aux Flow: 27.0 gpm	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Second Aux Flow: 11.6 gpm	Side by side radiator and hydraulic cooler
Boom Swing: Left 78° / Right 55°	Variable Displacement axial piston pump
Track Width: 15.7"	Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls
Two speed travel with automatic shift down	Primary auxiliary continuous mode and one-way mode
Reinforced arm w/ Integrated thumb mount	Safety features include: TOPS/ROPS/FOPS 4 post Canopy, travel alarm, retractable seat belt, control lockdown, pilot accumulator, mirrors and lights
Heavy duty dozer blade with float	
Auto Idle	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB260	TB260 Equipped with ROPS/TOPS/FOPS canopy, Rubber or Steel Tracks	\$69,716
TB260A (w/Angle Blade)	TB260 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$72,716
TB260L (w/ Road Liner Tracks)	TB260 Canopy (above Equipped with Road Liner Tracks)	\$74,716
TB260LA (w/ Angle Blade & Road Liner Tracks)	TB260 Canopy (above Equipped with Road Liner Tracks) w/ Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$77,716
TB260C	TB260 Cab Equipped with Rubber or Steel Tracks TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 5.7" color monitor, 12v power outlet	\$76,316
TB260CA (w/Angle Blade)	TB260 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$79,316
TB260CL (w/ Road Liner Tracks)	TB260 Cab (above Equipped with Road Liner Tracks)	\$81,316
TB260CLA (w/ Angle Blade & Road Liner Tracks)	TB260 Cab (above Equipped with Road Liner Tracks) w/ Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$84,316

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB26012	12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity	\$945
BTB26018	18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity	\$1,000
BTB26024	24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity	\$1,080
BTB26036	36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity	\$1,340
BQC26000	Quick Coupler	\$800
BQC14512	12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity	\$945
BQC14518	18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity	\$1,000
BQC14524	24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity	\$1,080
BQC14536	36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity	\$1,340
BQC14536D	36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity	\$1,283
BTH260I INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,070

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH260K	Hydraulic Thumb (Only compatible with 18" and larger buckets)	\$1,722



519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel: 706-693-3600 Fax: 706-693-3725
 www.takeuchi-us.com

TB290

Excavator

STANDARD EQUIPMENT

Operating Weight: 18,780 lbs.	ROPS/FOPS enclosed cab w/ air conditioner/heat, windshield wiper,
Width: 7' 7"	12v power outlet, and AM/FM/MP3 radio
Maximum Dig Depth: 15'	Color 5.7" gauge panel with multi-function operator information center
Bucket Digging Force: 16,565 lbs.	10-way adjustable high back suspension seat
Net Horsepower / RPM: 69.2 / 2,000	Pilot operated joystick control with control pattern change valve
Travel Speed: 1.6 / 3.1 mph	EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system
Auxiliary Flow: 26.4 gpm / 14.5 gpm	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Boom Swing: Left 70° / Right 60°	Side by side radiator and hydraulic cooler
Track Width: 17.7" Rubber / 21.7" Steel	Load sensing variable displacement hydraulic system
	Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch
Two speed travel with automatic shift down	Primary auxiliary continuous mode and one-way mode
Reinforced arm w/ Integrated thumb mount	Safety features include: ROPS/FOPS enclosed cab, large skylight with sun shade,
Heavy duty dozer blade with float	travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding
Automatic track tensioner	valve with lift alarm, mirrors and lights
Auto Idle	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB290C	TB290 Cab Equipped with Rubber or Steel Tracks	\$110,500
TB290CA (w/ Angle Blade)	TB290 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$116,500
TB290CL (w/ Road Liner Tracks)	TB290 Cab (above Equipped except with Road Liner Tracks)	\$116,290
TB290CLA (w/ Angle Blade & Road Liner Tracks)	TB290 Cab (above Equipped except with Road Liner Tracks) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$122,290

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB07018	18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,080
BTB07024	24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,155
BTB07036	36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07000	Quick Coupler	\$1,030
BQC07018	18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,080
BQC07024	24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,155
BQC07036	36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07036D	36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,420
BTH0701	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,790

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH070K	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$2,435



TB280FR

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

Zero Swing Excavator

STANDARD EQUIPMENT

Operating Weight: 19,077 lbs. Width: 7' 7" Maximum Dig Depth: 14' 11" Bucket Digging Force: 16,335 lbs. Horsepower / RPM: 69.2 / 2,000 Travel Speed: 1.6 / 3.1 mph Auxiliary Flow: 39 gpm / 15 gpm Boom swing: Left 30° / Right 15° Track Width: 17.7"	ROPS/FOPS enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet and AM/FM/MP3 radio Tilt-up operator's platform Color 5.7" gauge panel with multi-function operator information center 10-way adjustable high back suspension seat Pilot operated joystick control with control pattern change valve EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Variable displacement axial piston main hydraulic pumps Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch Primary auxiliary continuous mode and one-way mode Safety features include: ROPS/FOPS enclosed cab, large skylight with sun shade, travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding valve with lift alarm, mirrors and lights
Side-to-Side (STS) offset boom system Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float Auto idle	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB280FRC	TB280FR Cab Equipped with Rubber or Steel Tracks	\$114,000
TB280FRCL (w/ Road Liner Tracks)	TB280FR Cab Equipped with Road Liner Tracks	\$119,790

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB07018	18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,080
BTB07024	24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,155
BTB07036 *	36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07000	Quick Coupler	\$1,030
BQC07018	18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,080
BQC07024	24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,155
BQC07036 *	36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07036D *	36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,420
BTH070I	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,790

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2" belt	\$91
BTH070K *	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$2,435

* **NOTE:** The Zero Swing front radius feature is only available for the standard bucket attachment (30" or smaller)