



GC1705 GARDEN COMPACT

MASSEY FERGUSON®

(F.O.B. Port of Entry)

TRACTOR FEATURES

POWER TRAIN

- Engine:
 - 22.5 Gross HP 3 Cyl Diesel 68.5 CID (1.1 L)
 - 22.0 Net HP @ 2600 RPM
 - 18.7 PTO HP @ 2600 RPM
- Dry Type Single Air Cleaner
- Transmission: 2 Range Hydrostatic with Cruise Control
- Wet Disk Brakes
- Parking Brake
- Differential Lock
- PTO: 540 RPM Independent PTO
2000 RPM Mid Independent PTO

HYDRAULIC SYSTEM

- 3-Point Hitch, Cat I With Directional Control,
 - Auto Return Lever System
- Engine Driven Gear Pump
- 3-Point Hitch 4.3 GPM (15.5 LPM)
- Power Steering 2.0 GPM (7.5 LPM)
- Total Combined Flow 6.3 GPM (23.1 LPM)

INSTRUMENTS

- Tachometer / Hourmeter
- Engine Coolant Gauge Fuel Gauge
- Warning Lights: Electrical Charging, Oil Pressure and Water Temperature

OTHER STANDARD FEATURES

- Hydrostatic Power Steering
- Hand Accelerator
- Forward And Reverse Foot Pedal
- Electric Fuel Shut-Off
- 12 Volt Electrical System
- Battery: 390 Cold Cranking Amps
- Full Adjustable Seat With Retractable Seat Belt
- 2 Post Fixed Rops
- Tilt-Up Hood
- Turn Signals, Flashers, Tail Lights
- Factory Joystick Optional
- Hydraulic Manifold with Pressure and Return Lines on Model with Factory Joystick

- **Note: 3-Point Backhoe Installation Voids Warranty**

IMPLEMENT FEATURES

MF DL95 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 1.6 inch Double Acting Lift Cylinders
- (2) 1.75 inch Double Acting Bucket Cylinders
- Regenerative Hydraulics for Simultaneous Operation of Lift/Lower and Curl/Dump Functions
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- 48-inch Standard Duty Pin-Type Bucket
- Grille Guard Standard
- Maximum Lift Height: 72.8 Inches
- Lift Capacity to Full Height @ 19.6 inches Forward of Pivot Pin: 580 lbs
- Breakout Force: 920 lbs
- Rated Hydraulic Pressure: 1914 PSI
- Fits all GC1700 Series Tractors

AVAILABLE ATTACHMENTS (REFER TO IMPLEMENT SECTIONS)

- MF 2315, 2320 and 2326 Mid Mounted Mowers
- MF 2360 Front Mounted Snow Blower
- MF 2330 Front Mounted Rotary Broom
- MF 2335 Front Mounted Blade
- MF 2340 Front Mounted Heavy Duty Blade

GC1705 GARDEN COMPACT



MASSEY FERGUSON*

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

**ORDER TRACTOR ONLY OR
TRACTOR AND LOADER BELOW
THEN ORDER ONE CODE FROM GROUP 03 THROUGH 04 AS REQUIRED**

BASE MACHINE

GROUP 01

MFGC1705		MFGC1705 Hydrostatic Base Tractor			
F-RE3	72530380	4wd Platform	65C8473		9,969.00
F-J-RE3	72530381	4wd Platform with Factory Joystick	90C9072		10,674.00

LOADER - For 4WD with Joystick Only

GROUP 02

	72533626	MFDL95 Loader Package Includes: Mount, Bucket, Hoses, Grille Guard	00C2397	486	2,820.00
--	----------	---	---------	-----	----------

NOTE: With addition of a Loader, the Model changes to MFGC1705L

*** ALL Tractors will be charged \$90 for Assembly**

**** ALL Tractor-Loader Packages will be charged a total \$150 for Assembly
(\$90 for Tractor and \$60 for Loader)**

TIRES & WHEELS - Choose only one set of Tires & Wheels

GROUP 03

NOTE: See Dealer / Field Installed Accessories for list of Tires & Wheels available as Loose Accessory orders. Tire and wheel options ordered with the tractor and not subject to availability can be returned via RGA. Contact Dealer Central with questions.

For Tractor or Tractor-Loader:

	72530281M	Front: 18x8.50-10 AG Rear: 26x12.00-12 AG	05C555	148	653.00
	72530282M	Front: 18x8.50-10 Turf Rear: 26x12.00-12 Turf	65C500	140	589.00
	72530283M	Front: 18x8.50-10 Industrial Rear: 26x12.00-12 Industrial	85C595		701.00

FRENCH OPERATOR'S MANUAL

GROUP 04

	72530175	French Operator's Manual			No Charge
--	----------	--------------------------	--	--	-----------



GC1710 TLB GARDEN COMPACT

MASSEY FERGUSON®

(F.O.B. Port of Entry)

TRACTOR FEATURES

POWER TRAIN

- Engine:
 - 22.5 Gross HP 3 Cyl Diesel 68.5 CID (1.1 L)
 - 22.0 Net HP @ 2600 RPM
 - 18.7 PTO HP @ 2600 RPM
- Dry Type Single Air Cleaner
- Transmission: 2 Range Hydrostatic with Cruise Control
- Wet Disk Brakes
- Parking Brake
- Differential Lock
- PTO: 540 RPM Independent PTO
2000 RPM Mid Independent PTO

HYDRAULIC SYSTEM

- 3-Point Hitch, Cat I With Directional Control,
 - Auto Return Lever System
- Engine Driven Gear Pump
- 3-Point Hitch 4.3 GPM (15.5 LPM)
- Power Steering 2.0 GPM (7.5 LPM)
- Total Combined Flow 6.3 GPM (23.1 LPM)

INSTRUMENTS

- Tachometer / Hourmeter
- Engine Coolant Gauge Fuel Gauge
- Warning Lights: Electrical Charging, Oil Pressure and Water Temperature

OTHER STANDARD FEATURES

- Hydrostatic Power Steering
- Hand Accelerator
- Forward And Reverse Foot Pedal
- Electric Fuel Shut-Off
- 12 Volt Electrical System
- Battery: 390 Cold Cranking Amps
- Full Adjustable Seat With Retractable Seat Belt
- 2 Post Folding Rops
- Tilt-Up Hood
- Turn Signals, Flashers, Tail Lights
- Factory Joystick
- Hydraulic Manifold with Pressure and Return Lines on Model with Factory Joystick

- **Note: 3-Point Backhoe Installation Voids Warranty**

IMPLEMENT FEATURES

MF DL95 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 1.6 inch Double Acting Lift Cylinders
- (2) 1.75 inch Double Acting Bucket Cylinders
- Regenerative Hydraulics for Simultaneous Operation of Lift/Lower and Curl/Dump Functions
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- 48-inch Standard Duty Pin-Type Bucket
- Grille Guard Standard
- Maximum Lift Height: 72.8 Inches
- Lift Capacity to Full Height @ 19.6 inches Forward of Pivot Pin: 580 lbs
- Breakout Force: 920 lbs
- Rated Hydraulic Pressure: 1914 PSI
- Fits all GC1700 Series Tractors

MF CB65 BACKHOE

- Digging Depth: 78 inch (2.0 m)
- Max Reach: 107 inch (2.7 m)
- Transport Height: 71 inches (1.8 m)
- Stabilizer Spread - Transport: 47 inch (1.2 m)
- Stabilizer Spread - Operating: 80 inch (2.0 m)
- Loading Height: 66 inch (1.7 m)
- Angle of Departure: 20 Degrees
- Swing Arc: 150 Degrees
- Bucket Rotation: 177 Degrees
- Shipping Weight: 635 lbs (288 kg)
- Digging Force Using Bucket Cylinder: 2476 lb (1123 kg)
- Digging Force Using Dipper Cylinder: 1748 lb (793 kg)
- Single Cylinder Boom Swing

NOTE: Dimensions may change due to tire size

AVAILABLE ATTACHMENTS (REFER TO IMPLEMENT SECTIONS)

- MF 2315, 2320, 2326 Mid Mounted Mowers
- MF 2360 Front Mounted Snow Blower
- MF 2330 Front Mounted Rotary Broom
- MF 2335 Front Mounted Blade
- MF 2340 Front Mounted Heavy Duty Blade

GC1710 TLB GARDEN COMPACT



MASSEY FERGUSON®

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

**ORDER TRACTOR, LOADER AND BACKHOE BELOW
THEN ORDER ONE CODE FROM GROUP 02 THROUGH 04 AS REQUIRED**

BASE MACHINE

GROUP 01

MFGC1710		MFGC1710 Hydrostatic Base Tractor Loader Backhoe			
F-J-LE3	72530382	4WD Platform Tractor with Joystick Includes DL95 Loader and CB65 Backhoe completely assembled	05C15906		18,713.00

TIRES & WHEELS

GROUP 02

NOTE: See Dealer / Field Installed Accessories for list of Tires & Wheels available as Loose Accessory orders. Tire and wheel options ordered with the tractor and not subject to availability can be returned via RGA. Contact Dealer Central with questions.

72530281M	Front: 18x8.50-10 AG Rear: 26x12.00-12 AG	05C555	148	653.00
72530282M	Front: 18x8.50-10 Turf Rear: 26x12.00-12 Turf	65C500	140	589.00
72530283M	Front: 18x8.50-10 Industrial Rear: 26x12.00-12 Industrial	85C595		701.00

BACKHOE OPTIONS

GROUP 03

72533783ML	10-inch Bucket with 2 Teeth	65C296		349.00
72533784ML	12-inch Bucket with 3 Teeth	00C340		400.00

FRENCH OPERATOR'S MANUAL

GROUP 04

72530175	French Operator's Manual			No Charge
----------	--------------------------	--	--	-----------



GC1715 GARDEN COMPACT

MASSEY FERGUSON®

(F.O.B. Port of Entry)

TRACTOR FEATURES

POWER TRAIN

- Engine:
 - 25.0 Gross HP 3 Cyl Diesel 68.5 CID (1.1 L)
 - 23.9 Net HP @ 3000 RPM
 - 19.6 PTO HP @ 3000 RPM
- Dry Type Single Air Cleaner
- Transmission: 2 Range Hydrostatic with Cruise Control
- Wet Disk Brakes
- Parking Brake
- Differential Lock
- PTO: 540 RPM Independent PTO
2000 RPM Mid Independent PTO

HYDRAULIC SYSTEM

- 3-Point Hitch, Cat I With Directional Control,
 - Auto Return Lever System
- Engine Driven Gear Pump
- 3-Point Hitch 4.8 GPM (15.5 LPM)
- Power Steering 2.0 GPM (7.5 LPM)
- Total Combined Flow 6.8 GPM (23.1 LPM)

INSTRUMENTS

- Tachometer / Hourmeter
- Engine Coolant Gauge Fuel Gauge
- Warning Lights: Electrical Charging and Oil Pressure and Water Temperature

OTHER STANDARD FEATURES

- Hydrostatic Power Steering
- Hand Accelerator
- Forward And Reverse Foot Pedal
- Electric Fuel Shut-Off
- 12 Volt Electrical System
- Battery: 390 Cold Cranking Amps
- Full Adjustable Seat With Retractable Seat Belt
- 2 Post Fixed ROPS
- Tilt-Up Hood
- Turn Signals, Flashers, Tail Lights
- Factory Joystick
- Hydraulic Manifold with Pressure and Return Lines on Model with Factory Joystick

- **Note: 3-Point Backhoe Installation Voids Warranty**

IMPLEMENT FEATURES

MF DL95 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 1.6 inch Double Acting Lift Cylinders
- (2) 1.75 inch Double Acting Bucket Cylinders
- Regenerative Hydraulics for Simultaneous Operation of Lift/Lower and Curl/Dump Functions
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- 48-inch Standard Duty Pin-Type Bucket
- Grille Guard Standard
- Maximum Lift Height: 72.8 Inches
- Lift Capacity to Full Height @ 19.6 inches Forward of Pivot Pin: 580 lbs
- Breakout Force: 920 lbs
- Rated Hydraulic Pressure: 1914 PSI
- Fits all GC1700 Series Tractors

AVAILABLE ATTACHMENTS (REFER TO IMPLEMENT SECTIONS)

- MF 2315, 2320 and 2326 Mid Mounted Mowers
- MF 2360 Front Mounted Snow Blower
- MF 2330 Front Mounted Rotary Broom
- MF 2335 Front Mounted Blade
- MF 2340 Front Mounted Heavy Duty Blade

GC1715 GARDEN COMPACT



MASSEY FERGUSON*

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

**ORDER TRACTOR ONLY OR
TRACTOR AND LOADER BELOW
THEN ORDER ONE CODE FROM GROUP 03 THROUGH 04 AS REQUIRED**

BASE MACHINE

GROUP 01

MFGC1715		MFGC1715 Hydrostatic Base Tractor			
F-J-RE3	72530383	4wd Platform with Factory Joystick	25C10255		12,065.00

LOADER

GROUP 02

	72533626	MFDL95 Loader Package Includes: Mount, Bucket, Hoses, Grille Guard	00C2397	486	2,820.00
--	----------	---	---------	-----	----------

NOTE: With addition of a Loader, the Model changes to MFGC1715L

*** ALL Tractors will be charged \$90 for Assembly**

**** ALL Tractor-Loader Packages will be charged a total \$150 for Assembly
(\$90 for Tractor and \$60 for Loader)**

TIRES & WHEELS - Choose only one set of Tires & Wheels

GROUP 03

NOTE: See Dealer / Field Installed Accessories for list of Tires & Wheels available as Loose Accessory orders. Tire and wheel options ordered with the tractor and not subject to availability can be returned via RGA. Contact Dealer Central with questions.

For Tractor or Tractor-Loader:

72530281M	Front: 18x8.50-10 AG Rear: 26x12.00-12 AG	05C555	148	653.00
72530282M	Front: 18x8.50-10 Turf Rear: 26x12.00-12 Turf	65C500	140	589.00
72530283M	Front: 18x8.50-10 Industrial Rear: 26x12.00-12 Industrial	85C595		701.00

FRENCH OPERATOR'S MANUAL

GROUP 04

72530175	French Operator's Manual			No Charge
----------	--------------------------	--	--	-----------



GC1720 TLB GARDEN COMPACT

TRACTOR LOADER BACKHOE

MASSEY FERGUSON®

(F.O.B. Port of Entry)

TRACTOR FEATURES

POWER TRAIN

- Engine:
 - 25.0 Gross HP 3 Cyl Diesel 68.5 CID (1.1 L)
 - 23.9 Net HP @ 3000 RPM
 - 19.6 PTO HP @ 3000 RPM
- Dry Type Single Air Cleaner
- Transmission: 2 Range Hydrostatic with Cruise Control
- Wet Disk Brakes
- Parking Brake
- Differential Lock
- PTO: 540 RPM Independent PTO
2000 RPM Mid Independent PTO

HYDRAULIC SYSTEM

- 3-Point Hitch Rockshaft with Control Valve
Category I Lower Draft Arms
- Engine Driven Gear Pump
- 3-Point Hitch 4.8 GPM (15.5 LPM)
- Power Steering 2.0 GPM (7.5 LPM)
- Total Combined Flow 6.8 GPM (23.1 LPM)

INSTRUMENTS

- Tachometer / Hourmeter
- Engine Coolant Gauge Fuel Gauge
- Warning Lights: Electrical Charging and Oil Pressure and Water Temperature

OTHER STANDARD FEATURES

- Hydrostatic Power Steering
- Hand Accelerator
- Side by Side Forward and Reverse Pedals
- Electric Fuel Shut-Off
- 12 Volt Electrical System
- Battery: 390 Cold Cranking Amps
- Full Adjustable Seat With Retractable Seat Belt
- 2 Post Folding Rops
- Tilt-Up Hood
- Turn Signals, Flashers, Tail Lights
- Factory Joystick
- Hydraulic Manifold with Pressure and Return Lines on Model with Factory Joystick

- **Note: 3-Point Backhoe Installation Voids Warranty**

IMPLEMENT FEATURES

MF DL95 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 1.6 inch Double Acting Lift Cylinders
- (2) 1.75 inch Double Acting Bucket Cylinders
- Regenerative Hydraulics for Simultaneous Operation of Lift/Lower and Curl/Dump Functions
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- 48-inch Standard Duty Pin-Type Bucket
- Grille Guard Standard
- Maximum Lift Height: 72.8 Inches
- Lift Capacity to Full Height @ 19.6 inches Forward of Pivot Pin: 580 lbs
- Breakout Force: 920 lbs
- Rated Hydraulic Pressure: 1914 PSI
- Fits all GC1700 Series Tractors

MF CB65 BACKHOE

- Digging Depth: 78 inch (2.0 m)
- Max Reach: 107 inch (2.7 m)
- Transport Height: 71 inches (1.8 m)
- Stabilizer Spread - Transport: 47 inch (1.2 m)
- Stabilizer Spread - Operating: 80 inch (2.0 m)
- Loading Height: 66 inch (1.7 m)
- Angle of Departure: 20 Degrees
- Swing Arc: 150 Degrees
- Bucket Rotation: 177 Degrees
- Shipping Weight: 635 lbs (288 kg)
- Digging Force Using Bucket Cylinder: 2476 lb (1123 kg)
- Digging Force Using Dipper Cylinder: 1748 lb (793 kg)
- Single Cylinder Boom Swing

NOTE: Dimensions may change due to tire size

AVAILABLE ATTACHMENTS (REFER TO IMPLEMENT SECTIONS)

- MF 2315, 2320, 2326 Mid Mounted Mowers
- MF 2360 Front Mounted Snow Blower
- MF 2330 Front Mounted Rotary Broom
- MF 2335 Front Mounted Blade
- MF 2340 Front Mounted Heavy Duty Blade

GC1720 TLB GARDEN COMPACT



MASSEY FERGUSON*

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

**ORDER TRACTOR, LOADER AND BACKHOE BELOW
THEN ORDER ONE CODE FROM GROUP 02 THROUGH 04 AS REQUIRED**

BASE MACHINE

GROUP 01

MFGC1720		MFGC1720 Hydrostatic Base Tractor Loader Backhoe			
F-J-LE3	72530384	4WD Platform Tractor with Joystick Includes DL95 Loader and CB65 Backhoe completely assembled	05C17538		20,633.00

TIRES & WHEELS

GROUP 02

NOTE: See Dealer / Field Installed Accessories for list of Tires & Wheels available as Loose Accessory orders. Tire and wheel options ordered with the tractor and not subject to availability can be returned via RGA. Contact Dealer Central with questions.

72530281M	Front: 18x8.50-10 AG Rear: 26x12.00-12 AG	05C555	148	653.00
72530282M	Front: 18x8.50-10 Turf Rear: 26x12.00-12 Turf	65C500	140	589.00
72530283M	Front: 18x8.50-10 Industrial Rear: 26x12.00-12 Industrial	85C595		701.00

BACKHOE OPTIONS

GROUP 03

72533783ML	10-inch Bucket with 2 Teeth	65C296		349.00
72533784ML	12-inch Bucket with 3 Teeth	00C340		400.00

FRENCH OPERATOR'S MANUAL

GROUP 04

72530175	French Operator's Manual			No Charge
----------	--------------------------	--	--	-----------



MASSEY FERGUSON®

RESERVED

MF 1726E



(F.O.B. Port of Entry)

MASSEY FERGUSON®

TRACTOR FEATURES

POWER TRAIN

- Shibaura Engine:
 - 24.0 Gross HP 3-Cylinder Liquid-Cooled Diesel Turbo Charged (91.5 Cu. In.)
 - 20.4 PTO HP @ 2600 RPM - Gear
 - 19.2 PTO HP @ 2600 RPM - Hydrostatic
 - Emission Standard Category: Tier 4
- Single Stage, Dry Element Type Air Cleaner
- Transmission:
 - 9F / 3R Speeds Gear Transmission
 - Hydrostatic: 3 Non-Synchronized Ranges
- Sealed Wet Disc Brakes
- Pedal Operated Rear Differential Lock
- PTO:
 - Rear - 540 RPM Transmission Driven PTO with Overrunning Clutch
 - Not Mid PTO Capable

HYDRAULIC SYSTEM

- 3-Point Hitch Cat I with Position Control
- Lift Capacity @ Hitch Point: 2205 lbs (1000 kg) @ 24 inches: 1600 lbs (725 kg)
- Dual Engine Driven Gear Pump
- Flow at Remotes 6.7 GPM (25.5 LPM)
- Power Steering Pump 3.8 GPM (14.4 LPM)
- Total Combined Flow 10.5 GPM (39.9 LPM)
- Can Support up to 2 Rear Remote Valves (Optional, Dealer Installed)

INSTRUMENTS

- Tachometer and Hour Meter
- Temperature and Fuel Gauges
- Warning Lights: High Beam Indicator, Engine Oil Pressure, PTO Engagement, Battery Charge (alt) Indicator, Glow Plug Indicator and Flasher Indicators
- Key Operated Electronic Fuel Shutoff and Glow Plug Control
- Regen Lights

OTHER STANDARD FEATURES

- Steel Tilt-up Hood
- Adjustable Spring Suspension Seat
- 2 Post Folding ROPS and Retractable Seat Belt
- Turn Signals, Flashers, Tail Lights and SMV Emblem
- 2 Headlights

- **Note: 3-Point Backhoe Installation Voids Warranty**

IMPLEMENT FEATURES

MF L105E LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 2.0 inch Double Acting Lift Cylinders
- (2) 2.2 inch Double Acting Bucket Cylinders
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- Skid Steer or Pin-Type Implement Attachments
- Grille Guard Standard
- Fits all MF1700E Series Economy Compact Tractor Models with R1 AG, R3 Turf or R4 Industrial Tires
- Maximum Lift Height: 95.7 inches at Pivot
- Lift Capacity to Full Height @ 19.6 inches Forward of Pivot Pin: 830 lbs
- Breakout Force: 1460 lbs
- Rated Hydraulic Pressure: 2132 PSI



MF 1726E

MASSEY FERGUSON®

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

**ORDER TRACTOR ONLY OR
TRACTOR AND LOADER BELOW
THEN ORDER ONE CODE FROM GROUP 03 THROUGH 05 AS REQUIRED**

BASE MACHINE

GROUP 01

MF1726E		MF1726E Base Tractor			
F-RE3	72530407	4wd Platform Gear 9x3 Transmission	55C11273		13,263.00
MF1726EH		MF1726EH Base Tractor			
F-H-RE3	72530408	4wd Platform Hydrostatic Transmission	80C12416		14,608.00

LOADER

GROUP 02

	72533739	MFL105E Loader Package Includes: Mounting Kit with Joystick and Grille Guard	90C3309		3,894.00
--	----------	---	---------	--	----------

NOTE: With addition of a Loader, the Model changes to MF1726EL and MF1726EHL

- * ALL Tractors will be charged \$250 for Assembly
- * ALL Tractor-Loader Packages will be charged \$360 for Assembly

MF 1726E



MASSEY FERGUSON®

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
<u>TIRES & WHEELS - Required</u>					<u>GROUP 03</u>
		AG Tires Options			
	72530436	Front: 7-16 6PR R1 Rear: 11.2 x 24 4PR R1 Adjustable	25C1432		1,685.00
		Turf Tires Options			
	72530253	Front: 27 x 8.50-15 4PR Rear: 38 x 14.00-20 4PR	30C1324		1,558.00
		Industrial Tires Options			
	72530254	Front: 27 x 8.50-15 6PR SS Rear: 15 x 19.5 6PR SS	60C1492		1,756.00
<u>BUCKET OPTIONS - Required with Loader Packages</u>					<u>GROUP 04</u>
	72533678ML	60-inch Skid Steer Type Material Bucket (Requires 72533709M Quick Attach Tool Carrier Kit)	50C552		650.00
	72533675ML	60-inch Pin Type Material Bucket	50C552		650.00
<u>LOADER ACCESSORIES - The Skid Steer Quick Attach is Required with the Skid Steer Bucket</u>					<u>GROUP 05</u>
	72533709ML	Skid Steer Type Bucket Quick Attach Tool Carrier Kit	35C468		551.00



MF 1734E

MASSEY FERGUSON®

(F.O.B. Port of Entry)

TRACTOR FEATURES

POWER TRAIN

- Shibaura Engine:
 - 34.0 Gross HP 3-Cylinder Liquid-Cooled Diesel Turbo Charged (91.5 Cu. In.)
 - 29.0 PTO HP @ 2600 RPM - Gear
 - 27.2 PTO HP @ 2600 RPM - Hydrostatic
 - Emission Standard Category: Tier 4
- Single Stage, Dry Element Type Air Cleaner
- Transmission:
 - 9F / 3R Speeds Gear Transmission
 - Hydrostatic: 3 Non-Synchronized Ranges
- Sealed Wet Disc Brakes
- Pedal Operated Rear Differential Lock
- PTO:
 - Rear - 540 RPM Transmission Driven PTO with Overrunning Clutch
 - Not Mid PTO Capable

HYDRAULIC SYSTEM

- 3-Point Hitch Cat I with Position Control
- Lift Capacity @ Hitch Point: 2205 lbs (1000 kg)
 - @ 24 inches: 1600 lbs (725 kg)
- Dual Engine Driven Gear Pump
- Flow at Remotes 6.7 GPM (25.5 LPM)
- Power Steering Pump 3.8 GPM (14.4 LPM)
- Total Combined Flow 10.5 GPM (39.9 LPM)
- Can Support up to 2 Rear Remote Valves (Optional, Dealer Installed)

INSTRUMENTS

- Tachometer and Hour Meter
- Temperature and Fuel Gauges
- Warning Lights: High Beam Indicator, Engine Oil Pressure, PTO Engagement, Battery Charge (alt) Indicator, Glow Plug Indicator and Flasher Indicators
- Key Operated Electronic Fuel Shutoff and Glow Plug Control
- Regen Lights

OTHER STANDARD FEATURES

- Steel Tilt-up Hood
- Adjustable Spring Suspension Seat
- 2 Post Folding ROPS and Retractable Seat Belt
- Turn Signals, Flashers, Tail Lights and SMV Emblem
- 2 Headlights

- **Note: 3-Point Backhoe Installation Voids Warranty**

IMPLEMENT FEATURES

MF L105E LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 2.0 inch Double Acting Lift Cylinders
- (2) 2.2 inch Double Acting Bucket Cylinders
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- Skid Steer or Pin-Type Implement Attachments
- Grille Guard Standard
- Fits all MF1700E Series Economy Compact Tractor Models with R1 AG, R3 Turf or R4 Industrial Tires
- Maximum Lift Height: 95.7 inches at Pivot
- Lift Capacity to Full Height @ 19.6 inches Forward of Pivot Pin: 830 lbs
- Breakout Force: 1460 lbs
- Rated Hydraulic Pressure: 2132 PSI

MF 1734E



MASSEY FERGUSON®

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

**ORDER TRACTOR ONLY OR
TRACTOR AND LOADER BELOW
THEN ORDER ONE CODE FROM GROUP 03 THROUGH 05 AS REQUIRED**

BASE MACHINE

GROUP 01

MF1734E		MF1734E Base Tractor			
F-RE3	72530356	4wd Platform Gear 9x3 Transmission	45C13274		15,617.00
MF1734EH		MF1734EH Base Tractor			
F-H-RE3	72530355	4wd Platform Hydrostatic Transmission	70C14417		16,962.00

LOADER

GROUP 02

	72533739	MFL105E Loader Package Includes: Mounting Kit with Joystick and Grille Guard	90C3309		3,894.00
--	----------	---	---------	--	----------

NOTE: With addition of a Loader, the Model changes to MF1734EL and MF1734EHL

- * ALL Tractors will be charged \$250 for Assembly
- * ALL Tractor-Loader Packages will be charged \$360 for Assembly



MF 1734E

MASSEY FERGUSON®

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
<u>TIRES & WHEELS - Required</u>					<u>GROUP 03</u>
		AG Tires Options			
	72530436	Front: 7-16 6PR R1 Rear: 11.2 x 24 4PR R1 Adjustable	25C1432		1,685.00
		Turf Tires Options			
	72530253	Front: 27 x 8.50-15 4PR Rear: 38 x 14.00-20 4PR	30C1324		1,558.00
		Industrial Tires Options			
	72530254	Front: 27 x 8.50-15 6PR SS Rear: 15 x 19.5 6PR SS	60C1492		1,756.00
<u>BUCKET OPTIONS - Required with Loader Packages</u>					<u>GROUP 04</u>
	72533678ML	60-inch Skid Steer Type Material Bucket (Requires 72533709M Quick Attach Tool Carrier Kit)	50C552		650.00
	72533675ML	60-inch Pin Type Material Bucket	50C552		650.00
<u>LOADER ACCESSORIES - The Skid Steer Quick Attach is Required with the Skid Steer Bucket</u>					<u>GROUP 05</u>
	72533709ML	Skid Steer Type Bucket Quick Attach Tool Carrier Kit	35C468		551.00

MF 1739E



(F.O.B. Port of Entry)

MASSEY FERGUSON®

TRACTOR FEATURES

POWER TRAIN

- Shibaura Engine:
 - 38.5 Gross HP 3-Cylinder Liquid-Cooled Diesel Turbo Charged (91.5 Cu. In.)
 - 32.7 PTO HP @ 2600 RPM - Gear
 - 30.9 PTO HP @ 2600 RPM - Hydrostatic
 - Emission Standard Category: Tier 4
- Single Stage, Dry Element Type Air Cleaner
- Transmission:
 - 9F / 3R Speeds Gear Transmission
 - Hydrostatic: 3 Non-Synchronized Ranges
- Sealed Wet Disc Brakes
- Pedal Operated Rear Differential Lock
- PTO:
 - Gear: Rear - 540 RPM Independent PTO
 - HST: Rear - 540 RPM Transmission Driven PTO with Overrunning Clutch
 - Not Mid PTO Capable

HYDRAULIC SYSTEM

- 3-Point Hitch Cat I with Position Control
- Lift Capacity @ Hitch Point: 2205 lbs (1000 kg)
 - @ 24 inches: 1600 lbs (725 kg)
- Flow at Remotes 7.2 GPM (27.3 LPM)
- Power Steering Pump 4.1 GPM (15.4 LPM)
- Total Combined Flow 11.3 GPM (42.7 LPM)
- Can Support up to 2 Rear Remote Valves (Optional, Dealer Installed)

INSTRUMENTS

- Tachometer and Hour Meter
- Temperature and Fuel Gauges
- Warning Lights: High Beam Indicator, Engine Oil Pressure, PTO Engagement, Battery Charge (alt) Indicator, Glow Plug Indicator and Flasher Indicators
- Key Operated Electronic Fuel Shutoff and Glow Plug Control
- Regen Lights

OTHER STANDARD FEATURES

- Steel Tilt-up Hood
- Adjustable Spring Suspension Seat
- 2 Post Folding ROPS and Retractable Seat Belt
- Turn Signals, Flashers, Tail Lights and SMV Emblem
- 2 Headlights

- **Note: 3-Point Backhoe Installation Voids Warranty**

IMPLEMENT FEATURES

MF L105E LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 2.0 inch Double Acting Lift Cylinders
- (2) 2.2 inch Double Acting Bucket Cylinders
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- Skid Steer or Pin-Type Implement Attachments
- Grille Guard Standard
- Fits all MF1700E Series Economy Compact Tractor Models with R1 AG, R3 Turf or R4 Industrial Tires
- Maximum Lift Height: 95.7 inches at Pivot
- Lift Capacity to Full Height @ 19.6 inches Forward of Pivot Pin: 830 lbs
- Breakout Force: 1460 lbs
- Rated Hydraulic Pressure: 2132 PSI



MF 1739E

MASSEY FERGUSON*

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

**ORDER TRACTOR ONLY OR
TRACTOR AND LOADER BELOW
THEN ORDER ONE CODE FROM GROUP 03 THROUGH 05 AS REQUIRED**

BASE MACHINE

GROUP 01

MF1739E		MF1739E Base Tractor			
F-G-RE3	72530357	4wd Platform Gear 9x3 Transmission	60C15075		17,736.00
MF1739EH		MF1739EH Base Tractor			
F-H-RE3	72530358	4wd Platform Hydrostatic Transmission	85C16218		19,081.00

LOADER

GROUP 02

	72533739	MFL105E Loader Package Includes: Mounting Kit with Joystick and Grille Guard	90C3309		3,894.00
--	----------	---	---------	--	----------

NOTE: With addition of a Loader, the Model changes to MF1739EL and MF1739EHL.

- * ALL Tractors will be charged \$250 for Assembly
- * ALL Tractor-Loader Packages will be charged \$360 for Assembly

MF 1739E



MASSEY FERGUSON®

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

TIRES & WHEELS - Required

GROUP 03

AG Tires Options

72530436	Front: 7-16 6PR R1 Rear: 11.2 x 24 4PR R1 Adjustable	25C1432	1,685.00
----------	---	---------	----------

Turf Tires Options

72530253	Front: 27 x 8.50-15 4PR Rear: 38 x 14.00-20 4PR	30C1324	1,558.00
----------	--	---------	----------

Industrial Tires Options

72530254	Front: 27 x 8.50-15 6PR SS Rear: 15 x 19.5 6PR SS	60C1492	1,756.00
----------	--	---------	----------

BUCKET OPTIONS - Required with Loader Packages

GROUP 04

72533678ML	60-inch Skid Steer Type Material Bucket (Requires 72533709M Quick Attach Tool Carrier Kit)	50C552	650.00
72533675ML	60-inch Pin Type Material Bucket	50C552	650.00

LOADER ACCESSORIES - The Skid Steer Quick Attach is Required with the Skid Steer Bucket

GROUP 05

72533709ML	Skid Steer Type Bucket Quick Attach Tool Carrier Kit	35C468	551.00
------------	--	--------	--------



MASSEY FERGUSON®

RESERVED

MF 1736



(F.O.B. Port of Entry)

MASSEY FERGUSON®

TRACTOR FEATURES

POWER TRAIN

- Engine:
 - 36.2 Rated HP Mitsubishi 3-Cylinder liquid cooled Diesel, 1.7L (101 cu in) Direct Injection, Turbocharged and Intercooled, Electronic Engine Control
 - 27.5 PTO HP @ 2500 RPM - Shuttle
 - 26.3 PTO HP @ 2500 RPM - Hydrostatic
 - Emission Standard Category: Tier 4
- Dual Element Dry Type Air Cleaner
- Transmission:
 - 12F/12R Power Shuttle with 4 Synchronized Gears and 3 Ranges.
- Servo-HST Electronic Hydrostatic Transmission with 3 Ranges, Cruise Control, Stall Guard, Max Speed Control and Response Control
- Sealed Wet Disc Brakes
- Pedal Operated Rear Differential Lock
- PTO:
 - Rear - 540 RPM Independent Electro Hydraulic
 - Mid - Optional 2000 RPM Independent

HYDRAULIC SYSTEM

- 3-Point Hitch Cat I with Position Control Standard, Draft Control Optional
- Lift Capacity @ 24 inches - 2,535 lb (1150 kg)
- Telescopic Stabilizers
- Telescopic Draft Link Ends
- Dual Engine Driven Gear Pump
- Flow at Remotes 11.6 GPM (43.8 LPM)
- Hydrostatic Power Steering
- One Rear Remote Valve Standard on Cab Models, up to 3 Possible. Loader Joystick Standard

INSTRUMENTS

- Combination Digital and Analog Front Dash Display
- Tachometer and Hour Meter
- Temperature and Fuel Gauges
- Warning Lights: High Beam Indicator, Engine Oil Pressure, PTO Engagement, Battery Charge (alt) Indicator, Glow Plug Indicator and Flasher Indicators
- Key Operated Electronic Fuel Shutoff and Glow Plug Control

OTHER STANDARD FEATURES

- ISO Mounted Flat Platform w/ Molded Rubber Floor Mat
- One Piece Tilt-up Hood
- 3 Position Tilt Steering
- Deluxe Adjustable Suspension Seat with Arm Rest
- 2 Post Folding ROPS and Retractable Seat Belt
- Turn Signals, Flashers, Tail Lights and SMV Emblem
- 4 Headlights

CAB FEATURES

- Heating and Air Conditioning
- Wired for Radio and Speakers
- Front and Rear Wiper / Washer
- 2 Front Work Lights
- 2 Rear Work Lights
- Rear and Side opening Windows
- Right and Left Entry Doors
- Right and Left External Mirrors
- Deluxe Digital Display with Ground Speed, Engine Coolant, Temperature, Fuel Level & Diagnostic Readout
- ROPS Certified
- Recirculation Filter

• **Note: 3-Point Backhoe Installation Voids Warranty**

• **Note: MF1736L with 4238082 MFDL120 Loader package is Not Compatible with MF1705 Mid Mount Mower; however, it is Compatible with MFDL125 Loader package with Industrial R4 Tire 7496747M Only.**

IMPLEMENT FEATURES

MF DL125 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 2.4 inch Double Acting Lift Cylinders
- (2) 2.4 inch Double Acting Bucket Cylinders
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- 3rd Function Capable, Soft-Drive Capable
- Galvanized Steel Bushings with Recessed Grease Points
- Universal Skid Steer Implement Attachment
- Grille Guard Standard
- Fits MF1736 and MF1742 Compact Tractor Models with R1 AG, R3 Turf, or R4 Industrial Tires
- Maximum Lift Height: 102.4 Inches at Pivot
- Lift Capacity to Full Height @ 19.6 inches Forward of Pivot Pin: 1300 lbs
- Breakout Force: 2190 lbs
- Rated Hydraulic Pressure: 2277 PSI



MF 1736

MASSEY FERGUSON®

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

**ORDER TRACTOR ONLY OR
TRACTOR AND LOADER BELOW
THEN ORDER ONE CODE FROM GROUP 03 THROUGH 04 AS REQUIRED**

<u>BASE MACHINE</u>				<u>GROUP 01</u>
MF1736		MF1736 Power Shuttle Tractor		
F-P-RE3-J	72530286	4wd Platform Power Shuttle 12x12 Factory Installed Joystick with Mid-Coupler	90C17912	21,074.00
F-P-V-CYE3-J	72530288	4wd Cab Power Shuttle 12x12 with 1 Rear Remote and Factory Installed Joystick with Mid-Coupler	25C24467	28,785.00
MF1736H		MF1736 Hydrostatic Tractor		
F-H-RE3-J	72530287	4wd Platform HST with Factory Installed Joystick with Mid-Coupler	10C18484	21,746.00
F-H-V-CYE3-J	72530289	4wd Cab HST with Factory Installed 1 Rear Remote and Factory Installed Joystick with Mid-Coupler	30C25039	29,458.00
<u>LOADER</u>				<u>GROUP 02</u>
	72533740	MFDL125 Loader Package, Skid Steer Attach Includes: Mounting Kit, Grille Guard, and Hose Kit	50C3612	4,250.00

NOTE: With addition of a Loader, the Model changes to MF1736L and MF1736HL

*** ALL Tractors will be charged \$250 for Assembly**

**** ALL Tractor-Loader Packages will be charged \$360 for Assembly**

MF 1736



MASSEY FERGUSON*

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

TIRES & WHEELS - Required

GROUP 03

NOTE: See Dealer / Field Installed Accessories for list of Tires & Wheels available as Loose Accessory orders. Tire and wheel options ordered with the tractor and not subject to availability can be returned via RGA. Contact Dealer Central with questions.

AG Tires Options					
7496701M		Front: 8-16 6 PR R1 HTL Rear: 12.4x24 6 PR R1 HTL Adjustable (Subject to Availability)	20C1710		2,012.00
7140701M		Front: 8-16 6 PR R1 HTL Rear: 13.6x24 6 PR R1 HTL Adjustable	20C1795		2,112.00
Turf Tires Options					
7496723M		Front: 27x8.50-15 4 PR MT Rear: 41x14.00-20 4 PR MT (Subject to Availability)	30C1324		1,558.00
Industrial Tires Options					
7496745M		Front: 10-16.5 6 PR SS TL Rear: 14.9-24 6 PR R4 Adjustable	80C1859		2,188.00
7498710M		Front: 10-16.5 6 PR Rear: 17.5L-24 6P R4 Adjustable	75C2069		2,435.00
7496747M		Front: 25x8.5-14 6PR SS Rear: 15x19.5 6PR SS	60C1492		1,756.00

BUCKET OPTIONS - Required with Loader Packages

GROUP 04

72533679ML	66-inch Skid Steer Bucket	00C765	900.00
72533680ML	72-inch Skid Steer Bucket	50C807	950.00

MF 1526



(F.O.B. Port of Entry)

MASSEY FERGUSON®

FEATURES

POWER TRAIN

- Engine:
 - 24.8 Gross HP 3 Cyl Diesel
 - 24.6 Net HP @ 2600 RPM
 - 20.1 PTO HP @ 2600 RPM - Hydro
 - Dry Single Element Air Cleaner
 - Emission Standard Category:
Tier 4i
- Transmission:
 - Hydrostatic: with 3 Non-Synchronized Ranges and Cruise Control with Auto-Throttle Control
- Wet Disc Brakes, Parking Brake
- Differential lock: Foot Pedal Operated
- PTO:
 - Rear - 540 RPM Independent Electro Hydraulic
 - Mid - Optional 2000 RPM Independent

INSTRUMENTS:

- Tachometer and hour Meter
- Temperature and Fuel Gauges
- Warning Lights: High Beam indicator, Battery Charge (alt) Indicator and Flasher Indicators
- Key operated electronic Fuel Shutoff and Glow Plug Control

OTHER STANDARD FEATURES:

- Turn Signals, Flashers, Tail Lights SMV Emblem
- Turn Buckle Stabilizers
- Hydrostatic Power Steering
- Foot Accelerator
- Hand Accelerator
- 2 post folding Rops and retractable Seat Belt
- Removable Side Panels
- Side Shift Control Levers
- Adjustable Suspension Seat with Arm Rests
- Tilt Hood

HYDRAULIC SYSTEM:

- 3-Point hitch Cat I with Position and Response Control
- Lift Capacity @ Hitch Point: 1323 lbs
- Dual Engine Driven Gear Pumps
- Flow @ Remotes 5.5 GPM (20.9 LPM)
- Power Steering Pump 3.3 GPM (12.3 LPM)
- Total Combined 10.6 GPM (41.0 LPM)
- Can Support Single Rear Remote Valve (Optional, Field Installed)

- **Note: 3-Point Backhoe Installation Voids Warranty**

IMPLEMENT FEATURES

MF L90 LOADER

- One Piece Main Frame Arms and Cross Member
- Pedestal Mount Quick Attach with Safety Lock
- 3/16" Tapered Box Section Frame
- 2" Double Acting Lift Cylinders
- 1-1/2" Double Acting Bucket Cylinders
- Plated Steel Hydraulic Lines
- Bucket Level Indicator Standard
- Standard Grille Guard
- Fits MF1526 with AG, Turf, or R4 Tires
- With MF1526
 - 90.5" Lift Height
 - 823 lbs. Lift Capacity to Full Height @ Pivot Pin
 - 594 lbs. Lift Capacity to full height @ 19.5" forward of Pivot Pin



MF 1526

MASSEY FERGUSON®

Order Code	Catalog Number	Description	Factory Code	Approx. Weight	List Price
------------	----------------	-------------	--------------	----------------	------------

**ORDER TRACTOR ONLY OR
TRACTOR AND LOADER BELOW
THEN ORDER ONE CODE FROM GROUP 03 THROUGH 05 AS REQUIRED**

BASE MACHINE

GROUP 01

MF1526H		MF1526 Hydrostatic Base Tractor			
F-H-RE3	72530241	4wd Platform with Hydrostatic Transmission	40C11903		14,004.00

LOADER

GROUP 02

	4238074	MFL90 Loader Package Includes: Mounting Kit and Loader Pedestal Mounted Valve	20C2900		3,412.00
--	---------	---	---------	--	----------

NOTE: With addition of a Loader, the Model changes to MF1526HL

*** ALL Tractors will be charged \$210 for Assembly**

*** ALL Tractor-Loader Packages will be charged a total \$320 for Assembly
(\$210 for Tractor and \$110 for Loader)**

TIRES & WHEELS - Required

GROUP 03

		Ag Tires Options			
	72530372M	Front: 7-12 4PR Dyna Torq II Rear: 35x12.00-16.5 4PR Tru Power	60C1101		1,296.00
	72530242M	Front: 7-12 4 PR Tru Power Rear: 9.5-16 6 PR Hi Traction Lug	60C914		1,076.00
		Turf Tires Option			
	72530371M	Front: 25x8.50-14 4PR M-T Rear: 36x13.50-15 4PR M-T	15C1053		1,239.00
		Industrial Tires Option			
	72530370M	Front: 25x8.50-14 6PR SS Rear: 14-17NHS 6PR SS	25C1364		1,605.00

BUCKET OPTIONS - Required with Loader Packages

GROUP 04

	9181710ML	48 Inch Combination Bucket	50C450	134	530.00
	5979712ML	54 Inch Combination Bucket	90C521	150	614.00
	5979711ML	60 Inch Combination Bucket	70C511	157	602.00

LOADER ACCESSORIES - Quick Attach can be Ordered with Bucket

GROUP 05

	9181908ML	Bucket Quick Attach Kit with Pin Lock Allows Fast Interchange of Buckets and Other Accessories without the use of Tools	85C221	31	261.00
--	-----------	---	--------	----	--------