CONSTRUCTION EQUIPMENT

U.S. PRICE LIST

EXCAVATORS

PL-200 CX SAP REVISION 13b

EFFECTIVE MAY 13, 2013 REVISED JUNE 20, 2013

THIS IS AN ELECTRONIC COPY ONLY - HARD COPIES WILL NOT BE DISTRIBUTED.

This price list is intended for dealers with the Excavators (CX) contract only.

The prices included in this revision supersede any prices established prior to the effective date shown unless specifically identified in a price bulletin as superseding this price list.

Below is a list of Family(s) and Model(s) that are included in this price list.

Crawler Excavator (Midi) CX75C Tier 4 Final CX80C Tier 4 Final

Crawler Excavator (Conventional)

CX130C Tier 4 Interim
CX145C MSR Tier 4 Interim
CX160C Tier 4 Interim
CX470C Tier 4 Interim
CX470C Tier 4 Interim

CX210C Tier 4 Interim CX700B CX235C MSR Tier 4 Interim CX800B

CX250C Tier 4 Interim

PLEASE NOTE: Retain the price book pages of the discontinued series for your records.

Copyright 2013 By

CNH America LLC



General Information

Prices shown herein are suggested prices only and in no way are they to be construed as limiting or restricting the dealer in his determination of the ultimate retail selling price. It is understood that the dealers are free to determine their selling price. Subject to any Federal, State or local laws.

Where shown herein liquid capacities are U.S. measure unless otherwise noted.

ADVANCE FREIGHT

Advance freight will be added to the machinery invoice as a separate net charge for machinery shipped from field locations or from other than specified Ex Works locations.

PRICES

Prices are Ex Works factory, where the goods are manufactured, except where noted. For detailed information concerning prices, please refer to your OPERATING GUIDE.

Prices and specifications are subject to change without notice.

CONTENTS OF ORGANIZATION

Case Construction Equipment Inc issues price lists and revisions covering each Case contract. U.S. Price List is published in U.S. funds. Canadian Price List is published in Canadian funds. Assure that you are using the correct price list. The Canadian price lists are denoted by a Maple Leaf on the price list cover page and the symbol "(CDN)" is printed at the head of the Factory Supplied Attachments List columns.

Freight, duty and sales taxes are NOT included in any wholegoods or attachment prices shown in the price list. Any appropriate freight, duty, Federal, State, and Provincial taxes will be added to the machinery invoice as separate net charges.

PROCEDURE

The price pages for each machine (or group of machines) lists both "Factory" and "Factory Supplied Attachments".

Each price list is comprised of the various machines sold under that contract. Each price book section has "Factory", "Factory Supplied Attachments", or "Third Party Supplied Attachments" pages. When ordering and pricing a machine follow the ordering instructions listed for that machine. Attachments listed following the "Factory Supplied Attachments" or "Third Party Supplied Attachments" heading are available for installation in the field.

ATTACHMENTS

Expect Attachments to be shipped within 2 -3 weeks from order entry.



General Information

DISTRIBUTION OF PRICE LISTS / REQUESTS FOR ADDITIONAL COPIES

Price lists will be provided electronically via that Dealer Portal.

Contact information for additional copies of Case Construction Equipment Price Lists

Additional price lists, divider tabs and binders may be ordered at the Document Management Center. From Dealer Portal click on Tools then Document Management Center link. Any questions you can call the Document Management Center at 262-636-7540

You will only receive price lists for contracts covered by your current Dealer Agreement with the Company.

The revisions are dated and are effective as of that date. However, PRICES ARE SUBJECT TO CHANGE WITHOUT NOTICE.



EXCAVATORS TABLE OF CONTENTS

CX SERIES EXCAVATORS CX75C MINIMUM SWING RADIUS CRAWLER EXCAVATOR EX-07 Standard Features Price List EX-09 Factory Supplied Accessories EX-15 CX80C CRAWLER EXCAVATOR Standard Features EX-17 Price List EX-19 Factory Supplied Accessories EX-25 CX130C STANDARD EXCAVATOR Standard Features EX-27 Price List EX-29 Factory Supplied Accessories EX-35 CX145C MINIMUM SWING RADIUS CRAWLER EXCAVATOR Standard Features EX-37 Price List EX-39 Factory Supplied Accessories EX-47 CX160C CRAWLER EXCAVATOR Standard Features EX-49 Price List EX-51 EX-57 Factory Supplied Accessories CX210C CRAWLER EXCAVATOR Standard Features EX-59 Price List EX-61 Factory Supplied Accessories EX-67 CX210C LR CRAWLER EXCAVATOR Standard Features EX-69 FX-71 Price List Factory Supplied Accessories EX-75 CX235C MINIMUM SWING RADIUS CRAWLER EXCAVATOR Standard Features EX-77 EX-79 Price List Factory Supplied Accessories EX-85 CX250C STD CRAWLER EXCAVATOR Standard Features EX-87 Price List EX-89 Factory Supplied Accessories EX-95 CX250C LR CRAWLER EXCAVATOR EX-97 Standard Features Price List EX-99 Factory Supplied Accessories EX-103 CX300C CRAWLER EXCAVATOR Standard Features EX-105 Price List EX-107

EX-113

Factory Supplied Accessories



EXCAVATORS TABLE OF CONTENTS

| CX350C EXCAVATOR | |
|-------------------------------|--------|
| Standard Features | EX-115 |
| Price List | EX-117 |
| Factory Supplied Accessories | EX-123 |
| CX470C CRAWLER EXCAVATOR | |
| Standard Features | EX-125 |
| Price List | EX-127 |
| Factory Supplied Accessories | EX-133 |
| CX470C MASS CRAWLER EXCAVATOR | |
| Standard Features | EX-135 |
| Price List | EX-137 |
| CX700B CRAWLER EXCAVATOR | |
| Standard Features | EX-143 |
| Price List | EX-145 |
| Factory Supplied Accessories | EX-151 |
| CX800B CRAWLER EXCAVATOR | |
| Standard Features | EX-153 |
| Price List | EX-155 |
| Factory Supplied Accessories | EX-161 |



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AP-4LE2X turbocharged
Tier 4 Final Certified
4 Cylinder liquid cooled diesel
High Pressure Common Rail
Cooled EGR with variable controlled
valve
DOC - diesel oxidation catalyst

133 cu. in. (2.2 liter) displacement Horsepower:

- Net (SAE) 55.2 (41.2kw) at 2000 RPM

Fuel Tank Capacity: 31.7 gal. (US) Long Life Anti-freeze (protect to -34°F)

OPERATOR'S CAB:

4-point iso-mounted ROPS cab

Pressurized cab

- Climate control: AC/Heat/Defrost
- Fully adjustable deluxe seat with 3" seat-belt
- AM/FM radio with dual speakers
- Floor mats
- 12-volt outlet
- In-cab light

Cab roof skylight

Safety glass:

- Two-piece front window
- Front windshield wiper with washer

Waterproof/illuminated membrane

switches

Low-effort pilot controls

Full-color LCD display - rearview

camera ready

Dial type throttle control for engine

speed

Work mode selector: SP, H, Auto

One-touch idle

Programmable anti-theft protection

ELECTRICAL:

24 Volt system
Alternator: 50 AMP
Batteries: 2

BLADE:

CX75C W/DOZER BLADE ONLY
Hydraulically controlled dozer blade

- Blade width: 7'7"
- Blade height: 1'6"

UPPER STRUCTURE:

Swing brake

Casted counterweight
Upper undercovers
500 hour greasing interval - turntable
bearing

UNDERCARRIAGE:

X-pattern car-body

LC/long undercarriage: 94" (2.85M)

Track gauge: 66" (1.99M)

Shoes: 3-bar/18" (39 per side)

Hydraulic adjustable track tension

Tapered upper track frame Sealed outer flange rollers

Front track guides Lower under covers

TRACK DRIVE:

2-speed independent hydrostatic travel
 (max. 3.2 mph)
SAHR disc brakes
Drive motor guards

HYDRAULICS:

interval

Open-center system

Two - variable displacement axial
piston pumps with regulating system
One - pilot control gear pump
Auxiliary hydraulic valve
Boom anti-drift valve
5000 hour hydraulic oil change interval
1000 hour hydraulic filter change



(Ex Works Port of Entry) Standard Equipment

ATTACHMENTS:

Arm: 5'6" (less bucket)
Boom: 12'4" one piece
Hammer operation adaptable Reinforcing required for
crusher/cutter operation

Swing brake

MISCELLANEOUS:

Parts catalogue
Single key lock-up
Travel alarm and horn
Centralized lube bank
Rubber bumpers for upper sides
 (order through Service Parts)
Working lights: lx boom, 1 x cab

OPTIONAL EQUIPMENT:

Attachments:

- Offset boom: 129"

- Arm: 7'2"

Arm: 59" (for offset boom)Arm: 6'10" (for offset boom)

Control pattern change selector

Auxiliary hydraulics Steel shoes: 3-bar/24"

Rubber shoes:

- 18" Rubber track pads bolted on steel

CASE SiteWatch™ - on board telematics

Order from Factory Supplied Attachments:

Please consult excavator
attachments weight limits prior to
selecting a coupler and large bucket.
Excessive bucket and coupler weight
will negatively impact machine
performance.



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|---------------------|--------|--------------|--------------|
| CX75C | | | \$121,439.00 |
| CX75C W/DOZER BLADE | | | \$130,117.00 |



(Ex Works Port of Entry) Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|--------------|---|--------|--------------|------------|
| | | | | |
| OOMS | | | | |
| | | | | |
| 00 55044 00 | 2004 | | | |
| SD_E5311 BC | | | | N - Ob |
| 481858 | Standard Boom | | | No Charg |
| 101005 | 12'4" (3.75 M) Standard Boom | | | 00.744.0 |
| 461025 | Offset Boom | | | \$8,744.0 |
| | 12'9" (3.89 M) Offset Boom | | | |
| | For use with CX75C w/dozer blade | | | |
| ARMS | | | | |
| | | | | |
| | | | | |
| SD F5320 AF | RM/DIPPERSTICK | | | |
| - | Standard Boom | | | |
| 781172 | 5'6" (1.7 M) Arm | | | No Charge |
| 481265 | 7'2" (2.2 M) Arm | | | \$2,014.00 |
| | Offset Boom | ļ. | | Ψ2,014.00 |
| 481062 | 5'9" (1.75 M) Standard Arm | | | \$1,066.00 |
| 401002 | For use with CX75C w/Dozer Blade | | | φ1,000.00 |
| 494062 | | | | ¢4 670 00 |
| 481063 | 6' 10" (2.11 M) Standard Arm | | | \$1,678.00 |
| | For use with CX75C w/Dozer Blade | | | |
| TRACK SHOES | | | | |
| | | | | |
| | | | | |
| SD_E5199 TR | ACK SHOES | | | |
| 9560017 | 18" (450mm) Steel Shoes, 3-bar | | | No Charge |
| 9560002 | 23.6" (600mm) Steel Shoes | | | \$1,949.00 |
| 3000002 | Blade will not fully cover track width when using 24" shoes | | | Ψ1,040.00 |
| 9560018 | 18" (450mm) Rubber Track | | | \$6,654.00 |
| 9360016 | | | | φ0,054.00 |
| | Rubber pads bolted on regular 18" track | | | |
| LANGUAGE | | | | |
| | | | | |
| | | | | |
| SD_47083 OF | PERATOR'S MANUAL | | | |
| | | | | |

781981

461540

781980

English Language Literature

French Canadian Language
Spanish Language Literature

No Charge

No Charge

No Charge



| ADI | DITIONAL EQU | JIPMENT CXM | |
|-----|----------------|--|------------|
| | | | |
| ΑĽ | DDITIONAL EQUI | PMENT | |
| | | | |
| | _ | B GUARD (FOPS) | |
| | | FOPS Top Cab Guard/Level 1 | No Charge |
| | 481070 | FOPS Top Cab Guard/Level 2 | \$1,294.00 |
| | SD_E5444 CA | B GUARD (FRONT) | |
| | XE5444X | No Front Guard | No Charge |
| | 461142 | Front grill guard - 2 x 2 mesh | \$1,497.00 |
| | 461024 | Front rock guard (OPG 2) | \$2,215.00 |
| | | vertical bars (one piece/full length) | |
| | SD_E6410 AU | XILIARY HYDRAULICS | |
| | - | No Optional Hydraulics | No Charge |
| | | Standard Boom | |
| | 461865 | HAM ELCT PRO CNTRL | \$4,794.00 |
| | | Hammer Circuit Electrical Proportional Control | |
| | | Not for use with Offset Boom option 461025 | |
| | | Joystick activated | |
| | | Provides single direction flow; use for hammer application | |
| | | Includes manually adjustable relief valve to set required pressures | |
| | | Notes: | |
| | | Not for use with other Auxiliary Hydraulic options, with the exception of Low Flow. | |
| | | Heavy duty bucket linkage is standard equipment on C series excavators. | |
| | | For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com) | |



| 404000 | LIAMUSE EL ET DDO CNITOL | 67.400.00 |
|--------|---|---|
| 461868 | | \$7,198.00 |
| | | |
| | Not for use with Offset Boom option 461025 | |
| | | |
| | Does not include the in-cab Electronic Pressure Control feature | |
| | layatisk activated | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | 1. | |
| | Is switchable to single acting flow for nammer applications | |
| | Notes: | |
| | | |
| | | |
| | · · · · · · · · · · · · · · · · · · · | |
| | | |
| | | |
| | | |
| 461871 | · · · · · · · · · · · · · · · · · · · | \$3,434.00 |
| 401071 | | ψ0,404.00 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | 1 ' ' - | |
| | This system is not switchable to single acting now | |
| | Notes: | |
| | 1) Not for use other Auxiliary Hydraulics options with the | |
| | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com). | |
| | 461868 | HAM/HF ELET PRO CNTRL Hammer/High Flow Circuit, Electrical Proportional Control Not for use with Offset Boom option 461025 Does not include the in-cab Electronic Pressure Control feature Joystick activated Provides single or dual pump, two-way flow, for use with multiple applications: thumb/grapples/crushers Secondary Low-flow Auxiliary Hydraulics can be added Includes manually adjustable relief valve to set required pressures Is switchable to single acting flow for hammer applications Notes: 1) Not for use with other Auxiliary Hydraulics options with the exception of Low Flow. 2) Heavy duty bucket linkage is standard equipment on C Series excavators. 3) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com) 461871 AUX, TMB ELEC PRO CNTRL Auxiliary Circuit, Thumb, Electrical Proportional Control Not for use with Offset Boom option 461025 Joystick activated Provides single pump, two-way flow; use for thumb application Hydraulic plumbing provided to the end of the boom only, no piping to the arm This system is not switchable to single acting flow Notes: 1) Not for use other Auxiliary Hydraulics options with the exception of Low Flow. 2) Heavy duty bucket linkage is standard equipment on C series excavators. 3) For dealer installed auxiliary hydraulic kits contact: |



| | (| | |
|--------------|---|--|------------|
| For use with | n Offset Boom | | |
| 461866 | HAM OFB ELET PRO CNTRL | | \$5,308.00 |
| | Hammer Circuit Offset Boom Electrical Proportional Control | | |
| | For use with Offset Boom option 461025 and 5'9" (1.75 M) | | |
| | Standard Arm option 481062 | | |
| | | | |
| | Joystick activated | | |
| | Provides single direction flow; use for hammer application | | |
| | Includes manually adjustable relief valve to set required pressures | | |
| | Notes: | | |
| | 1) Not for use other Auxiliary Hydraulics options, with the | | |
| | exception of Low Flow. | | |
| | 2) Heavy duty bucket linkage is standard equipment on C series | | |
| | excavators. | | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | | |
| | HKX (1-800-493-5487 or www.HKX.com). | | |
| 461873 | DAC, OFB, ELCT PRO | | \$3,955.00 |
| | Double Acting Circuit, Offset, Electrical Proportional | | |
| | For use with Offset Boom option 461025 and 5'9" (1.75 M) | | |
| | Standard Arm option 481062 | | |
| | Joystick activated | | |
| | Provides single pump, two-way flow; use for thumb application | | |
| | Hydraulic plumbing provided to the end of the boom only, | | |
| | no piping to the arm | | |
| | This system is not switchable to single acting flow | | |
| | | | |
| | Notes: | | |
| | 1) Not for use other Auxiliary Hydraulics options with the | | |
| | exception of Low Flow. | | |
| | 2) Heavy duty bucket linkage is standard equipment on | | |
| | C series excavators. | | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | | |
| | HKX (1-800-493-5487 or www.HKX.com). | | |

| SD E6417 | SECONDARY A | UXILIARY HYDRAULICS |
|----------|--------------|--------------------------|
| OD_E0+17 | OLOGINDAIL A | OXILIAIX I III DIXAGLIGG |

| | XE6417X No Extra Auxiliary Hydraulics | | | No Charge | |
|--|---------------------------------------|--|--|-----------|--|
|--|---------------------------------------|--|--|-----------|--|

No Charge

\$942.00



CX75C MIN SWING RADIUS CRAWLER EXCAVATOR US PRICE LIST

| | | (Ex Works Port of Entry) | |
|---|-------------|--|------------|
| | 461863 | LF ELCT PRO CNTRL | \$4,222.00 |
| | | Low Flow Electrical Proportional Control | |
| | | Not for use with Offset Boom option 461025 | |
| | | Joystick Activated | |
| | | Provides low-flow for rotation or tilt of hydraulic tools. | |
| | | Notes: | |
| | | 1) May be used standalone or with any Case Excavator Auxiliary | |
| | | Hydraulics option. | |
| | | 2) For dealer installed auxiliary hydraulic kits contact: | |
| | | HKX (1-800-493-5487 or www.HKX.com). | |
| | SD_E6423 CC | ONTROL PATTERN SELECTION | |
| | XE6423X | No Control Pattern Valve | No Charge |
| | 461558 | Control Pattern Selector Valve | \$1,518.00 |
| | SD_E9702 RE | EAR VIEW CAMERA | |
| | XE9702X | No Rear View Camera | No Charge |
| | 461504 | Rear View Camera | \$675.00 |
| | SD_E9730 SA | FETY VALVE | |
| | XE9730X | No Hose Burst Check Valve | No Charge |
| | 461559 | Hose Burst Check Valve (HBCV) | \$2,727.00 |
| | SD_E9874 RE | FUEL PUMP | |
| | XE9874X | No Refuel Pump | No Charge |
| | 481257 | Refuel Pump | \$1,175.00 |
| | | | |
| Т | ELEMATICS | | |
| | SD F9908 TF | ELEMATICS ON BOARD | |
| | | No Talana Car | N. Olasas |

XE9908X No Telematics

461860 CASE SiteWatch™

| Page | 14 | of | 162 |
|------|----|----|-----|



(Ex Works Port of Entry)

Factory Supplied Attachments

| Order Code | Description | Weight | Factory Data | List Price |
|------------------|--|--------|--------------|------------|
| ase Coupler Bu | ekets | | | |
| 84422902 | 18" Heavy Duty Coupler Bucket with 3 teeth (.24 cu. yd.) | 440 LB | | \$2,018.00 |
| 84422903 | 24" Heavy Duty Coupler Bucket with 4 teeth (.32 cu. yd.) | 520 LB | | \$2,385.00 |
| 84422906 | 30" Heavy Duty Coupler Bucket with 5 teeth (.41 cu. yd.) | 585 LB | | \$2,645.00 |
| 84422909 | 36" Heavy Duty Coupler Bucket with 5 teeth (.50 cu. yd.) | 670 LB | | \$2,942.00 |
| 84422911 | 42" Heavy Duty Coupler Bucket with 6 teeth (.59 cu. yd.) | 760 LB | | \$3,228.00 |
| ase Multi Fit Co | upler | | | |
| 86991584 | Case Multi Fit Hydraulic Coupler Optimized for use with Case coupler buckets. Also can be used with a wide range of buckets from other manufacturers including pin-on types. Includes hydraulic installation kit and instructions. | 354 LB | | \$5,062.00 |
| ase Pin On Bucl | xets . | | | |
| 84404122 | 42" Ditching Bucket (.60 cu. yd.) | 535 LB | | \$2,159.00 |
| 84404123 | 48" Ditching Bucket (.70 cu. yd.) | 550 LB | | \$2,247.00 |
| 84422873 | 18" Heavy Duty Bucket with 3 teeth (.21 cu. yd.) | 450 LB | | \$1,587.00 |
| 84422885 | 24" Heavy Duty Bucket with 4 teeth (.31 cu. yd.) | 530 LB | | \$1,866.00 |
| 84422889 | 30" Heavy Duty Bucket with 5 teeth (.39 cu. yd.) | 600 LB | | \$2,079.00 |
| 84422894 | 36" Heavy Duty Bucket with 5 teeth (.48 cu. yd.) | 685 LB | | \$2,311.00 |
| 84422897 | 42" Heavy Duty Bucket with 6 teeth (.57 cu. yd.) | 790 LB | | \$2,534.00 |



(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AU-4LE2X turbocharged Tier 4 Final Certified 4 Cylinder liquid cooled diesel High pressure common rail Cooled EGR with variable controlled valve DOC - diesel oxidation catalyst 133 cu. in. (2.2 liter) displacement Horsepower:

- Net (SAE) 55.2 (41.2kw) at 2000 RPM

Fuel Tank Capacity: 31.7 gal. (US) Long Life Anti-freeze (protect to - 34°F)

OPERATOR'S CAB:

4-point iso-mounted ROPS cab

Pressurized cab

- Climate control: AC/Heat/Defrost
- Fully adjustable deluxe seat with 3" seat-belt
- AM/FM radio with dual speakers
- Floor mats
- 12-volt outlet
- In-cab light

Cab roof skylight

Safety glass:

- Two-piece front window
- Front windshield wiper with washer

Waterproof/illuminated membrane

switches

Low-effort pilot controls

Full-color LCD display - rearview

camera ready

Dial type throttle control for engine

speed

Work mode selector: SP, H, Auto

One-touch idle

Programmable anti-theft protection

ELECTRICAL:

24 Volt system Alternator: 50 AMP Batteries: 2

BLADE:

Hydraulically controlled dozer blade

- Blade width: 7'7"

- Blade height: 1'6"

UPPER STRUCTURE:

Swing brake

Casted counterweight Upper undercovers 500 hour greasing interval - turntable

bearing

UNDERCARRIAGE:

X-pattern car-body

LC/long undercarriage: 94" (2.85M)

Track gauge: 62" (1.99M)

Shoes: 3-bar/18" (39 per side) Hydraulic adjustable track tension

Tapered upper track frame Sealed outer flange rollers

Front track guides Lower under covers

TRACK DRIVE:

2 speed independent hydrostatic travel (max. 3.2 mph) SAHR disc brakes Drive motor guards

HYDRAULICS:

Open-center system

Two - variable displacement axial piston pumps with regulating system

One - pilot control gear pump One position mode selector Auxiliary hydraulic valve

Boom anti-drift valve

5000 hour hydraulic oil change interval

1000 hour hydraulic filter change

interval



(Ex Works Port of Entry) Standard Equipment

ATTACHMENTS:

Arm: 5'6" (less bucket)
Swing Boom: 11'6" one piece
Hammer operation adaptable Reinforcing required for
crusher/cutter operation

MISCELLANEOUS:

Parts catalogue
Single key lock-up
Travel alarm and horn
Centralized lube bank
Rubber bumpers for upper sides
 (order through Service Parts)
Working lights: 1 x boom, 1 x cab

OPTIONAL EQUIPMENT:

Attachments:

- Arm: 7'2"

Control pattern change selector

Auxiliary hydraulics Steel shoes: 3-bar/24"

Rubber shoes:

- 18" Rubber track pads bolted on

steel

CASE SiteWatch™ - on board telematics

Order from Factory Supplied Attachments:

Please consult excavator
attachments weight limits prior to
selecting a coupler and large bucket.
Excessive bucket and coupler weight
will negatively impact machine
performance.



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|--------|--------------|--------------|
| CX80C | | | \$136,033.00 |



(Ex Works Port of Entry) Factory Supplied Options

| | | • | | |
|----------------|--------------------------------|--------|--------------|------------|
| Order Code | Description | Weight | Factory Data | List Price |
| | | · | | |
| BOOMS | | | | |
| BOOMS | | | | |
| | | | | |
| SD_E5311 B0 | OOM | | | |
| 481858 | Standard Boom | | | No Charge |
| | | | | J |
| ARMS | | | | |
| | | | | |
| | | | | |
| SD_E5320 AI | RM/DIPPERSTICK | | | |
| 781172 | 5'6" (1.7 M) Arm | | | No Charge |
| 481265 | 7'2" (2.2 M) Arm | | | \$2,014.00 |
| | | | | |
| TRACK SHOES | | | | |
| | | | | |
| | | | | |
| SD_E5199 TF | RACK SHOES | | | |
| 9560017 | 18" (450mm) Steel Shoes, 3-bar | | | No Charge |
| 9560002 | 23.6" (600mm) Steel Shoes | | | \$1,949.00 |
| 9560018 | 18" (450mm) Rubber Track | | | \$6,654.00 |
| | | | | |
| LANGUAGE | | | | |
| | | | | |
| | | | | |
| SD_47083 OI | PERATOR'S MANUAL | | | |
| 781981 | English Language Literature | | | No Charge |
| 461540 | French Canadian Language | | | No Charge |
| 781980 | Spanish Language Literature | | | No Charge |
| | | | | |
| ADDITIONAL EQ | UIPMENT CXM | | | |
| | | | | |
| ADDITIONAL EQU | JIPMENT | | | |
| | | | | |
| | AB GUARD (FOPS) | | | |
| | FOPS Top Cab Guard/Level 1 | | | No Charge |
| 481070 | FOPS Top Cab Guard/Level 2 | | | \$1,294.00 |
| | | | | |
| | AB GUARD (FRONT) | | , | |
| | No Front Guard | | | No Charge |
| 461142 | Front grill guard - 2 x 2 mesh | | | \$1,497.00 |



(Ex Works Port of Entry)

| | 461024 | Front rock guard (OPG 2) | | \$2,215.00 |
|--|--------|---------------------------------------|--|------------|
| | | vertical bars (one piece/full length) | | |

SD E6410 AUXILIARY HYDRAULICS

| SD | D_E6410 AU | XILIARY HYDRAULICS | | | |
|--------------------|------------|---|---|---|------------|
| $\sqcup \bot \bot$ | XE6410X | No Optional Hydraulics | | | No Charge |
| | 461865 | HAM ELCT PRO CNTRL | | | \$4,794.00 |
| | | Hammer Circuit Electrical Proportional Control | | | |
| | | Joystick activated | | | |
| | | Provides single direction flow; use for hammer application | | | |
| | | Includes manually adjustable relief valve to set required pressures | | | |
| | | Notes: | | | |
| | | 1) Not for use with other Auxiliary Hydraulic options, with the | | | |
| | | exception of Low Flow. | | | |
| | | 2) Heavy duty bucket linkage is standard equipment on | | | |
| | | C series excavators. | | | |
| | | 3) For dealer installed auxiliary hydraulic kits contact: | | | |
| | | HKX (1-800-493-5487 or www.HKX.com) | | | |
| | 461868 | HAM/HF ELET PRO CNTRL | | | \$7,198.00 |
| | | Hammer/High Flow Circuit, Electrical Proportional Control | | | |
| | | Not for use with Offset Boom option 461025 | | | |
| | | Does not include the in-cab Electronic Pressure Control feature | | | |
| | | Joystick activated | | | |
| | | Provides single or dual pump, two-way flow, for use with | | | |
| | | multiple applications: thumb/grapples/crushers | | | |
| | | Secondary Low-flow Auxiliary Hydraulics can be added | | | |
| | | Includes manually adjustable relief valve to set required | | | |
| | | pressures | | | |
| | | Is switchable to single acting flow for hammer applications | | | |
| | | Notes: | | | |
| | | 1) Not for use with other Auxiliary Hydraulics options with the | | | |
| | | exception of Low Flow. | | | |
| | | 2) Heavy duty bucket linkage is standard equipment | | | |
| | | on C Series excavators. | | | |
| | | 3) For dealer installed auxiliary hydraulic kits contact: | | | |
| | | HKX (1-800-493-5487 or www.HKX.com) | | | |
| | | THAT (1-000-430-0401 OF WWW.HITA.COM) | l | l | |



| (Ex Works | Port of | Entry) |
|-----------|---------|--------|
|-----------|---------|--------|

| | (EX WORKS PORT OF ENTRY) | |
|-------------|--|------------|
| 461871 | AUX, TMB ELEC PRO CNTRL | \$3,434.00 |
| | Auxiliary Circuit, Thumb, Electrical Proportional Control | |
| | Not for use with Offset Boom option 461025 | |
| | Joystick activated | |
| | Provides single pump, two-way flow; use for thumb application | |
| | Hydraulic plumbing provided to the end of the boom only, | |
| | no piping to the arm | |
| | This system is not switchable to single acting flow | |
| | | |
| | Notes: | |
| | 1) Not for use other Auxiliary Hydraulics options with the | |
| | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com). | |
| | | <u> </u> |
| SD_E6417 SE | CONDARY AUXILIARY HYDRAULICS | |
| XE6417X | No Extra Auxiliary Hydraulics | No Charge |
| 461863 | LF ELCT PRO CNTRL | \$4,222.00 |
| | Low Flow Electrical Proportional Control | |
| | Not for use with Offset Boom option 461025 | |
| | Joystick Activated | |
| | Provides low-flow for rotation or tilt of hydraulic tools. | |
| | | |
| | Notes: | |
| | 1) May be used standalone or with any Case Excavator Auxiliary | |
| | Hydraulics option. | |
| | 2) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com). | |
| | | |
| SD_E6423 CC | ONTROL PATTERN SELECTION | |
| XE6423X | No Control Pattern Valve | No Charge |
| 461558 | Control Pattern Selector Valve | \$1,518.00 |
| | | |
| SD_E9702 RE | AR VIEW CAMERA | |
| XE9702X | No Rear View Camera | No Charge |
| 461504 | Rear View Camera | \$675.00 |
| | | |
| SD_E9730 SA | 1 | |
| | No Hose Burst Check Valve | No Charge |
| 461559 | Hose Burst Check Valve (HBCV) | \$2,727.00 |

SD_E9874 REFUEL PUMP

XE9874X No Refuel Pump 481257 Refuel Pump No Charge

\$1,175.00



(Ex Works Port of Entry)

| TELEMATICS | |
|------------|--|
|------------|--|

SD_E9908 TELEMATICS ON BOARD

| | XE9908X | No Telematics | | No Charge |
|--|---------|-----------------|--|-----------|
| | 461860 | CASE SiteWatch™ | | \$942.00 |



(This page intentionally left blank)



(Ex Works Port of Entry) Factory Supplied Attachments

| Order Code | Description | Weight | Factory Data | List Price |
|------------------|--|--------|--------------|------------|
| Case Coupler Bud | ekets | | | |
| 84422902 | 18" Heavy Duty Coupler Bucket with 3 teeth (.24 cu. yd.) | 440 LB | | \$2,018.00 |
| 84422903 | 24" Heavy Duty Coupler Bucket with 4 teeth (.32 cu. yd.) | 520 LB | | \$2,385.00 |
| 84422906 | 30" Heavy Duty Coupler Bucket with 5 teeth (.41 cu. yd.) | 585 LB | | \$2,645.00 |
| 84422909 | 36" Heavy Duty Coupler Bucket with 5 teeth (.50 cu. yd.) | 670 LB | | \$2,942.00 |
| 84422911 | 42" Heavy Duty Coupler Bucket with 6 teeth (.59 cu. yd.) | 760 LB | | \$3,228.00 |
| 87457194 | Case Multi Fit Hydraulic Coupler Optimized for use with Case coupler buckets. Also can be used with a wide range of buckets from other manufacturers including pin-on types. Includes hydraulic installation kit and instructions. | 392 LB | | \$5,062.00 |
| Case Pin On Buck | kets | | | |
| 84404122 | 42" Ditching Bucket (.60 cu. yd.) | 535 LB | | \$2,159.00 |
| 84404123 | 48" Ditching Bucket (.70 cu. yd.) | 550 LB | | \$2,247.00 |
| 84422873 | 18" Heavy Duty Bucket with 3 teeth (.21 cu. yd.) | 450 LB | | \$1,587.00 |
| 84422885 | 24" Heavy Duty Bucket with 4 teeth (.31 cu. yd.) | 530 LB | | \$1,866.00 |
| 84422889 | 30" Heavy Duty Bucket with 5 teeth (.39 cu. yd.) | 600 LB | | \$2,079.00 |
| 84422894 | 36" Heavy Duty Bucket with 5 teeth (.48 cu. yd.) | 685 LB | | \$2,311.00 |
| 84422897 | 42" Heavy Duty Bucket with 6 teeth (.57 cu. yd.) | 790 LB | | \$2,534.00 |



(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE: Isuzu AM-4JJ1X Tier-4a Interim Certified (cooled EGR) 183 cubic in. displacement /3.0 Liter Turbocharged/air cooled intercooler Horsepower: Net: 100 (74.9 kW) @ 2000 RPM High pressure common rail system Auto engine warm-up FEA (Fuel Economy Assist System) Engine Idle/Fuel Economy System: Auto Idle One-touch Idle Idle Shut-down Fuel Capacity: 69 gallons (260 L) AEC (auto economy control) BEC (boom economy control) OPERATOR'S CAB: ROPS protection Pressurized cab area AC/heat/defrost with auto control Electronics: Color monitor (7 in/180 mm) with Rearview camera view Rearview camera AM/FM radio with antenna and 2-speakers Aux-in port for personal electronics 12-volt electric socket 24-volt cigarette lighter KAB ® Air-suspension seat (cloth) Seat belt Adjustable arm rests 4-position tilting consoles Sliding cockpit (7 in/180 mm) Low-effort joystick controls Clear (poly carbonate) roof window External rearview mirrors Rubber floormat

```
OPERATOR'S CAB (Continued):
  Cab interior features:
    Cup holder
    Storage compartments
    Warm/cool storage compartments
    Easy access fuse box
    Interior dome light
    One touch lock front window
    One key start & lock-up
    Interior Light (1 x 10 watt)
  Two-speed independent travel
  Straight travel
  Travel alarm and horn
  Windshield wiper and washer
  Programmable anti-theft system
ELECTRICAL:
  24-volt system
  Two batteries (12 volt/92 Ah)
  50 Amp Alternator
  Worklights (4 x 70 watt)
    Boom mounted (1)
    Upper mounted (1)
    Cab top mounted (2)
HYDRAULICS:
  Open-center system design
  Optional auxiliary hydraulics
  Selectable work modes (3)
 Auto power boost
 Auto swing priority
  SWC (swing relief control)
  SSC (spool stroke control)
  5000 hour hydraulic oil change interval
  1000 hour hyd. filter change interval
```



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE: X-pattern carbody LC Undercarriage: STD LC: 12'4" (3.76 M) length STD DZB: 11'6" (3.50 M) length Track Gauge: STD: 6'6" (1.99 M) gauge Shoe: STD: 23.6" triple grouser 6.75" pitch 46 shoes per side LC: Carrier rollers (2 per side) DZB: Carrier rollers (1 per side) LC: Track rollers (7 per side) DZB: Track rollers (7 per side) Grease lubricated and strutted track chains Hydraulic track adjustment SAHR disc parking break Tapered upper track frame Dozer Blade: Dozer blade width: 8' 6" (2590 mm) Dozer blade height: **ATTACHMENTS:** STD LC and DZB Versions:

Boom: 15'2" (4.63 M) Arm: 82" (2.50M) Heavy-duty bucket linkage Auxiliary pipe brackets Attachment cushion valve Arm and boom regeneration Arm and boom holding valves Centralized grease bank

OTHER BASIC EQUIPMENT: CASE SiteWatch™ - on board telematics

OPTIONAL EQUIPMENT: Cab and Operator's Station: Side view camera Sun visor FOPS top cab guard (Level 2) Front grill guard (2" x 2" mesh) Front rock guard (OPG 1) Front rock quard (OPG 2) Vandal guard (not for use with FOPS top cab guard) Rain deflector Control pattern change selector Free swing Hose burst check valve (HBCV) Refueling Pump Auxiliary hydraulics Attachments: Arm: 610" (2.10 M) Heavy-duty Arm: 911" (3.01 M) Standard Undercarriage: Steel shoes/triple-grouser: 27.6" (700 mm) Rubber track: 20.0" (500 mm) Track chain guides - double Order from Wholegood Attachments -Third Party setion: Buckets Coupler/Case multi-pin grabber Order from Service Parts:

Rubber bumpers for upper



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|-----------|--------------|--------------|
| CX130C STD LC | 27,800 LB | | \$184,775.00 |
| CX130C STD DZB | 27,800 LB | | \$197,251.00 |



(Ex Works Port of Entry)

Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|-------------|--|--------|--------------|--------------|
| | · | | | |
| BOOMS | | | | |
| | | | | |
| | | | | |
| SD_E5311 B | ООМ | | | |
| 481858 | Standard Boom | | | No Charge |
| | 15'2" (4.63 M) Boom | | | |
| 781917 | No Boom | | | (\$3,756.00) |
| | Less boom, hoist and arm cylinders and plumbing. | | | |
| | Boom-foot and cylinder pins are provided. | | | |
| | Not for use with CX130C STD DZB commercial model | | | |
| | | | | |
| ARMS | | | | |
| | | | | |
| | | | | |
| SD_E5320 A | RM/DIPPERSTICK | | | |
| 461574 | 6'10" (2.11 M) Heavy-duty Arm | | | \$665.00 |
| 781174 | 8' 2" (2.50 M) Standard Arm | | | No Charge |
| 781178 | 9'11" (3.01M) Standard Arm | | | \$1,257.00 |
| XE5320X | No Arm/Dipperstick | | | (\$2,408.00) |
| | Less arm, bucket cylinder and linkage | | | |
| • | · · · · · · · · · · · · · · · · · · · | | | |
| TRACK SHOES | | | | |
| | | | | |
| | | | | |
| SD_E5199 TF | RACK SHOES | | | |
| 9560002 | I | | | No Charge |
| | Triple-Grouser Steel Shoes | | | 9- |
| 9560003 | | | | \$1,365.00 |
| | Triple-Grouser Steel Shoes | | | ψ1,000.00 |
| 9560052 | | | | \$9,550.00 |
| 5000002 | Continous belt bolted on standard chain | | | ψο,οοο.ος |
| | Continuous peri ported on standard origin | I | ll. | |
| LANGUAGE | | | | |
| LANGUAGE | | | | |
| | | | | |
| OD 47000 01 | DED A TODIO MANULAL | | | |
| | PERATOR'S MANUAL | 1 | 1 | NI- OL |
| 461540 | French Canadian Language | | | No Charge |
| 781980 | Spanish Language Literature | | | No Charge |

781981

English Language Literature

No Charge



| ADDITION | AL EQU | IIPMENT CXC | |
|-------------|---------|--|------------|
| | | | |
| ADDITION | AL OPTI | ONS | |
| OD EEG | one TD | ACK CHAIN GUIDE | |
| | | No Track Guide | No Charge |
| | 61542 | Double Track Chain Guide | \$840.00 |
| | 01042 | Bodble Hadik Ghain Galde | ψ040.00 |
| SD E54 | 443 CA | B GUARD (FOPS) | |
| | | FOPS Top Cab Guard/Level 1 | No Charge |
| | 81070 | FOPS Top Cab Guard/Level 2 | \$1,290.00 |
| | | | • |
| SD_E54 | 444 CA | B GUARD (FRONT) | |
| Х | E5444X | No Front Guard | No Charge |
| 46 | 61142 | Front grill guard - 2 x 2 mesh | \$1,500.00 |
| 78 | 81986 | Front rock guard (OPG 1) | \$2,045.00 |
| | | vertical bars (two piece/upper and lower) | |
| 46 | 61024 | Front rock guard (OPG 2) | \$2,295.00 |
| | | vertical bars (one piece/full length) | |
| 46 | 61552 | Vandal Guard | \$505.00 |
| | | Not for use with FOPS Top Cab Guard (option 481070) | |
| | | | |
| | | IN DEFLECTOR | |
| | | No Rain Deflector | No Charge |
| 46 | 61555 | Rain Deflector | \$390.00 |
| | | Not for use with Front grill guard - 2 x 2 mesh option 461142, | |
| | | Front rock guard (OPG 1) option 781986, or | |
| | | Front rock guard (OPG 2) option 461024. | |
| CD EE | 454 CU | NI VICOD | |
| | | N VISOR No Sun Visor | No Charge |
| | 61554 | Sun Visor | No Charge |
| 1 1 40 | 01004 | OUIT VISUE | \$125.00 |
| SD_E64 | 410 AU | XILIARY HYDRAULICS | |
| | | No Optional Hydraulics | No Charge |



| | with No Boom | | |
|--------|---|---|------------|
| 461865 | HAM ELCT PRO CNTRL | | \$6,147.00 |
| | Hammer Circuit Electrical Proportional Control | | |
| | Joystick activated | | |
| | Provides single direction flow; use for hammer application | | |
| | Includes manually adjustable relief valve to set required pressures | | |
| | Notes: | | |
| | 1) Not for use with other Auxiliary Hydraulic options, with the | | |
| | exception of Low Flow. | | |
| | 2) Heavy duty bucket linkage is standard equipment on | | |
| | C series excavators. | | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | | |
| | HKX (1-800-493-5487 or www.HKX.com) | | |
| 461868 | HAM/HF ELET PRO CNTRL | | \$8,664.00 |
| | Hammer/High Flow Circuit, Electrical Proportional Control | | |
| | Does not include the in-cab Electronic Pressure Control feature | | |
| | | | |
| | Joystick activated | | |
| | Provides single or dual pump, two-way flow, for use with | | |
| | multiple applications: thumb/grapples/crushers | | |
| | Secondary Low-flow Auxiliary Hydraulics can be added | | |
| | Includes manually adjustable relief valve to set required | | |
| | pressures | | |
| | Is switchable to single acting flow for hammer applications | | |
| | Notes: | | |
| | 1) Not for use with other Auxiliary Hydraulics options with the | 1 | |
| | exception of Low Flow. | 1 | |
| | 2) Heavy duty bucket linkage is standard equipment | | |
| | on C Series excavators. | 1 | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | | |
| | HKX (1-800-493-5487 or www.HKX.com) | 1 | |



| (Ex Works | Port of | Entry) |
|-----------|---------|--------|
|-----------|---------|--------|

| | (Ex Works For or Entry) | |
|---------------------------|---|--|
| 46187 | 71 AUX, TMB ELEC PRO CNTRL | \$5,179.00 |
| | Auxiliary Circuit, Thumb, Electrical Proportional Control | |
| | Joystick activated | |
| | Provides single pump, two-way flow; use for thumb application | |
| | Hydraulic plumbing provided to the end of the boom only, | |
| | no piping to the arm | |
| | This system is not switchable to single acting flow | |
| | Notes: | |
| | 1) Not for use other Auxiliary Hydraulics options with the | |
| | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com). | |
| • | | • |
| SD_E6417 | SECONDARY AUXILIARY HYDRAULICS | |
| XE64 | 17X No Extra Auxiliary Hydraulics | No Charge |
| 46186 | 3 LF ELCT PRO CNTRL | \$6,020.00 |
| | Low Flow Electrical Proportional Control | |
| | Joystick Activated | |
| | Provides low-flow for rotation or tilt of hydraulic tools. | |
| | , | |
| | Notes: | |
| | | |
| | | |
| | May be used standalone or with any Case Excavator Auxiliary | |
| | May be used standalone or with any Case Excavator Auxiliary Hydraulics option. | |
| | 1) May be used standalone or with any Case Excavator Auxiliary Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: | |
| | May be used standalone or with any Case Excavator Auxiliary Hydraulics option. | |
| SD E6423 | 1) May be used standalone or with any Case Excavator Auxiliary Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com). | |
| | 1) May be used standalone or with any Case Excavator Auxiliary Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com). CONTROL PATTERN SELECTION | No Charge |
| XE64 | 1) May be used standalone or with any Case Excavator Auxiliary Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com). CONTROL PATTERN SELECTION 23X No Control Pattern Valve | |
| | 1) May be used standalone or with any Case Excavator Auxiliary Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com). CONTROL PATTERN SELECTION 23X No Control Pattern Valve | |
| XE64 4615 | 1) May be used standalone or with any Case Excavator Auxiliary Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com). CONTROL PATTERN SELECTION 23X No Control Pattern Valve Control Pattern Selector Valve | |
| XE64 46158 SD_E9730 | 1) May be used standalone or with any Case Excavator Auxiliary Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com). CONTROL PATTERN SELECTION 23X No Control Pattern Valve | \$950.00 |
| XE64 46158 SD_E9730 | 1) May be used standalone or with any Case Excavator Auxiliary Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com). CONTROL PATTERN SELECTION 23X No Control Pattern Valve Control Pattern Selector Valve SAFETY VALVE 30X No Hose Burst Check Valve | No Charge \$950.00 No Charge \$9,130.00 |

SD_E9740 SIDE VIEW CAMERA

SD_E9741 FREE SWING

461568

XE9740X No Side View Camera

Free Swing

switch activated

461560 Side View Camera

XE9741X No Free Swing

No Charge

No Charge

\$285.00

\$725.00



(Ex Works Port of Entry)

SD_E9874 REFUEL PUMP

| L | XE9874X | No Refuel Pump | | No Charge |
|---|---------|----------------|--|------------|
| | 481257 | Refuel Pump | | \$1,050.00 |

| L | | 481257 | Refuel Pump | | | \$1,050.00 |
|---|-------------------|-------------|--|--|--|------------|
| | | | | | | |
| | INVISIBLE CHAPTER | | | | | |
| _ | | | | | | |
| | S | SD_E6300 EX | CAVATOR BUCKET(S) | | | |
| ſ | | XE6300X | No Bucket (E6300) | | | No Charge |
| | | | Buckets may be ordered using Order Codes listed in the | | | |
| | | | Direct Ship Attachment Section | | | |



(Ex Works Port of Entry) Factory Supplied Attachments

| Order Code | Description | Weight | Factory Data | List Price | | |
|---------------------|--|----------|--------------|------------|--|--|
| ase Coupler Buckets | | | | | | |
| 84404117 | 24" Heavy Duty Coupler Bucket with 4 teeth (.43 cu. yd.) | 775 LB | | \$4,702.00 | | |
| 84404118 | 30" Heavy Duty Coupler Bucket with 4 teeth (.56 cu. yd.) | 870 LB | | \$5,219.00 | | |
| 84404119 | 36" Heavy Duty Coupler Bucket with 5 teeth (.70 cu. yd.) | 970 LB | | \$5,660.00 | | |
| 84404121 | 42" Heavy Duty Coupler Bucket with 5 teeth (.83 cu. yd.) | 1,055 LB | | \$5,923.00 | | |
| Case Multi Fit Co | ıpler | | | | | |
| 405486A1 | Case Multi Fit Hydraulic Coupler Optimized for use with Case coupler buckets. Also can be used with a wide range of buckets from other manufacturers including pin-on types. Includes hydraulic installation kit and instructions. | 603 LB | | \$9,129.00 | | |
| Case Pin On Bucl | kets | | | | | |
| 84404093 | 24" Heavy Duty Bucket with 4 teeth (.43 cu. yd.) | 969 LB | | \$3,402.00 | | |
| 84404095 | 30" Heavy Duty Bucket with 4 teeth (.56 cu. yd.) | 1,073 LB | | \$3,546.00 | | |
| 84404103 | 36" Heavy Duty Bucket with 5 teeth (.70 cu. yd.) | 1,227 LB | | \$3,841.00 | | |
| 84404105 | 24" Extra Heavy Duty Bucket with 4 teeth (.51 cu. yd.) | 1,050 LB | | \$3,644.00 | | |
| 84404108 | 30" Extra Heavy Duty Bucket with 4 teeth (.66 cu. yd.) | 1,200 LB | | \$4,044.00 | | |
| 84404109 | 36" Extra Heavy Duty Bucket with 5 teeth (.81 cu. yd.) | 1,375 LB | | \$4,429.00 | | |
| 84404110 | 42" Extra Heavy Duty Bucket with 5 teeth (.97 cu. yd.) | 1,500 LB | | \$4,727.00 | | |
| 84404113 | 48" Ditching Bucket (.79 cu. yd.) | 860 LB | | \$3,452.00 | | |
| 84404115 | 60" Ditching Bucket (1.02 cu. yd.) | 1,000 LB | | \$3,916.00 | | |
| 84406310 | 42" Heavy Duty Bucket with 5 teeth (.83 cu. yd.) | 1,351 LB | | \$4,315.00 | | |



(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE: OPERATOR'S CAB (Continued): Isuzu AM-4JJ1X Cab interior features: Tier-4a Interim Certified (cooled EGR) Cup holder 183 cubic in. displacement/3.0 Liter Storage compartments Turbocharged/air cooled intercooler Warm/cool storage compartments Horsepower: Easy access fuse box Net: 100 (74.9 kW) @ 2000 RPM Interior dome light One touch lock front window High pressure common rail system Auto engine warm-up One key start & lock-up Interior Light (1 x 10 watt) FEA (Fuel Economy Assist System) Engine Idle/Fuel Economy System: Two-speed independent travel Auto Idle Straight travel One-touch Idle Travel alarm and horn Idle Shut-down Windshield wiper and washer Fuel Capacity: Programmable anti-theft system 53 gallons (200 L) AEC (auto economy control) ELECTRICAL: BEC (boom economy control) 24-volt system Two batteries (12 volt/92 Ah) OPERATOR'S CAB: 50 Amp Alternator ROPS protection Worklights (4 x 70 watt) Pressurized cab area Boom mounted (1) AC/heat/defrost with auto control Upper mounted (1) Electronics: Cab top mounted (2) Color monitor (7 in/180 mm) with Rearview camera view HYDRAULICS: Rearview camera Open-center system design AM/FM radio with antenna and Optional auxiliary hydraulics Selectable work modes (3) 2-speakers Aux-in port for personal electronics Auto power boost 12-volt electric socket Auto swing priority 24-volt cigarette lighter SWC (swing relief control) KAB ® Air-suspension seat (cloth) SSC (spool stroke control) 5000 hour hydraulic oil change interval Seat belt 1000 hour hyd. filter change interval Adjustable arm rests 4-position tilting consoles Sliding cockpit (7 in/180 mm) Low-effort joystick controls Clear (poly carbonate) roof window External rearview mirrors Rubber floormat



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

X-pattern carbody
Undercarriage:

STD LC: 12'4" (3.76 M) length STD DZB: 11'6" (3.50 M) length

Track Gauge:

STD: 6'6" (1.99 M) gauge

Shoe:

STD: 23.6" triple grouser

6.75" pitch

43 shoes per side

LC: Carrier rollers (2 per side)
DZB: Carrier rollers (1 per side)
LC: Track rollers (7 per side)
DZB: Track rollers (7 per side)

 $\label{lem:conditional} \mbox{Grease lubricated and strutted track}$

chains

Hydraulic track adjustment Single track chain guides SAHR disc parking break Tapered upper track frame

DOZER BLADE:

Dozer blade width: 8'6" (2590 mm)
Dozer blade height: 22" (570 mm)

ATTACHMENTS:

Standard LC and DZB Versions:

Boom: 152" (4.63M)
Arm: 82" (2.50 M)
Heavy-duty bucket linkage
Auxiliary pipe brackets
Attachment cushion valve
Arm and boom regeneration
Arm and boom holding valves
Centralized grease bank

OTHER BASIC EQUIPMENT:

CASE SiteWatch™ - on board telematics

OPTIONAL EQUIPMENT:

Cab and Operator's Station:

Side view camera

Sun visor

FOPS top cab guard (Level 2)
Front grill guard (2" x 2" mesh)

Front rock guard (OPG 1)

Front rock guard (OPG 2)

Vandal guard (not for use with

FOPS top cab guard)

Rain deflector

Control pattern change selector

Free swing

Hose burst check valve (HBCV)

Refueling Pump

Auxiliary hydraulics

Attachments:

Arm: 610" (2.10 M) Standard Arm

(for offset boom only)

Arm: 610" (2.10 M) Heavy-duty
Arm: 910" (3.00 M) Standard Arm

Undercarriage:

Rubber shoes: 23.6" (600 mm)

Steel/triple-grouser: 27.6" (700 mm)

Track chain guides - double

Order from Wholegood Attachments

-Third Party setion:

Buckets

Coupler/Case multi-pin grabber



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|--------------------|-----------|--------------|--------------|
| CX145C MSR LC | 39,500 LB | | \$186,310.00 |
| CX145C MSR W/DOZER | 31,746 LB | | \$202,559.00 |



(Ex Works Port of Entry)

Factory Supplied Options

| | Order Code | Description | Weight | Factory Data | List Price |
|--|------------|-------------|--------|--------------|------------|
|--|------------|-------------|--------|--------------|------------|

BOOMS

SD_E5311 BOOM

| 05_E0011 BCOM | | | | | |
|---------------|--------|--|--|--|--------------|
| | 481858 | Standard Boom | | | No Charge |
| | | 15' 6" (4.72 M) Standard Boom | | | |
| | 461025 | Offset Boom | | | \$24,365.00 |
| | | 15' 6" (4.72 M) Offset Boom | | | |
| | | For use with CX145C MSR W/DOZER | | | |
| | 781917 | No Boom | | | (\$3,898.00) |
| | | Less boom, hoist and arm cylinders and plumbing. | | | |
| | | Boom foot and cylinder pins are provided. | | | |

ARMS

SD_E5320 ARM/DIPPERSTICK

| 781174 | 8' 2" (2.50 M) Standard Arm | No Charge |
|---------|---|--------------|
| | For use with CX145C MSR LC and CX145C MSR W/DOZER | |
| | FOR USE WITH STANDARD BOOM (options 481858) | |
| 481063 | 6' 10" (2.11 M) Standard Arm | \$665.00 |
| | For use with CX145C MSR W/DOZER | |
| | FOR USE WITH OFFSET BOOM (options 461025) | |
| 461574 | 6'10" (2.11 M) Heavy-duty Arm | \$665.00 |
| | For use with CX145C MSR LC and CX145C MSR W/DOZER | |
| | FOR USE WITH STANDARD BOOM (options 481858) | |
| | (Recommended for heavy-duty applications - example: hammer) | |
| 781178 | 9'11" (3.01M) Standard Arm | \$1,257.00 |
| | For use with CX145C MSR LC and CX145C MSR W/DOZER | |
| | FOR USE WITH STANDARD BOOM (options 481858) | |
| XE5320X | No Arm/Dipperstick | (\$2,367.00) |
| | Less arm, bucket cylinder and linkage | |

TRACK SHOES

SD_E5199 TRACK SHOES

| | 9560002 | 23.6" (600mm) Steel Shoes | | No Charge |
|--|---------|----------------------------|--|------------|
| | | Triple-Grouser Steel Shoes | | |
| | 9560003 | 27.6" (700mm) Steel Shoes | | \$1,365.00 |
| | | Triple-Grouser Steel Shoes | | |



CX145C MIN SWING RADIUS CRAWLER EXCAVAT **US PRICE LIST** (Ex Works Port of Entry) 9560052 20" (500mm) Rubber Track \$9,550.00 Rubber pads molded to steel base on steel chain **LANGUAGE** SD_47083 OPERATOR'S MANUAL 781981 English Language Literature No Charge 461540 French Canadian Language No Charge 781980 Spanish Language Literature No Charge ADDITIONAL EQUIPMENT CXC ADDITIONAL OPTIONS SD_E5206 TRACK CHAIN GUIDE XE5206X No Track Guide No Charge 461542 Double Track Chain Guide \$840.00 SD_E5443 CAB GUARD (FOPS) XE5443X FOPS Top Cab Guard/Level 1 No Charge \$1,290.00 481070 FOPS Top Cab Guard/Level 2 SD_E5444 CAB GUARD (FRONT) XE5444X No Front Guard No Charge 461142 Front grill guard - 2 x 2 mesh \$1,500.00 781986 Front rock guard (OPG 1) \$2,045.00 vertical bars (two piece/upper and lower) 461024 Front rock guard (OPG 2) \$2,295.00 vertical bars (one piece/full length) 461552 Vandal Guard \$505.00 Not for use with FOPS Top Cab Guard (option 481070)

| SD_E5449 | RAIN DEFLECTOR |
|----------|----------------|
| | |

| L | XE5449X | No Rain Deflector | | No Charge |
|---|---------|--|--|-----------|
| | 461555 | Rain Deflector | | \$390.00 |
| | | Not for use with Front grill guard - 2 x 2 mesh option 461142, | | |
| | | Front rock guard (OPG 1) option 781986, or | | |
| L | | Front rock guard (OPG 2) option 461024. | | |

SD_E5451 SUN VISOR

| | XE5451X | No Sun Visor | | No Charge |
|--|---------|--------------|--|-----------|
| | 461554 | Sun Visor | | \$125.00 |
| | | | | |

SD F6410 AUXILIARY HYDRAULICS

| OB_EOTIO TIONIENTITI TITOLOGO | | | | |
|-----------------------------------|--|--|-----------|--|
| XE6410X No Optional Hydraulics | | | No Charge | |



(Ex Works Port of Entry)

| For use with | Standard Boom | |
|--------------|---|---|
| 461865 | HAM ELCT PRO CNTRL | \$6,368.00 |
| | Hammer Circuit Electrical Proportional Control | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, |
| | Joystick activated | |
| | Provides single direction flow; use for hammer application | |
| | Includes manually adjustable relief valve to set required pressures | |
| | | |
| | Notes: | |
| | Not for use with other Auxiliary Hydraulic options, with the exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com) | |
| For use with | Offset Boom | |
| 461866 | HAM OFB ELET PRO CNTRL | \$6,564.00 |
| | Hammer Circuit Offset Boom Electrical Proportional Control | |
| | For use with Offset Boom option 461025 only | |
| | Joystick activated | |
| | Provides single direction flow; use for hammer application | |
| | Includes manually adjustable relief valve to set required pressures | |
| | Notes: | |
| | 1) Not for use other Auxiliary Hydraulics options, with the | |
| | exception of Low Flow. | |
| | Heavy duty bucket linkage is standard equipment on C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com). | |



(Ex Works Port of Entry)

| | 404000 | LIAM/UE FLET PRO CNITRI | \$0,004.00 |
|--------|--------|---|------------|
| | 461868 | HAM/HF ELET PRO CNTRL | \$8,961.00 |
| | | Hammer/High Flow Circuit, Electrical Proportional Control | |
| | | Not for use with Offset Boom option 461025 | |
| | | Does not include the in-cab Electronic Pressure Control feature | |
| | | | |
| | | Joystick activated | |
| | | Provides single or dual pump, two-way flow, for use with | |
| | | multiple applications: thumb/grapples/crushers | |
| | | Secondary Low-flow Auxiliary Hydraulics can be added | |
| | | Includes manually adjustable relief valve to set required | |
| | | pressures | |
| | | Is switchable to single acting flow for hammer applications | |
| | | | |
| | | Notes: | |
| | | 1) Not for use with other Auxiliary Hydraulics options with the | |
| | | exception of Low Flow. | |
| | | 2) Heavy duty bucket linkage is standard equipment | |
| | | on C Series excavators. | |
| | | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | | HKX (1-800-493-5487 or www.HKX.com) | |
| | 461871 | AUX, TMB ELEC PRO CNTRL | \$5,315.00 |
| | | Auxiliary Circuit, Thumb, Electrical Proportional Control | |
| | | Not for use with Offset Boom option 461025 | |
| | | Joystick activated | |
| | | Provides single pump, two-way flow; use for thumb application | |
| | | Hydraulic plumbing provided to the end of the boom only, | |
| | | no piping to the arm | |
| | | This system is not switchable to single acting flow | |
| | | Notes: | |
| | | 1) Not for use other Auxiliary Hydraulics options with the | |
| | | exception of Low Flow. | |
| | | 2) Heavy duty bucket linkage is standard equipment on | |
| | | C series excavators. | |
| | | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | | | |
| \Box | | HKX (1-800-493-5487 or www.HKX.com). | |



| | | (Ex Works Port of Entry) | |
|--------|-------------|--|-------------------|
| | 461873 | DAC, OFB, ELCT PRO | \$6,200.00 |
| | | Double Acting Circuit, Offset, Electrical Proportional | , , , , , , , , , |
| | | For use with Offset Boom option 461025 only | |
| | | To use with offset boom option 401025 only | |
| | | Joystick activated | |
| | | Provides single pump, two-way flow; use for thumb application | |
| | | Hydraulic plumbing provided to the end of the boom only, | |
| | | no piping to the arm | |
| | | This system is not switchable to single acting flow | |
| | | The system is not omissinable to single asing non | |
| | | Notes: | |
| | | 1) Not for use other Auxiliary Hydraulics options with the | |
| | | exception of Low Flow. | |
| | | 2) Heavy duty bucket linkage is standard equipment on | |
| | | C series excavators. | |
| | | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | | HKX (1-800-493-5487 or www.HKX.com). | |
| | - | | |
| | SD_E6417 SE | CONDARY AUXILIARY HYDRAULICS | |
| Ш | XE6417X | No Extra Auxiliary Hydraulics | No Charge |
| | 461863 | LF ELCT PRO CNTRL | \$6,057.00 |
| | | Low Flow Electrical Proportional Control | |
| | | For use with Standard Boom option 481858 | |
| | | Joystick Activated | |
| | | Provides low-flow for rotation or tilt of hydraulic tools. | |
| | | | |
| | | Notes: | |
| | | 1) May be used standalone or with any Case Excavator Auxiliary | |
| | | Hydraulics option. | |
| | | 2) For dealer installed auxiliary hydraulic kits contact: | |
| Ш | | HKX (1-800-493-5487 or www.HKX.com). | |
| | 00 50400 00 | NITROL BATTERN OF FOTION | |
| П | | ONTROL PATTERN SELECTION | No Chargo |
| + | | No Control Pattern Valve | No Charge |
| ш | 461558 | Control Pattern Selector Valve | \$950.00 |
| | SD_E9730 SA | FETY VALVE | |
| | XE9730X | No Hose Burst Check Valve | No Charge |
| \Box | 461559 | Hose Burst Check Valve (HBCV) | \$9,130.00 |
| | | boom and arm | , , |
| | • | • | |
| | SD_E9740 SI | DE VIEW CAMERA | |
| | XE9740X | No Side View Camera | No Charge |
| | 461560 | Side View Camera | \$725.00 |
| | | | _ |

SD_E9741 FREE SWING

XE9741X No Free Swing

No Charge



(Ex Works Port of Entry)

| | 461568 | Free Swing | | \$285.00 |
|--|--------|------------------|--|----------|
| | | switch activated | | |

SD_E9874 REFUEL PUMP

| | XE9874X | No Refuel Pump | | No Charge |
|--|---------|----------------|--|------------|
| | 481257 | Refuel Pump | | \$1,050.00 |



(This page intentionally left blank)



(Ex Works Port of Entry)

Factory Supplied Attachments

| Order Co | de Description | Weight | Factory Data | List Price |
|---------------|---|----------|--------------|------------|
| ase Pin On | Buckets | | | |
| 844040 | | 969 LB | | \$3,402.00 |
| 844040 | 30" Heavy Duty Bucket with 4 teeth (.56 cu. yd.) | 1,073 LB | | \$3,546.00 |
| 84404 | 03 36" Heavy Duty Bucket with 5 teeth (.70 cu. yd.) | 1,227 LB | | \$3,841.00 |
| 844063 | 42" Heavy Duty Bucket with 5 teeth (.83 cu. yd.) | 1,351 LB | | \$4,315.00 |
| 84404 | 05 24" Extra Heavy Duty Bucket with 4 teeth (.51 cu. yd.) | 1,050 LB | | \$3,644.00 |
| 84404 | 08 30" Extra Heavy Duty Bucket with 4 teeth (.66 cu. yd.) | 1,200 LB | | \$4,044.00 |
| 84404 | 36" Extra Heavy Duty Bucket with 5 teeth (.81 cu. yd.) | 1,375 LB | | \$4,429.00 |
| 84404 | 42" Extra Heavy Duty Bucket with 5 teeth (.97 cu. yd.) | 1,500 LB | | \$4,727.00 |
| 84404 | 13 48" Ditching Bucket (.79 cu. yd.) | 860 LB | | \$3,452.00 |
| 84404 | 15 60" Ditching Bucket (1.02 cu. yd.) | 1,000 LB | | \$3,916.00 |
| ase Couple | Buckets | | | |
| 84404 | 17 24" Heavy Duty Coupler Bucket with 4 teeth (.43 cu. yd.) | 775 LB | | \$4,702.0 |
| 84404 | 18 30" Heavy Duty Coupler Bucket with 4 teeth (.56 cu. yd.) | 870 LB | | \$5,219.0 |
| 84404 | 19 36" Heavy Duty Coupler Bucket with 5 teeth (.70 cu. yd.) | 970 LB | | \$5,660.00 |
| 84404 | 21 42" Heavy Duty Coupler Bucket with 5 teeth (.83 cu. yd.) | 1,055 LB | | \$5,923.00 |
| Case Multi Fi | t Coupler | | | |
| 869915 | <u> </u> | 709 LB | | \$9,433.00 |



(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE: Isuzu AM-4JJ1X Tier-4a Interim Certified (cooled EGR) 183 cubic in. displacement/3.0 Liter Turbocharged/air cooled intercooler Horsepower: Net: 124 (92.2 kW) @ 2200 RPM High pressure common rail system Auto engine warm-up FEA (Fuel Economy Assist System) Engine Idle/Fuel Economy System: Auto Idle One-touch Idle Idle Shut-down Fuel Capacity: 79 gallons (90 L) AEC (auto economy control) BEC (boom economy control) OPERATOR'S CAB: ROPS protection Pressurized cab area AC/heat/defrost with auto control Electronics: Color monitor (7 in/180 mm) with Rearview camera view Rearview camera AM/FM radio with antenna and 2-speakers Aux-in port for personal electronics 12-volt electric socket 24-volt cigarette lighter KAB ® Air-suspension seat (cloth) Seat belt Adjustable arm rests 4-position tilting consoles Sliding cockpit (7 in/180 mm) Low-effort joystick controls Clear (poly carbonate) roof window External rearview mirrors Rubber floormat

```
OPERATOR'S CAB (Continued):
  Cab interior features:
    Cup holder
    Storage compartments
    Warm/cool storage compartments
    Easy access fuse box
    Interior dome light
    One touch lock front window
    One key start & lock-up
    Interior Light (1 x 10 watt)
  Two-speed independent travel
  Straight Travel
  Travel alarm and horn
  Windshield wiper and washer
  Programmable anti-theft system
ELECTRICAL:
  24-volt system
  Two batteries (12 volt/92 Ah)
  50 Amp Alternator
  Worklights (4 x 70 watt)
    Boom mounted (1)
    Upper mounted (1)
    Cab top mounted (2)
HYDRAULICS:
  Open-center system design
  Optional auxiliary hydraulics
  Selectable work modes (3)
 Auto power boost
 Auto swing priority
  SWC (swing relief control)
  SSC (spool stroke control)
  5000 hour hydraulic oil change interval
  1000 hour hyd. filter change interval
```



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

X-pattern carbody
Undercarriage:

STD LC: 13'1" (3.99 M) length

Track Gauge:

STD: 6'6" (1.99 M) gauge

Shoe:

STD: 23.6" triple grouser

7.5" pitch

44 shoes per side

Carrier rollers (2 per side)

Track rollers (7 per side)

Grease lubricated and strutted track

chains

Hydraulic track adjustment Single track chain guides

SAHR disc parking break

Tapered upper track frame

ATTACHMENTS:

Standard LC Version:

Boom: 1611" (5.15 M)

Arm: 87" (2.62 M)

Heavy-duty bucket linkage

Auxiliary pipe brackets

Attachment cushion valve

Arm and boom regeneration

Arm and boom holding valves

Centralized grease bank

OTHER BASIC EQUIPMENT:

CASE SiteWatch $^{\text{\tiny{M}}}$ - on board

telematics

OPTIONAL EQUIPMENT:

Cab and Operator's Station:

Side view camera

Sun visor

FOPS top cab guard (Level 2)

Front grill guard (2" x 2" mesh)

Front rock guard (OPG 1)

Front rock guard (OPG 2)

Vandal guard (not for use with FOPS

top cab guard)

Rain deflector

Control pattern change selector

Free swing

Hose burst check valve (HBCV)

Refueling Pump

Auxiliary hydraulics

Attachments:

Arm: 100" (3.05 M) Standard

Undercarriage:

Steel/triple-grouser: 27.6" (700 mm)

Track chain guides - triple

Order from Wholegood Attachments

-Third Party setion:

Buckets

Coupler/Case multi-pin grabber

Order from Service Parts:

Rubber bumpers for upper



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|-----------|--------------|--------------|
| CX160C STD LC | 39,500 LB | | \$221,953.00 |

List Price



CX160C CRAWLER EXCAVATOR (STD LC) US PRICE LIST

Weight

Factory Data

(Ex Works Port of Entry) Factory Supplied Options

Description

| ВС | OOMS | | |
|----|-------------|--|--------------|
| | | | |
| | SD_E5311 BC | DOM | |
| | 481858 | Standard Boom | No Charge |
| | | 16' 11" (5.15 m) Standard Boom | |
| | 781917 | No Boom | (\$5,540.00) |
| | | Less boom, hoist and arm cylinders and plumbing. | |
| | | Boom-foot and cylinder pins are provided. | |

| | SD_E5320 | ARM/DIPPERSTICK |
|--|----------|-----------------|
|--|----------|-----------------|

| | 781176 | 8' 7" (2.62 M) Standard Arm | | No Charge |
|---|---------|---------------------------------------|--|--------------|
| | 781178 | 9'11" (3.01M) Standard Arm | | \$2,870.00 |
| Ī | XE5320X | No Arm/Dipperstick | | (\$3,090.00) |
| ı | | Less arm, bucket cylinder and linkage | | |

TRACK SHOES

ARMS

Order Code

SD_E5199 TRACK SHOES

| ſ | 9560002 | 23.6" (600mm) Steel Shoes | | No Charge |
|---|---------|----------------------------|--|------------|
| L | | Triple-Grouser Steel Shoes | | |
| Ī | 9560003 | 27.6" (700mm) Steel Shoes | | \$1,770.00 |
| | | Triple-Grouser Steel Shoes | | |

LANGUAGE

SD_47083 OPERATOR'S MANUAL

| | 781981 | English Language Literature | | No Charge |
|--|--------|-----------------------------|--|-----------|
| | 461540 | French Canadian Language | | No Charge |
| | 781980 | Spanish Language Literature | | No Charge |



(Ex Works Port of Entry)

| ADDITION | NAL EQU | JIPMENT CXC | |
|----------|---------------------|--|------------|
| ADDITIO | NAL OPTI | ONS | |
| 7.551110 | | 0.10 | |
| SD_E | 5206 TR | ACK CHAIN GUIDE | |
| | 461541 | Single Track Chain Guide | No Charge |
| | 461143 | Triple Track Chain Guide | \$2,440.00 |
| 00.5 | E440 OA | D CHARD (FORC) | |
| | | B GUARD (FOPS) | No Charre |
| | 481070 | FOPS Top Cab Guard/Level 1 | No Charge |
| | 481070 | FOPS Top Cab Guard/Level 2 | \$1,290.00 |
| SD E | 5444 CA | B GUARD (FRONT) | |
| | | No Front Guard | No Charge |
| | 461142 | Front grill guard - 2 x 2 mesh | \$1,500.00 |
| | 781986 | Front rock guard (OPG 1) | \$2,045.00 |
| | | vertical bars (two piece/upper and lower) | |
| | 461024 | Front rock guard (OPG 2) | \$2,295.00 |
| | | vertical bars (one piece/full length) | |
| | 461552 | Vandal Guard | \$505.00 |
| | | Not for use with FOPS Top Cab Guard (option 481070) | |
| | | | |
| | | IN DEFLECTOR | |
| - | | No Rain Deflector | No Charge |
| | 461555 | Rain Deflector | \$390.00 |
| | | Not for use with Front grill guard - 2 x 2 mesh option 461142, | |
| | | Front rock guard (OPG 1) option 781986, or | |
| | | Front rock guard (OPG 2) option 461024. | |
| SD E | 5451 SU | N VISOR | |
| | | No Sun Visor | No Charge |
| | 461554 | Sun Visor | \$125.00 |
| | 70 100 1 | Curi visor | Ι ψ123.00 |
| SD_E | 6410 AU | XILIARY HYDRAULICS | |
| | XE6410X | No Optional Hydraulics | No Charge |



(Ex Works Port of Entry)

| | (Ex Works For Circle Entry) | | |
|--------|---|--|------------|
| 461865 | HAM ELCT PRO CNTRL | | \$6,589.00 |
| | Hammer Circuit Electrical Proportional Control | | |
| | Joystick activated | | |
| | Provides single direction flow; use for hammer application | | |
| | Includes manually adjustable relief valve to set required pressures | | |
| | | | |
| | Notes: | | |
| | 1) Not for use with other Auxiliary Hydraulic options, with the | | |
| | exception of Low Flow. | | |
| | 2) Heavy duty bucket linkage is standard equipment on | | |
| | C series excavators. | | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | | |
| | HKX (1-800-493-5487 or www.HKX.com) | | |
| 461868 | HAM/HF ELET PRO CNTRL | | \$9,258.00 |
| | Hammer/High Flow Circuit, Electrical Proportional Control | | |
| | | | |
| | Does not include the in-cab Electronic Pressure Control feature | | |
| | Joystick activated | | |
| | Provides single or dual pump, two-way flow, for use with | | |
| | multiple applications: thumb/grapples/crushers | | |
| | Secondary Low-flow Auxiliary Hydraulics can be added | | |
| | Includes manually adjustable relief valve to set required | | |
| | pressures | | |
| | Is switchable to single acting flow for hammer applications | | |
| | | | |
| | Notes: | | |
| | 1) Not for use with other Auxiliary Hydraulics options with the | | |
| | exception of Low Flow. | | |
| | 2) Heavy duty bucket linkage is standard equipment | | |
| | on C Series excavators. | | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | | |
| | HKX (1-800-493-5487 or www.HKX.com) | | |



| | (Ex Works Port of Entry) | |
|------------|---|------------|
| 461871 | AUX, TMB ELEC PRO CNTRL | \$5,449.00 |
| | Auxiliary Circuit, Thumb, Electrical Proportional Control | |
| | Joystick activated | |
| | Provides single pump, two-way flow; use for thumb application | |
| | Hydraulic plumbing provided to the end of the boom only, | |
| | no piping to the arm | |
| | This system is not switchable to single acting flow | |
| | Notes: | |
| | 1) Not for use other Auxiliary Hydraulics options with the | |
| | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com). | |
| SD_E6417 S | ECONDARY AUXILIARY HYDRAULICS | |
| XE6417 | No Extra Auxiliary Hydraulics | No Charge |
| 461863 | LF ELCT PRO CNTRL | \$6,092.00 |
| | Low Flow Electrical Proportional Control | |
| | Joystick Activated | |
| | Provides low-flow for rotation or tilt of hydraulic tools. | |
| I | | |

SD E6423 CONTROL PATTERN SELECTION

Hydraulics option.

| OB_LORGO CONTROL FANTERIA GELECTION | | | | | |
|-------------------------------------|---------|--------------------------------|--|--|-----------|
| | XE6423X | No Control Pattern Valve | | | No Charge |
| | 461558 | Control Pattern Selector Valve | | | \$950.00 |

1) May be used standalone or with any Case Excavator Auxiliary

2) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com).

SD_E9730 SAFETY VALVE

| | XE9730 | No Hose Burst Check Valve | | No Charge |
|--|--------|-------------------------------|--|------------|
| | 461559 | Hose Burst Check Valve (HBCV) | | \$9,130.00 |
| | | boom and arm | | |

SD_E9740 SIDE VIEW CAMERA

| L | | XE9740X | No Side View Camera | | No Charge |
|---|--|---------|---------------------|--|-----------|
| | | 461560 | Side View Camera | | \$725.00 |

SD_E9741 FREE SWING

| | XE9741X | No Free Swing | | No Charge |
|---|---------|------------------|--|-----------|
| Ī | 461568 | Free Swing | | \$285.00 |
| L | | switch activated | | |



(Ex Works Port of Entry)

SD_E9874 REFUEL PUMP

| | XE9874X | No Refuel Pump | | No Charge |
|--|---------|----------------|--|------------|
| | 481257 | Refuel Pump | | \$1,050.00 |



(Ex Works Port of Entry) Factory Supplied Attachments

| Order Code | Description | Weight | Factory Data | List Price |
|------------------|--|----------|--------------|------------|
| ase Coupler Bud | ckets | | | |
| 84404140 | 24" Heavy Duty Coupler Bucket with 4 teeth (.51 cu. yd.) | 1,030 LB | | \$5,186.00 |
| 84404141 | 30" Heavy Duty Coupler Bucket wtih 4 teeth (.66 cu. yd.) | 1,160 LB | | \$5,682.00 |
| 84404142 | 36" Heavy Duty Coupler Bucket with 5 teeth (.81 cu. yd.) | 1,265 LB | | \$5,992.00 |
| 84404143 | 42" Heavy Duty Coupler Bucket with 5 teeth (.97 cu. yd.) | 1,400 LB | | \$6,335.00 |
| ase Multi Fit Co | upler | | | |
| 429659A1 | Case Multi Fit Hydraulic Coupler Optimized for use with Case coupler buckets. Also can be used with a wide range of buckets from other manufacturers including pin-on types. Includes hydraulic installation kit and instructions. | 887 LB | | \$9,589.00 |
| ase Pin On Bucl | kets | | | |
| 84404124 | 24" Heavy Duty Bucket with 4 teeth (.51 cu. yd.) | 1,000 LB | | \$4,124.00 |
| 84404125 | 30" Heavy Duty Bucket with 4 teeth (.66 cu. yd.) | 1,085 LB | | \$4,290.00 |
| 84404126 | 36" Heavy Duty Bucket with 5 teeth (.81 cu. yd.) | 1,185 LB | | \$4,536.00 |
| 84404129 | 42" Heavy Duty Bucket with 5 teeth (.97 cu. yd.) | 1,265 LB | | \$4,803.00 |
| 84404131 | 24" Extra Heavy Duty Bucket with 4 teeth (.58 cu. yd.) | 1,220 LB | | \$4,064.00 |
| 84404132 | 30" Extra Heavy Duty Bucket with 4 teeth (.76 cu. yd.) | 1,375 LB | | \$4,352.00 |
| 84404133 | 36" Extra Heavy Duty Bucket with 5 teeth (.93 cu. yd.) | 1,550 LB | | \$4,607.00 |
| 84404134 | 42" Heavy Duty Bucket wtih 5 teeth (1.11 cu. yd.) | 1,700 LB | | \$5,068.00 |
| | 401 Ditabine Dualest (70 av. vol.) | 860 LB | | \$3,230.00 |
| 84404136 | 48" Ditching Bucket (.79 cu. yd.) | 000 LB | | φ3,230.00 |



(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE: OPERATOR'S CAB (Cont'd): Isuzu AM-4HK1X Cab interior features: Tier-4a Interim Certified (cooled EGR) Cup holder 317 cubic in. displacement/5.2 Liter Storage compartments Turbocharged/air cooled intercooler Warm/cool storage compartments Horsepower: Easy access fuse box Net: 160 (119.3 kW) @ 1800 RPM Interior dome light One touch lock front window High pressure common rail system Auto engine warm-up One key start & lock-up Interior light (1 x 10 watt) FEA (Fuel Economy Assist System) Engine Idle/Fuel Economy System: Two-speed independent travel Auto Idle Straight travel One-touch Idle Travel alarm and horn Idle Shut-down Windshield wiper and washer Fuel Capacity: Programmable anti-theft system 108 gallons (410 L) AEC (auto economy control) ELECTRICAL: BEC (boom economy control) 24-volt system Two batteries (12 volt/92 Ah) OPERATOR'S CAB: 50 Amp Alternator ROPS protection Worklights (4 x 70 watt) Pressurized cab area Boom mounted (1) AC/heat/defrost w/auto control Upper mounted (1) Electronics: Cap top mounted (2 x 70 watt) Color monitor (7 in/180 mm) Telematics Ready with Rearview camera view Wiring harness and 16-pin connector Rearview camera AM/FM radio with antenna and HYDRAULICS: 2-speakers Open-center system design Aux-in port for personal electronics Optional auxiliary hydraulics 12-volt electric socket Selectable work modes (3) 24-volt cigarette lighter Auto power boost Air-suspension seat (cloth) Auto swing priority SWC (swing relief control) KAB® adjustable deluxe seat Seat belt - 3" SSC (spool stroke control) Adjustable arm rests 5000 hour hydraulic oil change interval 4-position tilting consoles 1000 hour hyd. filter change interval Sliding cockpit (7 in/180 mm) Low-effort joystick controls Clear (poly carbonate) roof window External rearview mirrors Rubber floormat



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE: OPTIONAL EQUIPMENT: X-pattern carbody Cab and Operator's Station: Undercarriage: Side view camera STD LC: 14' 8" (4.47 M) length Sun visor STD LC: 10'6" (3.19 M) width FOPS top cab guard (Level 2) Narrow: 14' 8" (4.47 M) length Front grill guard (2" x 2" mesh) Narrow: 8'6" (2.59 M) width Front rock guard (OPG 1) Front rock guard (OPG 2) (with 600 mm shoes) Track Gauge: Vandal guard (not for use with FOPS STD LC: 7'10" (2.4 M) gauge top cab guard) Narrow: 6' 5" (1.99 M) guage Rain deflector Shoe: Control pattern change selector STD: 31.5" (800 mm) triple grouser Free swing Narrow: 23.6" (600 mm) triple gouser Hose burst check valve (HBCV) 7.5" pitch Refueling Pump Auxiliary hydraulics 49 shoes per side Attachments: Carrier rollers (2 per side) Track rollers (8 per side) Arm: 7'10" (2.40 M) Heavy-duty Grease lubricated and strutted track Undercarriage: Steel shoes/triple-grouser: chains 23.6" (600 mm) Hydraulic track adjustment Single track chain guides Steel shoes/triple-grouser: 27.6" (700 mm) SAHR disc parking break Rubber shoes 23.6" (600 mm) Tapered upper track frame Track chain guides - triple ATTACHMENTS: High Ambient Temperature Cooling Standard LC Version: Package Boom: 18'8" (5.70 M) Arm: 98" (2.94 M) Order from Wholegood Attachments Heavy-duty bucket linkage -Third Party setion: Auxiliary pipe brackets Buckets Attachment cushion valve Coupler/Case multi-pin grabber Arm and boom regeneration Order from Service Parts: Arm and boom holding valves Rubber bumpers for upper Centralized grease bank OTHER BASIC EQUIPMENT:

CASE SiteWatch™ - on board

telematics



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|-----------|--------------|--------------|
| CX210C STD LC | 42,000 LB | | \$266,206.00 |
| CX210C NRRW | 42,000 LB | | \$265,661.00 |



(Ex Works Port of Entry) Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|------------|-------------|--------|--------------|------------|
| | | | | |

BOOMS

SD_E5311 BOOM

| | 481858 | Standard Boom | | No Charge |
|--|--------|--|--|--------------|
| | | 18'8" (5.70 M) Standard Boom | | |
| | 781917 | No Boom | | (\$6,220.00) |
| | | Less boom, hoist and arm cylinders and plumbing. | | |
| | | Boom-foot and cylinder pins are provided. | | |

ARMS

SD_E5320 ARM/DIPPERSTICK

| | 461501 | 7'10" (2.40 M) Heavy-duty Arm | | (\$315.00) |
|--|---------|---|--|--------------|
| | | For use with 18'8" Standard Boom (option 481858) | | |
| | | (Recommended for heavy-duty applications - example: hammer) | | |
| | 481268 | 9'8" (2.94 M) Arm | | No Charge |
| | | For use with 18'8" Standard Boom (option 481858) | | |
| | XE5320X | No Arm/Dipperstick | | (\$3,452.00) |
| | | Less arm, bucket cylinder and linkage | | |

TRACK SHOES

SD_E5199 TRACK SHOES

| 9560002 | 23.6" (600mm) Steel Shoes | (\$1,534.00) |
|---------|--|--------------|
| | Triple-Grouser Steel Shoes | |
| | Standard equipment on CX210C NRRW commercial model | |
| | only. | |
| 9560003 | 27.6" (700mm) Steel Shoes | (\$250.00) |
| | Triple-Grouser Steel Shoes | |
| | For use with CX210C STD LC commercial model only | |
| 9560005 | 31.5" (800mm) Steel Shoes | No Charge |
| | Triple-Grouser Steel Shoes | |
| | For use with CX210C STD LC commercial model only | |
| 9560055 | 23.6" (600 mm) Rubber Pads | \$13,982.00 |
| | Rubber pads molded to steel base on standard chain | |
| | For use with CX210C STD L and CX210C NRRW | |
| | commercial models | |



(Ex Works Port of Entry)

| LANGUAGE | | |
|--------------------|---|-----------------------|
| LANGUAGE | | |
| | | |
| SD 47083 | OPERATOR'S MANUAL | |
| 78198 | | No Charge |
| 461540 | | No Charge |
| 781980 | | No Charge |
| | | |
| ADDITIONAL E | QUIPMENT CXC | |
| | | |
| ADDITIONAL O | PTIONS | |
| | | |
| SD_E5206 | TRACK CHAIN GUIDE | |
| 46154 ⁻ | | No Charge |
| 461143 | Triple Track Chain Guide | \$2,440.00 |
| | | |
| | COOLING PACKAGE | |
| XE540 | 7X No Optional Cooling Package | No Charge |
| | Includes standard cooling package for temperatures | |
| 481027 | up to 110° F/43° C | ¢4.005.00 |
| 46102 | High Ambient Cooling Package High ambient temperature cooling package | \$1,095.00 |
| | Note: Recommended for machines operating in high heat | |
| | conditions not to exceed 122°F (50°C) | |
| | Conditions not to exceed 122 1 (30 C) | |
| SD E5443 | CAB GUARD (FOPS) | |
| | 3X FOPS Top Cab Guard/Level 1 | No Charge |
| 481070 | | \$1,290.00 |
| | | |
| SD_E5444 | CAB GUARD (FRONT) | |
| XE544 | 4X No Front Guard | No Charge |
| 461142 | 0 0 | \$1,500.00 |
| 781986 | š , , | \$2,045.00 |
| | vertical bars (two piece/upper and lower) | |
| 461024 | š ` , | \$2,295.00 |
| | vertical bars (one piece/full length) | |
| 461552 | | \$505.00 |
| | Not for use with FOPS Top Cab Guard (option 481070) | |
| CD F5440 | DAIN DEFLECTOR | |
| | RAIN DEFLECTOR 9X No Rain Deflector | No Observe |
| 46155 | | No Charge \$390.00 |
| 401550 | Not for use with Front grill guard - 2 x 2 mesh option 461142, | \$390.00 |
| | Front work ground (ODC 4) antion 704000 ar | |

Front rock guard (OPG 1) option 781986, or Front rock guard (OPG 2) option 461024.



(Ex Works Port of Entry)

SD_E5451 SUN VISOR

| | XE5451X | No Sun Visor | | No Charge |
|--|---------|--------------|--|-----------|
| | 461554 | Sun Visor | | \$125.00 |

SD E6410 AUXILIARY HYDRAULICS

| | AUXILIARY HYDRAULICS | |
|--------|---|-------------|
| XE6410 | X No Optional Hydraulics | No Charge |
| 461865 | HAM ELCT PRO CNTRL | \$7,703.00 |
| 1 1 1 | Hammer Circuit Electrical Proportional Control | |
| 1 1 1 | Joystick activated | |
| | Provides single direction flow; use for hammer application | |
| | Includes manually adjustable relief valve to set required pressures | |
| | Notes: | |
| | 1) Not for use with other Auxiliary Hydraulic options, with the | |
| | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| 1 1 1 | 3) For dealer installed auxiliary hydraulic kits contact: | |
| 1 1 1 | HKX (1-800-493-5487 or www.HKX.com) | |
| 461869 | HAM/HF W/PRSR ELET PRO CNTRL | \$11,796.00 |
| 1 1 1 | Hammer/High Flow Circuit, with Pressure Control, Electrical | |
| | Proportional Control | |
| | Includes in-cab Electronic Pressure Control feature | |
| | Joystick Activated | |
| | Pressure Control feature allows hydraulic pressure setting | |
| | from the cab monitor and maintaining pressure settings in | |
| | memory when multiple tools are used. | |
| | Provides single or dual pump, two-way flow, for use with | |
| | multiple applications: thumb/grapples/crushers. | |
| | Secondary Low-flow Auxiliary Hydraulics can be added | |
| | Includes in-cab electronically controlled pressure setting feature | |
| | Is switchable to single acting flow for hammer application. | |
| | Notes: | |
| | 1) Not for use with other Auxiliary Hydraulics options, with the | |
| | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com) | |



| | (Ex Works Port of Entry) | | |
|-------------|--|---|------------|
| 461871 | AUX, TMB ELEC PRO CNTRL | | \$5,981.00 |
| | Auxiliary Circuit, Thumb, Electrical Proportional Control | | |
| | Joystick activated | | |
| | Provides single pump, two-way flow; use for thumb application | | |
| | Hydraulic plumbing provided to the end of the boom only, | | |
| | no piping to the arm | | |
| | This system is not switchable to single acting flow | | |
| | Notes: | | |
| | 1) Not for use other Auxiliary Hydraulics options with the | | |
| | exception of Low Flow. | | |
| | 2) Heavy duty bucket linkage is standard equipment on | | |
| | C series excavators. | | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | | |
| | HKX (1-800-493-5487 or www.HKX.com). | | |
| | | | |
| | ECONDARY AUXILIARY HYDRAULICS | 1 | T |
| | No Extra Auxiliary Hydraulics | | No Charge |
| 461863 | LF ELCT PRO CNTRL | | \$6,380.00 |
| | Low Flow Electrical Proportional Control | | |
| | Joystick Activated | | |
| | Provides low-flow for rotation or tilt of hydraulic tools. | | |
| | Notes: | | |
| | 1) May be used standalone or with any Case Excavator Auxiliary | | |
| | Hydraulics option. | | |
| | 2) For dealer installed auxiliary hydraulic kits contact: | | |
| | HKX (1-800-493-5487 or www.HKX.com). | | |
| | | | |
| SD_E6423 C | ONTROL PATTERN SELECTION | | |
| XE6423X | No Control Pattern Valve | | No Charge |
| 461558 | Control Pattern Selector Valve | | \$950.00 |
| SD E0720 S | NEETY MALME | | |
| SD_E9730 S/ | No Hose Burst Check Valve | | No Charge |
| 461559 | Hose Burst Check Valve (HBCV) | | \$9,130.00 |
| 401339 | boom and arm | | ψθ,130.00 |
| | NOOM WIN WITH | 1 | |

SD_E9740 SIDE VIEW CAMERA

SD_E9741 FREE SWING

461568

XE9740X No Side View Camera

Free Swing

switch activated

461560 Side View Camera

XE9741X No Free Swing

No Charge

No Charge

\$285.00

\$725.00



(Ex Works Port of Entry)

SD_E9874 REFUEL PUMP

| XE9874X | No Refuel Pump | | No Charge |
|---------|----------------|--|------------|
| 481257 | Refuel Pump | | \$1,050.00 |

SD_E6300 EXCAVATOR BUCKET(S)

| | XE6300X | No Bucket (E6300) | | No Charge |
|---|---------|--|--|-----------|
| | | Buckets may be ordered using Order Codes listed in the | | |
| L | | Direct Ship Attachment Section | | |



(Ex Works Port of Entry)

Factory Supplied Attachments

| Order Code | Description | Weight | Factory Data | List Price |
|-------------------|--|----------|--------------|-------------|
| ase Coupler Bud | ekets | | | |
| 84404187 | 24" Heavy Duty Coupler Bucket with 4 teeth (.63 cu. yd.) | 1,350 LB | | \$6,252.00 |
| 84404188 | 30" Heavy Duty Coupler Bucket with 4 teeth (.82 cu. yd.) | 1,525 LB | | \$6,875.00 |
| 84404189 | 36" Heavy Duty Coupler Bucket with 5 teeth (1.02 cu. yd.) | 1,660 LB | | \$7,565.00 |
| 84404190 | 42" Heavy Duty Coupler Bucket with 5 teeth (1.20 cu. yd.) | 1,835 LB | | \$8,323.00 |
| 84404191 | 48" Heavy Duty Coupler Bucket with 6 teeth (1.48 cu. yd.) | 1,990 LB | | \$8,795.00 |
| ase Multi Fit Cou | upler | | | |
| 405487A1 | Case Multi Fit Hydraulic Coupler Optimized for use with Case coupler buckets. Also can be used with a wide range of buckets from other manufacturers including pin-on types. Includes hydraulic installation kit and instructions. | 945 LB | | \$10,164.00 |
| ase Pin On Buck | rets | | | |
| 84404166 | 24" Heavy Duty Bucket with 4 teeth (.55 cu. yd.) | 1,420 LB | | \$4,612.00 |
| 84404167 | 30" Heavy Duty Bucket with 4 teeth (.73 cu. yd.) | 1,630 LB | | \$5,164.00 |
| 84404168 | 36" Heavy Duty Bucket with 5 teeth (.90 cu. yd.) | 1,835 LB | | \$5,635.00 |
| 84404169 | 42" Heavy Duty Bucket with 5 teeth (1.08 cu. yd.) | 1,975 LB | | \$6,075.00 |
| 84404170 | 24" Heavy Duty High Capacity Bucket with 4 teeth (.75 cu. yd.) | 1,500 LB | | \$4,987.00 |
| 84404175 | 30" Heavy Duty High Capacity Bucket with 4 teeth (.94 cu. yd.) | 1,700 LB | | \$5,510.00 |
| 84404178 | 36" Heavy Duty High Capacity Bucket with 5 teeth (1.15 cu. yd.) | 1,925 LB | | \$6,090.00 |
| 84404179 | 42" Heavy Duty High Capacity Bucket with 5 teeth (1.37 cu. yd.) | 2,110 LB | | \$6,395.00 |
| 84404180 | 48" Heavy Duty High Capacity Bucket with 6 teeth (1.59 cu. yd.) | 2,340 LB | | \$6,988.00 |
| 84404181 | 24" Severe Duty Bucket with 4 teeth (.55 cu. yd.) | 1,635 LB | | \$6,235.00 |
| 84404182 | 30" Severe Duty Bucket with 4 teeth (.73 cu. yd.) | 1,875 LB | | \$6,985.00 |
| 84404183 | 36" Severe Duty Bucket with 5 teeth (.90 cu. yd.) | 2,110 LB | | \$7,823.00 |
| 84404184 | 42" Severe Duty Bucket with 5 teeth (1.08 cu. yd.) | 2,270 LB | | \$8,094.00 |
| 84404185 | 60" Ditching Bucket (1.02 cu. yd.) | 1,000 LB | | \$4,177.00 |
| 84404186 | 72" Ditching Bucket (1.22 cu. yd.) | 1,000 LB | | \$4,524.0 |



(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

```
Isuzu AM-4HK1X
 Tier-4a Interim Certified (cooled EGR)
  317 cubic in. displacement/5.2 Liter
 Turbocharged/air cooled intercooler
 Horsepower:
   Net: 160 (119.3 kW) @ 1800 RPM
 High pressure common rail system
 Auto engine warm-up
 FEA (Fuel Economy Assist System)
 Engine Idle System/Fuel Economy
 System:
   Auto Idle
   One-touch Idle
   Idle Shut-down
 Fuel Capacity:
    108 gallons (410 L)
 AEC (auto economy control)
 BEC (boom economy control)
OPERATOR'S CAB:
 ROPS protection
 Pressurized cab area
 AC/heat/defrost w/climate control
 Electronics:
   Color monitor (7 in/180 mm)
      with Rearview camera view
   Rearview camera
    AM/FM radio with antenna and
      2-speakers
   Aux-in port for personal electronics
    12-volt electric socket
    24-volt cigarette lighter
 Air-suspension seat (cloth)
   KAB® adjustable deluxe seat
    Seat belt - 3"
   Adjustable arm rests
    4-position tilting consoles
    Sliding cockpit (7 in/180 mm)
 Low-effort joystick controls
  Clear (poly carbonate) roof window
  External rearview mirrors
 Rubber floormat
```

ENGINE:

```
OPERATOR'S CAB (Cont'd):
  Cab interior features:
    Cup holder
    Storage compartments
    Warm/cool storage compartments
    Easy access fuse box
    One touch lock front window
    One key start & lock-up
    Interior Light (1 x 10 watt)
  Two-speed independent travel
  Straight travel
  Travel alarm and horn
  Windshield wiper and washer
  Programmable anti-theft system
ELECTRICAL:
  24-volt system
  Two batteries (12 volt/92 Ah)
  50 Amp Alternator
  Worklights (4 x 70 watt)
    Boom mounted (1)
    Upper mounted (1)
    Cab top mounted (2)
  Telematics ready
    Wiring harness and 16-pin connector
HYDRAULICS:
  Open-center system design
  Selectable work modes (3)
 Auto power boost
 Auto swing priority
  SWC (swing relief control)
  SSC (spool stroke control)
  5000 hour hydraulic oil change interval
  1000 hour hyd. filter change interval
```



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

X-pattern carbody
Undercarriage:

STD LC: 14'7" (4.47 M) length

Track Gauge:

STD LC: 8'6" (2.6 M) gauge

Shoe:

STD: 31.5" (800 mm) triple grouser

7.5" pitch

49 shoes per side

Carrier rollers (2 per side)

Track rollers (8 per side)

Grease lubricated and strutted track

chains

Hydraulic track adjustment

Single track chain guides

SAHR disc parking break

Tapered upper track frame

ATTACHMENTS:

Standard LC Version:

Boom: 287" (8.70 M)

Arm: 21'0" (6.40 M)

Heavy-duty bucket linkage

Auxiliary pipe brackets

Attachment cushion valve

Arm and boom regeneration

Arm and boom holding valves

Centralized grease bank

OTHER BASIC EQUIPMENT:

CASE SiteWatch $^{\text{M}}$ - on board

telematics

OPTIONAL EQUIPMENT:

Cab and Operator's Station:

Side view camera

Sun visor

FOPS top cab guard (Level 2)

Front grill guard (2" x 2" mesh)

Front rock guard (OPG 1)

Front rock guard (OPG 2)

Vandal guard (not for use with

FOPS top cab guard)

Rain deflector

Control pattern change selector

Free swing

Hose burst check valve (HBCV)

Refueling Pump

Track chain guides - triple

High Ambient Temperature Cooling

Package

Auxiliary Hydraulics

Order from Wholegood Attachments

-Third Party setion:

Buckets

Coupler/Case multi-pin grabber

Order from Service Parts:

Rubber bumpers for upper



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|-----------|--------------|--------------|
| CX210C LR | 49,090 LB | | \$291,772.00 |



(Ex Works Port of Entry) Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|----------------|--|--------|--------------|------------|
| | | | | |
| BOOMS | | | | |
| | | | | |
| SD_E5311 B0 | OOM | | | |
| 461029 | Standard Long Reach Boom | | | No Charge |
| | 28'7" (8.70 M) Long Reach Boom | | | |
| ARMS | | | | |
| | | | | |
| SD_E5320 AI | RM/DIPPERSTICK | | | |
| 481248 | 21'0" (6.40 M) Arm | | | No Charge |
| | | | | |
| TRACK SHOES | | | | |
| | | | | |
| SD_E5199 TF | | _ | | |
| 9560005 | 1 ' ' | | | No Charge |
| | Triple-Grouser Steel Shoes | ļ | | |
| LANGUAGE | | | | |
| | | | | |
| 05 47000 01 | DED ATODIO MANUAL | | | |
| 781981 | PERATOR'S MANUAL English Language Literature | | | No Charge |
| 461540 | French Canadian Language | | | No Charge |
| 781980 | Spanish Language Literature | | | No Charge |
| | | | | |
| ADDITIONAL EQ | UIPMENT CXC | | | |
| ADDITIONAL OPT | TIONS | | | |
| | | | | |
| | RACK CHAIN GUIDE | | | |
| 461541 | Single Track Chain Guide | | | No Charge |
| 461143 | Triple Track Chain Guide | | | \$2,440.00 |
| SD_E5407_C | OOLING PACKAGE | | | |
| XE5407X | No Optional Cooling Package | | | No Charge |
| | Includes standard cooling package for temperatures | | | |
| | up to 110° F/43° C | | | |



CX210C LONG REACH CRAWLER EXCAVATOR (LR) US PRICE LIST

| 481027 | High Ambient Cooling Package | | \$1,095 |
|-------------|--|-----|-----------|
| | High ambient temperature cooling package | | |
| | Note: Recommended for machines operating in high heat | | |
| | conditions not to exceed 122°F (50°C) | | |
| SD E5443 C | AB GUARD (FOPS) | | |
| XE5443X | FOPS Top Cab Guard/Level 1 | | No Cha |
| 481070 | FOPS Top Cab Guard/Level 2 | | \$1,290 |
| SD E5444 C | AB GUARD (FRONT) | | |
| | No Front Guard | | No Cha |
| 461142 | Front grill guard - 2 x 2 mesh | | \$1,500 |
| 781986 | Front rock guard (OPG 1) | | \$2,045 |
| | vertical bars (two piece/upper and lower) | | |
| 461024 | Front rock guard (OPG 2) | | \$2,295 |
| | vertical bars (one piece/full length) | | |
| 461552 | Vandal Guard | | \$505 |
| | Not for use wtih FOPS Top Cab Guard (option 481070) | | |
| SD_E5449 R | AIN DEFLECTOR | | |
| | No Rain Deflector | | No Cha |
| 461555 | Rain Deflector | | \$390 |
| | Not for use with Front grill guard - 2 x 2 mesh option 461142, | | |
| | Front rock guard (OPG 1) option 781986, or | | |
| | Front rock guard (OPG 2) option 461024. | | |
| SD_E5451 SI | IN VISOR | | |
| | No Sun Visor | | No Cha |
| 461554 | Sun Visor | | \$125 |
| | , | ! ! | , , , , , |
| | CONDARY AUXILIARY HYDRAULICS | | |
| | No Extra Auxiliary Hydraulics | | No Cha |
| XE6417X | , | | |
| | LF ELCT PRO CNTRL | | \$8,166 |
| XE6417X | Low Flow Electrical Proportional Control | | \$8,166 |
| XE6417X | Low Flow Electrical Proportional Control Joystick Activated | | \$8,166 |
| XE6417X | Low Flow Electrical Proportional Control | | \$8,160 |
| XE6417X | Low Flow Electrical Proportional Control Joystick Activated | | \$8,166 |
| XE6417X | Low Flow Electrical Proportional Control Joystick Activated Provides low-flow for rotation or tilt of hydraulic tools. | | \$8,166 |
| XE6417X | Low Flow Electrical Proportional Control Joystick Activated Provides low-flow for rotation or tilt of hydraulic tools. Notes: | | \$8,166 |
| XE6417X | Low Flow Electrical Proportional Control Joystick Activated Provides low-flow for rotation or tilt of hydraulic tools. Notes: 1) May be used standalone or with any Case Excavator Auxiliary | | \$8,160 |

XE6423X No Control Pattern Valve

461558 Control Pattern Selector Valve

No Charge

\$950.00



CX210C LONG REACH CRAWLER EXCAVATOR (LR) US PRICE LIST

(Ex Works Port of Entry)

| SD_E9730 SAFETY VALVE | |
|---------------------------------------|--------------------|
| XE9730X No Hose Burst Check Valve | No Charge |
| 461559 Hose Burst Check Valve (HBCV) | \$9,130.00 |
| boom and arm | |
| | |
| SD_E9740 SIDE VIEW CAMERA | |
| XE9740X No Side View Camera | No Charge |
| 461560 Side View Camera | \$725.00 |
| | |
| SD_E9741 FREE SWING | |
| XE9741X No Free Swing | No Charge |
| 461568 Free Swing | \$285.00 |
| switch activated | |
| | |
| SD_E9874 REFUEL PUMP | |
| XE9874X No Refuel Pump | No Charge |
| 481257 Refuel Pump | \$1,050.00 |
| | |
| | |
| SD_E6300 EXCAVATOR BUCKET(S) | |
| XE6300X No Bucket (E6300) | No Charge |
| Buckets may be ordered using Order Co | odes listed in the |

Factory Supplied Attachments section



CX210C LONG REACH CRAWLER EXCAVATOR (LR) US PRICE LIST

(Ex Works Port of Entry)

Factory Supplied Attachments

| | Order Code | Description | Weight | Factory Data | List Price |
|---------------------|------------|------------------------------------|----------|--------------|------------|
| Case Pin On Buckets | | | | | |
| | 84404113 | 48" Ditching Bucket (.79 cu. yd.) | 860 LB | | \$3,452.00 |
| | 84404115 | 60" Ditching Bucket (1.02 cu. yd.) | 1,000 LB | | \$3,916.00 |



(This page intentionally left blank)



CX235C MIN SWING RADIUS EXCAVATOR **US PRICE LIST**

(Ex Works Port of Entry) Standard Equipment

ENGINE: Isuzu AM-4HK1X Tier-4 Interim Certified (CEGR) 317 cubic in. displacement/5.2 Liter Turbocharged/air cooled intercooler Horsepower: Net: 160 (119.3 kW) @ 1800 RPM High pressure common rail system Auto engine warm-up FEA (Fuel Economy Assist System) Engine Idle/Fuel Economy System: Auto Idle One-touch Idle Idle Shut-down Fuel Capacity: 85 gallons (320 L) AEC (auto economy control) BEC (boom economy control) OPERATOR'S CAB: ROPS protection Pressurized cab area AC/heat/defrost with auto control Electronics: Color monitor (7 in/180 mm) with rearview camera view Rearview camera AM/FM radio with antenna and 2-speakers Aux-in port for personal electronics 12-volt electric socket 24-volt cigarette lighter Air-suspension seat (cloth) KAB® adjustable deluxe seat with 3" seat-belt Adjustable arm rests 4-position tilting consoles Sliding cockpit (7 in/180 mm) Low-effort joystick controls Clear (poly carbonate) roof window

External rearview mirrors

Rubber floormat

```
OPERATOR'S CAB (Cont'd):
  Cab interior features:
    Cup holder
    Storage compartments
    Easy access fuse box
    One touch lock front window
    One key start & lock-up
    Interior Light (1 x 10 watt)
  Two-speed independent travel
  Straight travel
  Travel alarm and horn
  Windshield wiper and washer
  Programmable anti-theft system
ELECTRICAL:
  24-volt system
  Two batteries (12 volt/92 Ah)
  50 Amp Alternator
 Worklights (2 x 70 watt)
    Boom mounted (1)
    Upper mounted (1)
```

HYDRAULICS:

Open-center system design Optional auxiliary hydraulics Selectable work modes (3) Auto power boost Auto swing priority SWC (swing relief control) SSC (spool stroke control) 5000 hour hydraulic oil change interval 1000 hour hyd. filter change interval



CX235C MIN SWING RADIUS EXCAVATOR US PRICE LIST

OPTIONAL EQUIPMENT

(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE: X-pattern carbody Undercarriage: STD LC: 14'8" (4.47 M) length Track Gauge: STD: 7'10" (2.39 M) gauge Shoe: STD: 31.5" (800 mm) triple grouser 7.5" pitch 49 shoes per side Carrier rollers (2 per side) Track rollers (8 per side) Grease lubricated and strutted track chains Hydraulic track adjustment Single track chain guides SAHR disc parking break Tapered upper track frame DOZER BLADE: Dozer blade width: 9'1" (2800 mm) Dozer blade height: 24" (610 mm) ATTACHMENTS: Standard LC Version: Boom: 18'8" (5.70 M) Arm: 98" (2.94 M) Heavy-duty bucket linkage Auxiliary pipe brackets Attachment cushion valve

Arm and boom regeneration Arm and boom holding valves Centralized grease bank

CASE SiteWatch™ - on board

OTHER BASIC EQUIPMENT:

telematics

```
Cab and Operator's Station:
  Side view camera
  Sun visor
  FOPS top cab guard (Level 2)
  Front grill guard (2" x 2" mesh)
  Front rock guard (OPG 1)
  Front rock guard (OPG 2)
  Vandal guard (not for use with FOPS
    top cab guard)
  Rain deflector
Control pattern change selector
Hose burst check valve (HBCV)
Refueling Pump
Auxiliary hydraulics
Attachments:
  Arm: 7'10" (2.40 M) Heavy-duty
Under carriage:
  Steel shoes/triple-grouser:
    23.6" (600 mm)
  Rubber shoes: 23.6" (600 mm)
  Steel shoes/triple-grouser:
    27.6" (700 mm)
  Steel shoes/triple-grouser:
    35.4" (900 mm)
  Track chain guides - triple
Order from Factory Supplied
  Attachments Section:
    Buckets
    Coupler/Case multi-pin grabber
Order from Service Parts:
  Rubber bumpers for upper
```



CX235C MIN SWING RADIUS EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|-------------------|-----------|--------------|--------------|
| C235C MSR LC | 57,500 LB | | \$281,676.00 |
| C235C MSR W/DOZER | 59,600 LB | | \$305,317.00 |



CX235C MIN SWING RADIUS EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|-------------|---|--------|--------------|--------------|
| | | | | |
| BOOMS | | | | |
| 3001110 | | | | |
| | | | | |
| SD_E5311 BC | ром | | | |
| 481858 | Standard Boom | | | No Charge |
| | 18'8" (5.70 M) Standard Boom | | | |
| | For use with CX235C MSR LC and CX235C MSR w/dozer | | | |
| | commercial models. | | | |
| 781917 | No Boom | | | (\$6,989.00 |
| | Less boom, hoist and arm cylinders and plumbing. | | | |
| | Boom-foot and cylinder pins are provided. | | | |
| | | | | |
| ARMS | | | | |
| | | | | |
| | | | | |
| SD_E5320 AF | RM/DIPPERSTICK | | | |
| 481268 | 9'8" (2.94 M) Arm | | | No Charge |
| | For use wtih 18'8" Standard Boom (option 481858) | | | |
| 461501 | 7'10" (2.40 M) Heavy-duty Arm | | | (\$315.00 |
| | For use with 18'8" Standard Boom (option 481858) | | | |
| | (Recommended for heavy-duty applications - example: hammer) | | | |
| XE5320X | No Arm/Dipperstick | | | (\$3,625.00 |
| | Less arm, bucket cylinder and linkage | | | |
| | | | | |
| TRACK SHOES | | | | |
| | | | | |
| | | | | |
| SD_E5199 TF | RACK SHOES | | | |
| 9560002 | 23.6" (600mm) Steel Shoes | | | (\$1,785.00) |
| | Triple-Grouser Steel Shoes | | | |
| | For use with CX235C MSR LC and CX235C w/dozer | | | |
| | commercial models | | | |
| 9560003 | 27.6" (700mm) Steel Shoes | | | (\$205.00) |
| | Triple-Grouser Steel Shoes | | | |
| | For use with CX235C MSR LC and CX235C w/dozer | | | |
| | commercial models | | | |
| 9560005 | 31.5" (800mm) Steel Shoes | | | No Charge |
| | Triple-Grouser Steel Shoes | | | |
| | For use with CX235C MSR LC and CX235C w/dozer | | | |
| 1 1 | 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 | | | |

commercial models



CX235C MIN SWING RADIUS EXCAVATOR US PRICE LIST

| | 9560007 | 35.4" (900mm) Steel Shoes | | \$1,680.00 |
|--|---------|---|--|-------------|
| | | Triple-Grouser Steel Shoes | | |
| | | For use with CX235C MSR LC and CX235C w/dozer | | |
| | | commercial models | | |
| | 9560055 | 23.6" (600 mm) Rubber Pads | | \$13,982.00 |
| | | Continous belt bolted on standard chain | | |

LANGUAGE

SD_47083 OPERATOR'S MANUAL

| | 781981 | English Language Literature | | No Charge |
|--|--------|-----------------------------|--|-----------|
| | 461540 | French Canadian Language | | No Charge |
| | 781980 | Spanish Language Literature | | No Charge |

ADDITIONAL EQUIPMENT CXC

ADDITIONAL OPTIONS

SD_E5206 TRACK CHAIN GUIDE

| 461541 | Single Track Chain Guide | | No Charge |
|--------|--------------------------|--|------------|
| 461143 | Triple Track Chain Guide | | \$2,440.00 |

SD_E5443 CAB GUARD (FOPS)

| XE5443X | FOPS Top Cab Guard/Level 1 | | No Charge |
|---------|----------------------------|--|------------|
| 481070 | FOPS Top Cab Guard/Level 2 | | \$1,290.00 |

SD_E5444 CAB GUARD (FRONT)

| | XE5444X | No Front Guard | No Charge |
|---|---------|---|------------|
| | 461142 | Front grill guard - 2 x 2 mesh | \$1,500.00 |
| | 781986 | Front rock guard (OPG 1) | \$2,045.00 |
| L | | Vertical bars (two piece/upper and lower) | |
| | 461024 | Front rock guard (OPG 2) | \$2,295.00 |
| L | | Vertical bars (one piece/full length) | |
| | 461552 | Vandal Guard | \$505.00 |
| | | Not for use wtih FOPS Top Cab Guard (option 481070) | |

SD_E5449 RAIN DEFLECTOR

| L | XE5449X | No Rain Deflector | | No Charge |
|---|---------|--|--|-----------|
| | 461555 | Rain Deflector | | \$390.00 |
| | | Not for use with Front grill guard - 2 x 2 mesh option 461142, | | |
| | | Front rock guard (OPG 1) option 781986, or | | |
| | | Front rock guard (OPG 2) option 461024. | | |

SD_E5451 SUN VISOR

| | XE5451X | No Sun Visor | | No Charge |
|--|---------|--------------|--|-----------|
| | 461554 | Sun Visor | | \$125.00 |



CX235C MIN SWING RADIUS EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

SD E6410 AUXILIARY HYDRAULICS

| SD_E6410 | AUXILIARY HYDRAULICS | |
|----------|---|-------------|
| XE641 | 0X No Optional Hydraulics | No Charge |
| 46186 | 5 HAM ELCT PRO CNTRL | \$7,799.00 |
| | Hammer Circuit Electrical Proportional Control | |
| | Joystick activated | |
| | Provides single direction flow; use for hammer application | |
| | Includes manually adjustable relief valve to set required pressures | |
| | | |
| | Notes: | |
| | 1) Not for use with other Auxiliary Hydraulic options, with the | |
| | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com) | |
| 461869 | HAM/HF W/PRSR ELET PRO CNTRL | \$11,881.00 |
| | Hammer/High Flow Circuit, with Pressure Control, Electrical | |
| | Proportional Control | |
| | Includes in-cab Electronic Pressure Control feature | |
| | | |
| | Joystick Activated | |
| | Pressure Control feature allows hydraulic pressure setting | |
| | from the cab monitor and maintaining pressure settings in | |
| | memory when multiple tools are used. | |
| | | |
| | Provides single or dual pump, two-way flow, for use with | |
| | multiple applications: thumb/grapples/crushers. | |
| | Secondary Low-flow Auxiliary Hydraulics can be added | |
| | Includes in-cab electronically controlled pressure setting feature | |
| | Is switchable to single acting flow for hammer application. | |
| | | |
| | Notes: | |
| | 1) Not for use with other Auxiliary Hydraulics options, with the | |
| | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com) | |



CX235C MIN SWING RADIUS EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) 461871 AUX, TMB ELEC PRO CNTRL \$6,089.00 **Auxiliary Circuit, Thumb, Electrical Proportional Control** Joystick activated Provides single pump, two-way flow; use for thumb application Hydraulic plumbing provided to the end of the boom only, no piping to the arm This system is not switchable to single acting flow Notes: 1) Not for use other Auxiliary Hydraulics options with the exception of Low Flow. 2) Heavy duty bucket linkage is standard equipment on C series excavators. 3) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com). SD_E6417 SECONDARY AUXILIARY HYDRAULICS XE6417X No Extra Auxiliary Hydraulics No Charge 461863 LF ELCT PRO CNTRL \$6,440.00 **Low Flow Electrical Proportional Control Joystick Activated** Provides low-flow for rotation or tilt of hydraulic tools. Notes: 1) May be used standalone or with any Case Excavator Auxiliary Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com). SD_E6423 CONTROL PATTERN SELECTION XE6423X No Control Pattern Valve No Charge 461558 Control Pattern Selector Valve \$950.00 SD_E9730 SAFETY VALVE XE9730X No Hose Burst Check Valve No Charge Hose Burst Check Valve (HBCV) 461559 \$9,130.00 boom and arm SD_E9740 SIDE VIEW CAMERA XE9740X No Side View Camera No Charge 461560 Side View Camera \$725.00

SD_E9874 REFUEL PUMP

XE9874X No Refuel Pump

481257 Refuel Pump

No Charge

\$1,050.00



(This page intentionally left blank)



CX235C MIN SWING RADIUS EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Factory Supplied Attachments

| Order Code | Description | Weight | Factory Data | List Price |
|-------------------|---|----------|--------------|------------|
| ase Coupler Bud | ekets | | | |
| 84404187 | 24" Heavy Duty Coupler Bucket with 4 teeth (.63 cu. yd.) | 1,350 LB | | \$6,252.00 |
| 84404188 | 30" Heavy Duty Coupler Bucket with 4 teeth (.82 cu. yd.) | 1,525 LB | | \$6,875.00 |
| 84404189 | 36" Heavy Duty Coupler Bucket with 5 teeth (1.02 cu. yd.) | 1,660 LB | | \$7,565.00 |
| 84404190 | 42" Heavy Duty Coupler Bucket with 5 teeth (1.20 cu. yd.) | 1,835 LB | | \$8,323.00 |
| 84404191 | 48" Heavy Duty Coupler Bucket with 6 teeth (1.48 cu. yd.) | 1,990 LB | | \$8,795.00 |
| ase Multi Fit Cou | upler | | | |
| 87403730 | Case Multi Fit Hydraulic Coupler Optimized for use with Case coupler buckets. Also can be used with a wide range of buckets from other manufactures including pin on types. Includes hydraulic installation kit and instructions. | 859 LB | | \$9,909.00 |
| ase Pin On Buck | ets. | | | |
| 84404166 | 24" Heavy Duty Bucket with 4 teeth (.55 cu. yd.) | 1,420 LB | | \$4,612.00 |
| 84404167 | 30" Heavy Duty Bucket with 4 teeth (.73 cu. yd.) | 1,630 LB | | \$5,164.00 |
| 84404168 | 36" Heavy Duty Bucket with 5 teeth (.90 cu. yd.) | 1,835 LB | | \$5,635.00 |
| 84404169 | 42" Heavy Duty Bucket with 5 teeth (1.08 cu. yd.) | 1,975 LB | | \$6,075.00 |
| 84404170 | 24" Heavy Duty High Capacity Bucket with 4 teeth (.75 cu. yd.) | 1,500 LB | | \$4,987.00 |
| 84404175 | 30" Heavy Duty High Capacity Bucket with 4 teeth (.94 cu. yd.) | 1,700 LB | | \$5,510.00 |
| 84404178 | 36" Heavy Duty High Capacity Bucket with 5 teeth (1.15 cu. yd.) | 1,925 LB | | \$6,090.00 |
| 84404179 | 42" Heavy Duty High Capacity Bucket with 5 teeth (1.37 cu. yd.) | 2,110 LB | | \$6,395.00 |
| 84404180 | 48" Heavy Duty High Capacity Bucket with 6 teeth (1.59 cu. yd.) | 2,340 LB | | \$6,988.00 |
| 84404181 | 24" Severe Duty Bucket with 4 teeth (.55 cu. yd.) | 1,635 LB | | \$6,235.00 |
| 84404182 | 30" Severe Duty Bucket with 4 teeth (.73 cu. yd.) | 1,875 LB | | \$6,985.00 |
| 84404183 | 36" Severe Duty Bucket with 5 teeth (.90 cu. yd.) | 2,110 LB | | \$7,823.00 |
| 84404184 | 42" Severe Duty Bucket with 5 teeth (1.08 cu. yd.) | 2,270 LB | | \$8,094.00 |
| 84404185 | 60" Ditching Bucket (1.02 cu. yd.) | 1,000 LB | | \$4,177.00 |
| 84404186 | 72" Ditching Bucket (1.22 cu. yd.) | 1,000 LB | | \$4,524.0 |



(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

```
ENGINE:
                                                    OPERATOR'S CAB (Continued):
  Isuzu AL-4HK1k
                                                      Cab interior features:
 Tier 4 Interim Certified (CEGR)
                                                        Cup holder
  317 cubic in. displacement/5.2 Liter
                                                        Storage compartments
 Turbocharged/air cooled intercooler
                                                        Warm/cool storage compartments
 Horsepower:
                                                        Easy access fuse box
   Net: 177 (132 kW) @ 2000 RPM
                                                        Interior dome light
                                                        One touch lock front window
 High pressure common rail system
 Auto engine warm-up
                                                        One key start and lock-up
                                                        Interior Light (1 x 10 watt)
 FEA (Fuel Economy Assist System)
 Engine Idle/Fuel Economy System:
                                                      Single pedal travel
   Auto Idle
                                                      Straight travel
   One-touch Idle
                                                      Travel alarm and horn
   Idle Shut-down
                                                      Windshield wiper and washer
 Fuel Capacity:
                                                      Programmable anti-theft system
                                                      Worklights (2)
    108 gallons (410 L)
 AEC (auto economy control)
                                                    ELECTRICAL:
 BEC (boom economy control)
                                                      24-volt system
OPERATOR'S CAB:
                                                      Two batteries (12 volt/92 Ah)
 ROPS protection
                                                      50 Amp Alternator
 Pressurized cab area
                                                      Worklights (4 x 70 watt)
 AC/heat/defrost w/climate control
                                                        Boom mounted (1)
 Electronics:
                                                        Upper mounted (1)
    Color monitor (7 in/180 mm)
                                                        Cab mounted (2)
      with Rearview camera view
                                                      Telematics Ready
   Rearview camera
                                                        Wiring harness and 16-pin connector
    AM/FM radio with antenna and
                                                    HYDRAULICS:
      2-speakers
    Aux-in port for personal electronics
                                                      Open-center system design
    12-volt electric socket
                                                      Selectable work modes (3)
    24-volt cigarette lighter
                                                      Auto power boost
 Air-suspension seat (cloth)
                                                      Auto swing priority
                                                      SWC (swing relief control)
   KAB® adjustable deluxe seat
    Seat belt - 3"
                                                      SSC (spool stroke control)
   Adjustable arm rests
                                                      5000 hour hydraulic oil change interval
    4-position tilting consoles
                                                      1000 hour hyd. filter change interval
    Sliding cockpit (7 in/180 mm)
 Low-effort joystick controls
  Clear (poly carbonate) roof window
  External rearview mirrors
  Rubber floormat
```



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE: OPTIONAL EQUIPMENT X-pattern carbody Cab and Operator's Station: Undercarriage: Side view camera STD LC: 15'3" (4.65 M) length Sun visor Track Gauge: FOPS cab top guard (Level 2) STD: 8'6" (2.6 M) gauge Front grill guard (2" x 2" mesh) Shoe: Front rock guard (OPG 1) STD: 31.5" (800 mm) triple grouser Front rock guard (OPG 2) 7.5" pitch Vandal quard 51 shoes per side Rain deflector Two-speed independent travel Control pattern change selector Carrier rollers (2 per side) Free swing Track rollers (9 per side) Hose burst check valve Grease lubricated and strutted track Refueling Pump chains Auxiliary hydraulics Hydraulic track adjustment Attachments: Single Track Chain Guide Arm: 8'4" (2.53 M) Heavy-duty SAHR disc parking break Arm: 11'6" (3.50 M) Tapered upper track frame Load holding control Undercarriage: ATTACHMENTS: Steel shoes/triple-grouser: Standard LC Version: 23.6" (600mm) Steel shoes/triple-grouser: Boom: 192" (5.85 M) Arm: 910" (3.00 M) 27.6" (700 mm) Heavy-duty bucket linkage Track chain guides - triple Auxiliary pipe brackets High Ambient Temperature Cooling Attachment cushion valve Package

OTHER BASIC EQUIPMENT:

CASE SiteWatch™ - on board telematics

Centralized lube bank

Arm and boom regeneration

Rubber bumpers for upper

-Third Party setion:

Buckets

Order from Wholegood Attachments

(order thorough Service Parts)

Coupler/Case multi-pin grabber



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|-----------|--------------|--------------|
| CX250C STD | 64,700 LB | | \$331,469.00 |



(Ex Works Port of Entry) Factory Supplied Options

| | Description | | Factory Data | List Price |
|---|---|---|--------------|--|
| | | | | |
| OOMS | | | | |
| | | | | |
| | | | | |
| SD_E5311 BC | | 1 | 1 | |
| 481858 | Standard Boom | | | No Charge |
| | 19'2" (5.85 M) Standard Boom | | | |
| | For use with CX250B (Standard) Commercial Model | | | |
| 781917 | No Boom | | | (\$7,810.00 |
| | Less boom, hoist and arm cylinders and plumbing. | | | |
| | Boom-foot and cylinder pins are provided. | | | |
| RMS | | | | |
| SD_E5320 AF | RM/DIPPERSTICK | | | • |
| | 8'4" (2.53 M) Heavy-duty Arm | | | \$160.0 |
| SD_E5320 AF | 8'4" (2.53 M) Heavy-duty Arm For use with 19"2" Standard Boom (option 481858) | | | \$160.00 |
| SD_E5320 AF 461548 | 8'4" (2.53 M) Heavy-duty Arm For use with 19"2" Standard Boom (option 481858) (Recommended for heavy-duty applications - example: hammer) | | | |
| SD_E5320 AF | 8'4" (2.53 M) Heavy-duty Arm For use with 19"2" Standard Boom (option 481858) (Recommended for heavy-duty applications - example: hammer) 9'11" (3.01M) Standard Arm | | | |
| SD_E5320 AR 461548 781178 | 8'4" (2.53 M) Heavy-duty Arm For use with 19"2" Standard Boom (option 481858) (Recommended for heavy-duty applications - example: hammer) 9'11" (3.01M) Standard Arm For use with 19'2" Standard Boom (option 481858) | | | No Charg |
| SD_E5320 AF 461548 | 8'4" (2.53 M) Heavy-duty Arm For use with 19"2" Standard Boom (option 481858) (Recommended for heavy-duty applications - example: hammer) 9'11" (3.01M) Standard Arm For use with 19'2" Standard Boom (option 481858) 11'6" (3.50 M) Standard Arm | | | No Charg |
| SD_E5320 AR 461548 781178 781149 | 8'4" (2.53 M) Heavy-duty Arm For use with 19"2" Standard Boom (option 481858) (Recommended for heavy-duty applications - example: hammer) 9'11" (3.01M) Standard Arm For use with 19'2" Standard Boom (option 481858) 11'6" (3.50 M) Standard Arm For use with 19'2" Standard Boom (option 481858) | | | No Charg |
| SD_E5320 AR 461548 781178 | 8'4" (2.53 M) Heavy-duty Arm For use with 19"2" Standard Boom (option 481858) (Recommended for heavy-duty applications - example: hammer) 9'11" (3.01M) Standard Arm For use with 19'2" Standard Boom (option 481858) 11'6" (3.50 M) Standard Arm For use with 19'2" Standard Boom (option 481858) No Arm/Dipperstick | | | No Charg |
| SD_E5320 AR 461548 781178 781149 | 8'4" (2.53 M) Heavy-duty Arm For use with 19"2" Standard Boom (option 481858) (Recommended for heavy-duty applications - example: hammer) 9'11" (3.01M) Standard Arm For use with 19'2" Standard Boom (option 481858) 11'6" (3.50 M) Standard Arm For use with 19'2" Standard Boom (option 481858) | | | \$160.00 No Charge \$1,680.00 (\$4,180.00 |

SD_E5199 TRACK SHOES

| | 9560002 | 23.6" (600mm) Steel Shoes | | (\$1,330.00) |
|---|---------|----------------------------|--|--------------|
| L | | Triple-Grouser Steel Shoes | | |
| Ī | 9560003 | 27.6" (700mm) Steel Shoes | | (\$655.00) |
| L | | Triple-Grouser Steel Shoes | | |
| Ī | 9560005 | 31.5" (800mm) Steel Shoes | | No Charge |
| | | Triple-Grouser Steel Shoes | | |



(Ex Works Port of Entry)

| LANGUAGE | | | |
|----------------|--|----------|----------|
| | | | |
| | | | |
| T T = | PERATOR'S MANUAL | | |
| 781981 | English Language Literature | | Charge |
| 461540 | French Canadian Language | | Charge |
| 781980 | Spanish Language Literature | l No | Charge |
| | | | |
| ADDITIONAL EQU | JIPMENT CXC | | |
| ADDITIONAL ODT | IONO. | | |
| ADDITIONAL OPT | IUNS | | |
| SD EEOOS TE | NACK CHAIN CHIDE | | |
| 461541 | RACK CHAIN GUIDE Single Track Chain Guide | No. | Charge |
| 461143 | Triple Track Chain Guide | | ,440.00 |
| 1 1 401143 | The Hack Chain Guide | ΨΣ | ,440.00 |
| SD F5407 CC | OOLING PACKAGE | | |
| | No Optional Cooling Package | No | Charge |
| 481027 | High Ambient Cooling Package | | ,095.00 |
| | High ambient temperature cooling package | | , |
| | Note: Recommended for machines operating in high heat | | |
| | conditions not to exceed 122°F (50°C) | | |
| | Totalione not to oxoccu 122 1 (co o) | <u> </u> | |
| SD E5443 CA | AB GUARD (FOPS) | | |
| | FOPS Top Cab Guard/Level 1 | No | Charge |
| 481070 | FOPS Top Cab Guard/Level 2 | | ,290.00 |
| | · · · | • | • |
| SD_E5444 CA | AB GUARD (FRONT) | | |
| XE5444X | No Front Guard | No | Charge |
| 461142 | Front grill guard - 2 x 2 mesh | \$1 | ,500.00 |
| 781986 | Front rock guard (OPG 1) | \$2 | ,045.00 |
| | vertical bars (two piece/upper and lower) | | |
| 461024 | Front rock guard (OPG 2) | \$2 | ,295.00 |
| | vertical bars (one piece/full length) | | |
| 461552 | Vandal Guard | | \$505.00 |
| | | | |
| SD_E5449 RA | AIN DEFLECTOR | | |
| XE5449X | No Rain Deflector | | Charge |
| 461555 | Rain Deflector | | \$390.00 |
| | Not for use with Front grill guard - 2 x 2 mesh option 461142, | | |
| | Front rock guard (OPG 1) option 781986, or | | |
| | Front rock guard (OPG 2) option 461024. | | |
| | | | |
| SD_E5451 SL | | | |
| | No Sun Visor | | Charge |
| 461554 | Sun Visor | | \$125.00 |



(Ex Works Port of Entry)

SD E6410 AUXILIARY HYDRAULICS

| No Charge |
|-------------|
| |
| \$7,894.00 |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| \$11,964.00 |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |



(Ex Works Port of Entry)

| | | (Ex Works Port of Entry) | |
|-----|----------------------------------|---|-----------------------|
| | 461871 | AUX, TMB ELEC PRO CNTRL | \$6,197.00 |
| | | Auxiliary Circuit, Thumb, Electrical Proportional Control | |
| | | Joystick activated | |
| | | Provides single pump, two-way flow; use for thumb application | |
| | | Hydraulic plumbing provided to the end of the boom only, | |
| | | no piping to the arm | |
| | | This system is not switchable to single acting flow | |
| | | | |
| | | Notes: | |
| | | 1) Not for use other Auxiliary Hydraulics options with the | |
| | | exception of Low Flow. | |
| | | 2) Heavy duty bucket linkage is standard equipment on | |
| | | C series excavators. | |
| | | For dealer installed auxiliary hydraulic kits contact: | |
| | | HKX (1-800-493-5487 or www.HKX.com). | |
| | | | |
| | T = | CONDARY AUXILIARY HYDRAULICS | |
| | | No Extra Auxiliary Hydraulics | No Charge |
| | 461863 | LF ELCT PRO CNTRL | \$6,500.00 |
| | | Low Flow Electrical Proportional Control | |
| | | Joystick Activated | |
| | | Provides low-flow for rotation or tilt of hydraulic tools. | |
| | | Notes: | |
| | | 1) May be used standalone or with any Case Excavator Auxiliary | |
| | | Hydraulics option. | |
| | | 2) For dealer installed auxiliary hydraulic kits contact: | |
| | | HKX (1-800-493-5487 or www.HKX.com). | |
| | | , | |
| | SD_E6423 CC | NTROL PATTERN SELECTION | |
| | XE6423X | No Control Pattern Valve | No Charge |
| | 461558 | Control Pattern Selector Valve | \$950.00 |
| | | | |
| | SD_E9730 SA | | |
| | | No Hose Burst Check Valve | No Charge |
| | 461559 | Hose Burst Check Valve (HBCV) | \$9,130.00 |
| 1 1 | | | |
| | | boom and arm | |
| | 00 50510 015 | | , |
| | | DE VIEW CAMERA | No Observe |
| | XE9740X | DE VIEW CAMERA No Side View Camera | No Charge |
| | | DE VIEW CAMERA | No Charge \$725.00 |
| | XE9740X 461560 | DE VIEW CAMERA No Side View Camera Side View Camera | |
| | XE9740X 461560 SD_E9741 FR | DE VIEW CAMERA No Side View Camera Side View Camera EE SWING | \$725.00 |
| | XE9740X 461560 | DE VIEW CAMERA No Side View Camera Side View Camera EE SWING | |



(Ex Works Port of Entry)

SD_E9874 REFUEL PUMP

| | XE9874X | No Refuel Pump | | No Charge |
|--|---------|----------------|--|------------|
| | 481257 | Refuel Pump | | \$1,050.00 |



(Ex Works Port of Entry) Factory Supplied Attachments

| Order Code | Description | Weight | Factory Data | List Price |
|-----------------|--|----------|--------------|---|
| ase Pin On Buc | kats | | | |
| 84404217 | 36" Heavy Duty Bucket | 1,950 LB | | \$6,530.00 |
| | with 5 teeth (1.11 cu. yd.) | 1,000 LB | | ψ0,000.00 |
| 84404219 | 42" Heavy Duty Bucket | 2,186 LB | | \$7,184.00 |
| | with 5 teeth (1.32 cu. yd.) | , | | . , |
| 84404220 | 48" Heavy Duty Bucket | 2,407 LB | | \$7,512.00 |
| | with 6 teeth (1.54 cu. yd.) | | | |
| 84404224 | 36" Extra Heavy Duty Bucket | 2,150 LB | | \$7,042.00 |
| | with 5 teeth (1.32 cu. yd.) | | | |
| 84404228 | 42" Extra Heavy Duty Bucket | 2,350 LB | | \$7,746.00 |
| | with 5 teeth (1.58 cu. yd.) | | | |
| 84404230 | 48" Extra Heavy Duty Bucket | 2,600 LB | | \$8,196.00 |
| 84404232 | with 6 teeth (1.84 cu. yd.) 54" Extra Heavy Duty Bucket | 2 200 LB | | Ф0 <u>500</u> 00 |
| 04404232 | with 6 teeth (2.09 cu. yd.) | 2,800 LB | | \$8,582.00 |
| 84404234 | 36" Severe Duty Bucket | 2,200 LB | | \$8,413.00 |
| 04404204 | with 5 teeth (1.11 cu. yd.) | 2,200 LB | | ψο, 4 το.ος |
| 84404237 | 42" Severe Duty Bucket | 2,450 LB | | \$9,256.00 |
| | with 5 teeth (1.32 cu. yd.) | , | | , |
| 84404240 | 48" Severe Duty Bucket | 2,650 LB | | \$10,181.00 |
| | with 6 teeth (1.54 cu. yd.) | | | |
| 84404242 | 60" Ditching Bucket (1.38 cu. yd.) | 1,475 LB | | \$5,837.00 |
| 84404244 | 72" Ditching Bucket (1.77 cu. yd.) | 1,650 LB | | \$6,228.00 |
| | | | | |
| se Coupler Bu | | 1 | | |
| 84404245 | 36" Heavy Duty Coupler Bucket with 5 teeth (1.16 cu. yd.) | 2,040 LB | | \$8,208.00 |
| 84404246 | 42" Heavy Duty Coupler Bucket | 2,210 LB | | \$8,756.00 |
| 04404240 | with 5 teeth (1.38 cu. yd.) | 2,210 LB | | \$6,736.00 |
| 84404249 | 48" Heavy Duty Coupler Bucket | 2,350 LB | | \$9,594.00 |
| | with 6 teeth (1.60 cu. yd.) | 2,000 25 | | φο,σο 1.σο |
| 84404251 | 54" Heavy Duty Coupler Bucket | 2,610 LB | | \$10,383.00 |
| | with 6 teeth (1.84 cu. yd.) | , | | |
| | | | | |
| se Multi Fit Co | - 1 | | | |
| 429662A1 | Case Multi Fit Hydraulic Coupler | 1,401 LB | | \$12,804.00 |
| | Optimized for use with Case coupler buckets. | | | |
| | Also can be used with a wide range of buckets from other manufacturers including pin-on types. | | | |
| | Includes hydraulic installation kit and instructions. | | | |
| 1 1 | i indiado fryaraulo installation Ni alla Ilistiactions. | 1 | | |



(This page intentionally left blank)



CX250C LONG REACH CRAWLER EXCAVATOR US PRICE LIST

OPERATOR'S CAB (Continued):

(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AL-4HK1k Cab interior features: Tier 4 Interim Certified (CEGR) Cup holder 317 cubic in. displacement/5.2 Liter Storage compartments Turbocharged/air cooled intercooler Warm/cool storage compartments Horsepower: Easy access fuse box Net: 177 (132 kW) @ 2000 RPM Interior dome light One touch lock front window High pressure common rail system Auto engine warm-up One key start and lock-up Interior Light (1 x 10 watt) FEA (Fuel Economy Assist System) Engine Idle System/Fuel Economy Two-speed independent travel System: Single pedal travel Auto Idle Straight travel One-touch Idle Travel alarm and horn Idle Shut-down Windshield wiper and washer Fuel Capacity: Programmable anti-theft system 108 gallons (410 L) ELECTRICAL: AEC (auto economy control) BEC (boom economy control) 24-volt system Two batteries (12 volt/92 Ah) OPERATOR'S CAB: 50 Amp Alternator Worklights (4 x 70 watt) ROPS protection Pressurized cab area Boom mounted (1) AC/heat/defrost with auto climate Upper mounted (1) control Cab mounted (2) Electronics: Telematics Ready Color monitor (7 in/180 mm) Wiring harness and 16-pin connector with Rearview camera view Rearview camera HYDRAULICS: AM/FM radio with antenna and Open-center system design 2-speakers Selectable work modes (3) Auto power boost Aux-in port for personal electronics 12-volt electric socket Auto swing priority SWC (swing relief control) 24-volt cigarette lighter Air-suspension seat (cloth) SSC (spool stroke control) KAB® adjustable deluxe seat 5000 hour hydraulic oil change interval Seat belt - 3" 1000 hour hyd. filter change interval Adjustable arm rests 4-position tilting consoles Sliding cockpit (7 in/180 mm) Low-effort joystick controls Clear (poly carbonate) roof window External rearview mirrors Rubber floormat



CX250C LONG REACH CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

X-pattern carbody
Undercarriage:

STD LC: 15'3" (4.65 M) length

Track Gauge:

STD LC: 8'6" (2.6 M) gauge

Shoe:

STD: 31.5" (800 mm) triple grouser

7.5" pitch

51 shoes per side

Carrier rollers (2 per side)

Track rollers (9 per side)

Grease lubricated and strutted track

chains

Hydraulic track adjustment

Double chain guides

SAHR disc parking break

Tapered upper track frame

ATTACHMENTS:

Standard Version:

Boom: 3310" (10.30 M)

Arm: 263" (8.0 M)

Heavy-duty bucket linkage

Auxiliary pipe brackets

Attachment cushion valve

Arm and boom regeneration

Centralized lube bank

OTHER BASIC EQUIPMENT:

CASE SiteWatch $^{\text{\tiny{IM}}}$ - on board

telematics

OPTIONAL EQUIPMENT:

Cab and Operator's Station:

Side view camera

Sun visor

FOPS cab top guard (Level 2)

Front grill guard (2" x 2" mesh)

Front rock guard (OPG 1)

Front rock guard (OPG 2)

Vandal guard

Rain deflector

Control pattern change selector

Free swing

Hose burst check valve

Refueling Pump

Auxiliary Hydraulics

Order from Wholegood Attachments

-Third Party setion:

Case multi fit Coupler

Buckets

Load holding control

Undercarriage:

Track chain guides - triple

High Ambient Temperature Cooling

Package

Order from Service Parts:

1-Rubber bumpers for upper



CX250C LONG REACH CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|-----------|--------------|--------------|
| CX250C LR | 60,200 LB | | \$370,331.00 |



CX250C LONG REACH CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price | | |
|---------------|--|--------------|--|--------------|--|--|
| | | | | | | |
| | | | | | | |
| BOOMS | | | | | | |
| | | | | | | |
| 0D E5044 D | 004 | | | | | |
| SD_E5311 B | | 1 | | N 0 | | |
| 461029 | Standard Long Reach Boom | | | No Charge | | |
| . | 33'10" (10.30 M) Long Reach Boom | | | | | |
| | For use with CX250C LR (Long Reach) Commercial Model | | | | | |
| 781917 | No Boom | | | (\$7,810.00) | | |
| ı | Less boom, hoist and arm cylinders and plumbing. | | | | | |
| | Boom-foot and cylinder pins are provided. | | | | | |
| | | | | | | |
| ARMS | | | | | | |
| | | | | | | |
| 05 ===== . | | | | | | |
| | RM/DIPPERSTICK | т — | | | | |
| 481238 | 26'3" (8.00 M) Arm | | | No Charge | | |
| = | For use with 33'10" Standard Long Reach Boom (option 461029) | | | /# | | |
| XE5320 | No Arm/Dipperstick | | | (\$6,260.00) | | |
| | Less arm, bucket cylinder and linkage | | | | | |
| | | | | | | |
| TRACK SHOES | | | | | | |
| | | | | | | |
| | | | | | | |
| SD_E5199 T | | | | | | |
| 9560005 | 31.5" (800mm) Steel Shoes | | | No Charge | | |
| | Triple-Grouser Steel Shoes | | | | | |
| | | | | | | |
| LANGUAGE | | | | | | |
| | | | | | | |
| | | | | | | |
| SD_47083 O | PERATOR'S MANUAL | | | | | |
| 781981 | English Language Literature | | | No Charge | | |
| 461540 | French Canadian Language | | | No Charge | | |
| 781980 | Spanish Language Literature | | | No Charge | | |
| | | | | | | |
| ADDITIONAL EQ | UIPMENT CXC | | | | | |
| | | | | | | |
| ADDITIONAL OP | TIONS | | | | | |
| op = = | DAOK OLIANI OLUBE | | | | | |
| | RACK CHAIN GUIDE | | | | | |
| 461541 | Single Track Chain Guide | | | No Charge | | |



CX250C LONG REACH CRAWLER EXCAVATOR US PRICE LIST

| | (Ex Works Port of Entry) | |
|------------|---|---------------------------------------|
| 461143 | Triple Track Chain Guide | \$2,44 |
| | | |
| | COOLING PACKAGE | |
| | X No Optional Cooling Package | No Ch |
| 481027 | High Ambient Cooling Package | \$1,09 |
| | High ambient temperature cooling package | |
| | Note: Recommended for machines operating in high heat | |
| | conditions not to exceed 122°F (50°C) | |
| SD F5443 | CAB GUARD (FOPS) | |
| | X FOPS Top Cab Guard/Level 1 | No Ch |
| 481070 | · | \$1,29 |
| - | <u> </u> | <u> </u> |
| SD_E5444 (| CAB GUARD (FRONT) | |
| XE5444 | X No Front Guard | No Ch |
| 461142 | Front grill guard - 2 x 2 mesh | \$1,50 |
| 781986 | Front rock guard (OPG 1) | \$2,04 |
| | vertical bars (two piece/upper and lower) | |
| 461024 | Front rock guard (OPG 2) | \$2,29 |
| | vertical bars (one piece/full length) | |
| 461552 | Vandal Guard | \$50 |
| 05 == | | |
| | RAIN DEFLECTOR | No Ch |
| | X No Rain Deflector | No Ch |
| 461555 | Rain Deflector | \$39 |
| | Not for use with Front grill guard - 2 x 2 mesh option 461142, | |
| | Front rock guard (OPG 1) option 781986, or | |
| | Front rock guard (OPG 2) option 461024. | |
| SD_E5451 | SUN VISOR | |
| | X No Sun Visor | No Ch |
| 461554 | | \$12 |
| | 1 | · · · · · · · · · · · · · · · · · · · |
| SD_E6417 | SECONDARY AUXILIARY HYDRAULICS | |
| XE6417 | X No Extra Auxiliary Hydraulics | No Ch |
| 461863 | LF ELCT PRO CNTRL | \$8,38 |
| | Low Flow Electrical Proportional Control | |
| | Joystick Activated | |
| | Provides low-flow for rotation or tilt of hydraulic tools. | |
| | | |
| | Notes: | |
| | 1) May be used standalone or with any Case Excavator Auxiliary | |
| | Hydraulics option. | |
| | 2) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com). | |
| | , and the same of | ' |
| SD_E6423 | CONTROL PATTERN SELECTION | |
| XF6423 | X No Control Pattern Valve | No Ch |

\$1,050.00



CX250C LONG REACH CRAWLER EXCAVATOR US PRICE LIST

| | | (Ex Works Port of Entry) | | |
|--------|--------|--------------------------------|---|------------|
| 46 | 61558 | Control Pattern Selector Valve | | \$950.00 |
| | | | | |
| SD_E97 | '30 SA | FETY VALVE | | |
| L XI | E9730X | No Hose Burst Check Valve | | No Charge |
| 46 | 61559 | Hose Burst Check Valve (HBCV) | | \$9,130.00 |
| | | boom and arm | | |
| SD_E97 | | DE VIEW CAMERA | | No Charra |
| | E9740X | No Side View Camera | | No Charge |
| 46 | 61560 | Side View Camera | | \$725.00 |
| SD_E97 | '41 FR | EE SWING | | |
| XI | E9741X | No Free Swing | | No Charge |
| 46 | 61568 | Free Swing | | \$285.00 |
| | | switch activated | | |
| SD_E98 | 374 RE | FUEL PUMP | | |
| XI | E9874X | No Refuel Pump | | No Charge |
| | | | · | A |

481257 Refuel Pump



CX250C LONG REACH CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

Factory Supplied Attachments

| | Order Code | Description | Weight | Factory Data | List Price | | |
|----|---------------------|------------------------------------|----------|--------------|------------|--|--|
| Ca | Case Pin On Buckets | | | | | | |
| | 84404113 | 48" Ditching Bucket (.79 cu. yd.) | 860 LB | | \$3,452.00 | | |
| | 84404115 | 60" Ditching Bucket (1.02 cu. yd.) | 1,000 LB | | \$3,916.00 | | |



(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

```
ENGINE:
                                                    OPERATOR'S CAB (Continued):
  Isuzu AL-6HK1X
                                                      Cab interior features:
 Tier 4 Interim Certified (CEGR)
                                                        Cup holder
  475 cubic in. displacement /7.8 Liter
                                                        Storage compartments
 Turbocharged/air cooled intercooler
                                                        Warm/cool storage compartments
 Horsepower:
                                                        Easy access fuse box
   Net: 207 (154 kW) @ 1800 RPM
                                                        Interior dome light
                                                        One touch lock front window
 High pressure common rail system
 Auto engine warm-up
                                                        One key start and lock-up
 FEA (Fuel Economy Assist System)
                                                      Single pedal travel
 Engine Idle/Fuel Economy System:
                                                      Straight travel
   Auto Idle
                                                      Travel alarm and horn
   One-touch Idle
                                                      Windshield wiper and washer
   Idle Shut-down
                                                      Programmable anti-theft system
 Fuel Capacity:
                                                    ELECTRICAL:
   119 gallons (450 L)
 AEC (auto economy control)
                                                      24-volt system
 BEC (boom economy control)
                                                      Two batteries (12 volt/128 Ah)
                                                      50 Amp Alternator
OPERATOR'S CAB:
                                                      Worklights (4 x 70 watt)
 ROPS protection
                                                        Boom mounted (1)
 Pressurized cab area
                                                        Upper mounted (1)
 AC/heat/defrost w/auto climate
                                                        Cab mounted (2)
control
                                                      Telematics Ready
 Electronics:
                                                        Wiring harness and 16-pin connector
   Color monitor (7 in/180 mm)
     with Rearview camera view
                                                    HYDRAULICS:
   Rearview camera
                                                      Open-center system design
    AM/FM radio w/antenna and
                                                      Selectable work modes (3)
       2-speakers
                                                      Auto power boost
   Aux-in port for personal electronics
                                                      Auto swing priority
    12-volt electric socket
                                                      SWC (swing relief control)
    24-volt cigarette lighter
                                                      SSC (spool stroke control)
                                                      5000 hour hydraulic oil change interval
   Air-suspension seat (cloth)
     KAB® adjustable deluxe seat
                                                      1000 hour hyd. filter change interval
      Seat belt - 3"
     Adjustable arm rests
      4-position tilting consoles
      Sliding cockpit (7 in/180 mm)
    Low-effort joystick controls
    Clear (poly carbonate) roof window
    External rearview mirrors
    Rubber floormat
```



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE: OPTIONAL EQUIPMENT: X-pattern carbody Cab and Operator's Station: Undercarriage: Side view camera STD LC: 15'11 (4.85 M) length Sun visor Track Gauge: FOPS cab top guard (Level 2) STD: 8'6" (2.6 M) gauge Front grill guard (2" x 2" mesh) Shoe: Front rock guard (OPG 1) STD: 31.5" (800 mm) triple grouser Front rock guard (OPG 2) 8.0" pitch Vandal quard 50 shoes per side Rain deflector Two-speed independent travel Control pattern change selector Carrier rollers (2 per side) Free swing Track rollers (9 per side) Hose burst safety valve (HBSV) Grease lubricated and strutted track Refueling Pump chains Auxiliary hydraulics Hydraulic track adjustment Attachments: Arm: 8'8" (2.63 M) Single track chain guide SAHR disc parking break Arm: 12'0" (3.66 M) Tapered upper track frame Load holding control Undercarriage: ATTACHMENTS: Steel shoes/triple-grouser: Standard Version: 23.6" (600 mm) Boom: 20'2" (6.15 M) Steel shoes/triple-grouser: Arm: 10'5" (3.18 M) 27.6" (700 mm) Heavy-duty bucket linkage Track chain guides - triple Auxiliary pipe brackets High Ambient Temperature Cooling Attachment cushion valve Package Arm and boom regeneration Centralized lube bank Rubber bumpers for upper (order through Service Parts) OTHER BASIC EQUIPMENT:

CASE SiteWatch™ - on board

telematics

Order from Wholegood Attachments

Coupler/Case multi-pin grabber

-Third Party setion:

Buckets



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|-----------|--------------|--------------|
| CX300C STD | 65,900 LB | | \$389,273.00 |



(Ex Works Port of Entry) Factory Supplied Options

| Order Code | Description | Walaht | Eastery Data | List Price |
|-------------|---|--------|--------------|-------------|
| Order Code | Description | Weight | Factory Data | List Price |
| | | | | |
| OOMS | | | | |
| | | | | |
| SD_E5311 BC | DOM | | | |
| 481858 | Standard Boom | | | No Charg |
| | 20'2" (6.15 M) Standard Boom | | | |
| | For use with CX300B (Standard) Commercial Model | | | |
| 781917 | No Boom | | | (\$8,975.0 |
| | Less boom, hoist and arm cylinders and plumbing. | | | |
| | Boom-foot and cylinder pins are provided. | | | |
| | | | | |
| RMS | | | | |
| | | | | |
| | | | | |
| SD_E5320 AF | RM/DIPPERSTICK | | | |
| 481243 | 8'8" (2.63 M) Standard Arm | | | (\$800.0 |
| | For use with 20'2" Standard Boom (option 481858) | | | |
| 781180 | 10'5" (3.18 M) Standard Arm | | | No Charg |
| | For use with 20'2" Standard Boom (option 481858) | | | |
| 481850 | 12' (3.66 M) Standard Arm | | | \$1,800.0 |
| | For use with 20'2" Standard Boom (option 481858) | | | |
| XE5320X | No Arm/Dipperstick | | | (\$4,510.0 |
| | Less arm, bucket cylinder and linkage | | | |
| | For use with CX300B (Standard) Commercial Model only. | | | |
| | | | | |
| RACK SHOES | | | | |
| | | | | |
| | | | | |
| SD_E5199 TR | ACK SHOES | | | |
| 9560002 | 23.6" (600mm) Steel Shoes | | | (\$1,005.00 |
| | Triple-Grouser Steel Shoes | | | |
| 9560003 | 27.6" (700mm) Steel Shoes | | | (\$775.0 |
| | Triple-Grouser Steel Shoes | | | |
| 9560005 | 31.5" (800mm) Steel Shoes | | | No Charg |
| | Triple-Grouser Steel Shoes | | | |
| | | | | |
| | | | | |
| ANGUAGE | | | | |
| ANGUAGE | | | | |
| ANGUAGE | | | | |
| | PERATOR'S MANUAL | | | |

\$125.00

No Charge



CX300C CRAWLER EXCAVATOR US PRICE LIST

| | (Ex Works Port of Entry) | | |
|---------------|--|-----|------------|
| 461540 | French Canadian Language | | No Charge |
| 781980 | Spanish Language Literature | | No Charge |
| ADDITIONAL FO | NUDMENT OVO | | |
| ADDITIONAL EC | CUPMENT CXC | | |
| ADDITIONAL OP | TIONS | | |
| | | | |
| | RACK CHAIN GUIDE | | |
| 461541 | Single Track Chain Guide | | No Charge |
| 461143 | Triple Track Chain Guide | | \$2,440.00 |
| SD E5443 C | CAB GUARD (FOPS) | | |
| XE5443 | X FOPS Top Cab Guard/Level 1 | | No Charge |
| 481070 | · | | \$1,290.00 |
| | CAB GUARD (FRONT) X No Front Guard | | No Charge |
| 461142 | Front grill guard - 2 x 2 mesh | | \$1,500.00 |
| 781986 | Front rock guard (OPG 1) | | \$2,045.00 |
| | vertical bars (two piece/upper and lower) | | . , |
| 461024 | Front rock guard (OPG 2) | | \$2,295.00 |
| | vertical bars (one piece/full length) | | |
| 461552 | Vandal Guard | | \$505.00 |
| SD E5440 E | RAIN DEFLECTOR | | |
| XE5449 | | | No Charge |
| 461555 | Rain Deflector | | \$390.00 |
| 1 1 401000 | Not for use with Front grill guard - 2 x 2 mesh option 461142, | | Ψ000.00 |
| | Front rock guard (OPG 1) option 781986, or | | |
| | Front rock guard (OPG 2) option 461024. | | |
| | , | | |
| SD_E5451 S | | | |
| | X No Sun Visor | | No Charge |
| | 10 10 | _ i | A |

461554 Sun Visor

SD_E6410 AUXILIARY HYDRAULICS

XE6410X No Optional Hydraulics



| HAM ELCT DDO CNITDI | | \$8,500.00 |
|---|--|--|
| | | \$6,500.00 |
| | | |
| | | |
| | | |
| includes manually adjustable relief valve to set required pressures | | |
| Notes: | | |
| 1) Not for use with other Auxiliary Hydraulic options, with the | | |
| exception of Low Flow. | | |
| 2) Heavy duty bucket linkage is standard equipment on | | |
| C series excavators. | | |
| 3) For dealer installed auxiliary hydraulic kits contact: | | |
| HKX (1-800-493-5487 or www.HKX.com) | | |
| HAM/HF W/PRSR ELET PRO CNTRL | | \$12,377.00 |
| Hammer/High Flow Circuit, with Pressure Control, Electrical | | |
| Proportional Control | | |
| Includes in-cab Electronic Pressure Control feature | | |
| | | |
| Joystick Activated | | |
| Pressure Control feature allows hydraulic pressure setting | | |
| from the cab monitor and maintaining pressure settings in | | |
| memory when multiple tools are used. | | |
| | | |
| Provides single or dual pump, two-way flow, for use with | | |
| multiple applications: thumb/grapples/crushers. | | |
| Secondary Low-flow Auxiliary Hydraulics can be added | | |
| Includes in-cab electronically controlled pressure setting feature | | |
| Is switchable to single acting flow for hammer application. | | |
| Notes: | | |
| | | |
| | | |
| · · | | |
| | | |
| | | |
| | | |
| | 1) Not for use with other Auxiliary Hydraulic options, with the exception of Low Flow. 2) Heavy duty bucket linkage is standard equipment on C series excavators. 3) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com) HAM/HF W/PRSR ELET PRO CNTRL Hammer/High Flow Circuit, with Pressure Control, Electrical Proportional Control Includes in-cab Electronic Pressure Control feature Joystick Activated Pressure Control feature allows hydraulic pressure setting from the cab monitor and maintaining pressure settings in memory when multiple tools are used. Provides single or dual pump, two-way flow, for use with multiple applications: thumb/grapples/crushers. Secondary Low-flow Auxiliary Hydraulics can be added Includes in-cab electronically controlled pressure setting feature | Hammer Circuit Electrical Proportional Control Joystick activated Provides single direction flow; use for hammer application Includes manually adjustable relief valve to set required pressures Notes: 1) Not for use with other Auxiliary Hydraulic options, with the exception of Low Flow. 2) Heavy duty bucket linkage is standard equipment on C series excavators. 3) For dealer installed auxiliary hydraulic kits contact: HKX (1-800-493-5487 or www.HKX.com) HAM/HF W/PRSR ELET PRO CNTRL Hammer/High Flow Circuit, with Pressure Control, Electrical Proportional Control Includes in-cab Electronic Pressure Control feature Joystick Activated Pressure Control feature allows hydraulic pressure setting from the cab monitor and maintaining pressure settings in memory when multiple tools are used. Provides single or dual pump, two-way flow, for use with multiple applications: thumb/grapples/crushers. Secondary Low-flow Auxiliary Hydraulics can be added Includes in-cab electronically controlled pressure setting feature Is switchable to single acting flow for hammer application. Notes: 1) Not for use with other Auxiliary Hydraulics options, with the exception of Low Flow. 2) Heavy duty bucket linkage is standard equipment on C series excavators. 3) For dealer installed auxiliary hydraulic kits contact: |



| | 404074 | ALIX TMD ELEC DDO CNTDI | CC 244 00 |
|-----------------|-------------|--|----------------|
| | 461871 | AUX, TMB ELEC PRO CNTRL | \$6,341.00 |
| | | Auxiliary Circuit, Thumb, Electrical Proportional Control | |
| | | Joystick activated | |
| | | Provides single pump, two-way flow; use for thumb application | |
| | | Hydraulic plumbing provided to the end of the boom only, | |
| | | no piping to the arm | |
| | | This system is not switchable to single acting flow | |
| | | Notes: | |
| | | 1) Not for use other Auxiliary Hydraulics options with the | |
| | | exception of Low Flow. | |
| | | 2) Heavy duty bucket linkage is standard equipment on | |
| | | C series excavators. | |
| | | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | | HKX (1-800-493-5487 or www.HKX.com). | |
| | | | |
| | SD_E6417 SE | CONDARY AUXILIARY HYDRAULICS | |
| | XE6417X | No Extra Auxiliary Hydraulics | No Charge |
| | 461863 | LF ELCT PRO CNTRL | \$6,931.00 |
| | | Low Flow Electrical Proportional Control | |
| | | Joystick Activated | |
| | | Provides low-flow for rotation or tilt of hydraulic tools. | |
| | | Notes: | |
| | | 1) May be used standalone or with any Case Excavator Auxiliary | |
| | | Hydraulics option. | |
| | | 2) For dealer installed auxiliary hydraulic kits contact: | |
| | | HKX (1-800-493-5487 or www.HKX.com). | |
| | . | | |
| | SD_E6423 CC | ONTROL PATTERN SELECTION | |
| | XE6423X | No Control Pattern Valve | No Charge |
| | 461558 | Control Pattern Selector Valve | \$950.00 |
| | | | |
| | SD_E9730 SA | | |
| \vdash | | No Hose Burst Check Valve | No Charge |
| | 461559 | Hose Burst Check Valve (HBCV) | \$9,130.00 |
| \Box | | boom and arm | |
| | SD E0740 SI | DE VIEW CAMERA | |
| | | DE VIEW CAMERA No Side View Camera | No Charge |
| $\vdash \vdash$ | 461560 | Side View Camera Side View Camera | \$725.00 |
| ш | 401000 | Joine view Gaillela | ⊅/25.00 |

SD_E9741 FREE SWING

461568

XE9741X No Free Swing

Free Swing

switch activated

No Charge

\$285.00



(Ex Works Port of Entry)

SD_E9874 REFUEL PUMP

| | XE9874X | No Refuel Pump | | No Charge |
|--|---------|----------------|--|------------|
| | 481257 | Refuel Pump | | \$1,050.00 |



(Ex Works Port of Entry) Factory Supplied Attachments

| Order Code | Description | Weight | Factory Data | List Price |
|--|--|----------|--------------|------------------|
| D' 0 D | | | | |
| ase Pin On Bud | | 1 | | ^- |
| 84404254 | 36" Heavy Duty Bucket with 5 teeth (1.18 cu. yd.) | 2,157 LB | | \$7,335.00 |
| 84404255 | 42" Heavy Duty Bucket | 2,311 LB | | \$7,874.00 |
| 04404255 | with 5 teeth (1.42 cu. yd.) | 2,311 LB | | \$7,874.00 |
| 84404256 | 48" Heavy Duty Bucket | 2,600 LB | | \$8,661.00 |
| | with 6 teeth (1.65 cu. yd.) | | | ψο,σσσ |
| 84404257 | 36" Heavy Duty High Capacity Bucket | 2,875 LB | | \$8,317.00 |
| | with 5 teeth (1.52 cu. yd.) | | | |
| 84404258 | 42" Heavy Duty High Capacity Bucket | 3,100 LB | | \$8,818.00 |
| | with 5 teeth (1.85 cu. yd.) | | | |
| 84404259 | 48" Heavy Duty High Capacity Bucket | 3,400 LB | | \$9,698.00 |
| | with 6 teeth (2.12 cu. yd.) | | | |
| 84404260 | 54" Heavy Duty High Capacity Bucket | 3,625 LB | | \$10,668.00 |
| 0.440.4004 | with 6 teeth (2.42 cu. yd.) | 2 500 LD | | <u>Фо</u> гоо ос |
| 84404261 | 36" Severe Duty Bucket with 5 teeth (1.18 cu. yd.) | 2,500 LB | | \$8,590.00 |
| 84404262 | 42" Severe Duty Bucket | 2,650 LB | | \$9,228.00 |
| 04404202 | with 5 teeth (1.42 cu. yd.) | 2,000 LB | | ψ5,220.00 |
| 84404265 | 48" Severe Duty Bucket | 3,000 LB | | \$10,151.00 |
| | with 6 teeth (1.65 cu. yd.) | | | |
| 84404266 | 60" Ditching Bucket (1.71 cu. yd.) | 1,950 LB | | \$6,569.00 |
| 84404267 | 72" Ditching Bucket (2.09 cu. yd.) | 2,250 LB | | \$7,002.00 |
| | | | | |
| se Coupler Bu | | | | |
| 84404268 | 36" Heavy Duty Coupler Bucket | 2,120 LB | | \$8,786.00 |
| | with 5 teeth (1.26 cu. yd.) | | | |
| 84404269 | 42" Heavy Duty Coupler Bucket | 2,300 LB | | \$9,664.00 |
| 84404270 | with 5 teeth (1.52 cu. yd.) 48" Heavy Duty Coupler Bucket | 2,440 LB | | \$10,630.00 |
| 04404270 | with 6 teeth (1.78 cu. yd.) | 2,440 LB | | \$10,030.00 |
| 84404272 | 54" Heavy Duty Coupler Bucket | 2,725 LB | | \$11,692.00 |
| | with 6 teeth (2.03 cu. yd.) | 2,720 25 | | Ψ11,002.00 |
| | , , | ' | ' | |
| ase Multi Fit Co | pupler | | | |
| 447966A1 | Case Multi Fit Hydraulic Coupler | 1,447 LB | | \$12,804.00 |
| | Optimized for use with Case coupler buckets. | | | |
| | Also can be used with a wide range of buckets from | | | |
| | other manufacturers including pin-on types. | | | |
| | Includes hydraulic installation kit and instructions. | | | |



(This page intentionally left blank)



OPERATOR'S CAB (Continued):

(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AL-6HK1X Cab interior features: Tier 4 Interim Certified (CEGR) Cup holder 475 cubic in. displacement/7.8 Liter Storage compartments Turbocharged/air cooled intercooler Warm/cool storage compartments Horsepower: Easy access fuse box Net: 266 (198 kW) @ 1900 RPM Interior light (1 x 10 watt) One touch lock front window High pressure common rail system Auto engine warm-up Two-speed independent travel FEA (Fuel Economy Assist System) One key start and lock-up Engine Idle/Fuel Economy System: Single pedal travel Auto Idle Straight travel One-touch Idle Travel alarm and horn Idle Shut-down Windshield wiper and washer Fuel Capacity: Programmable anti-theft system 153 gallons (580 L) AEC (auto economy control) ELECTRICAL: BEC (boom economy control) 24-volt system Two batteries (12 volt/92 Ah) OPERATOR'S CAB: 50 Amp Alternator ROPS protection Worklights (4 x 70 watt) Boom mounted (1) Pressurized cab area AC/heat/defrost w/climate control Upper mounted (1) Electronics: Cab mounted (2) Color monitor (7 in/180 mm) Telematics Ready with rearview camera view Wiring harness and 16-pin connector Rearview camera AM/FM radio with antenna and HYDRAULICS: 2-speakers Open-center system design Aux-in port for personal electronics Selectable work modes (3) 12-volt electric socket Auto power boost 24-volt cigarette lighter Auto swing priority Air-suspension seat (cloth) SWC (swing relief control) KAB® adjustable deluxe seat SSC (spool stroke control) Seat belt - 3" 5000 hour hydraulic oil change interval Adjustable arm rests 1000 hour hyd. filter change interval 4-position tilting consoles Sliding cockpit (7 in/180 mm) Low-effort joystick controls Clear (poly carbonate) roof window External rearview mirrors Rubber floormat



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE: X-pattern carbody Undercarriage: STD LC: 16'4" (4.98 M) length Track Gauge: STD LC: 8'6" (2.6 M) gauge Shoe: STD: 31.5" (850 mm) triple grouser 8.5" pitch 48 shoes per side Carrier rollers (2 per side) Track rollers (8 per side) Grease lubricated and strutted track chains Hydraulic track adjustment Double track chain guides SAHR disc parking break Tapered upper track frame

ATTACHMENTS:

Standard LC Version:
Boom: 21'2" (6.45 M)
Arm: 10'8" (3.25 M)
Heavy-duty bucket linkage
Auxiliary pipe brackets
Attachment cushion valve
Arm and boom regeneration

MISCELLANEOUS:

One key lock-up Centralized lube bank High Ambient Temperature Cooling Package

OTHER BASIC EQUIPMENT:

CASE SiteWatch™ - on board telematics

OPTIONAL EQUIPMENT Cab and Operator's Station: Side view camera Sun visor FOPS cab top guard (Level 2) Front grill guard (2" x 2" mesh) Front rock guard (OPG 1) Front rock guard (OPG 2) Vandal quard Rain deflector Control pattern change selector Free swing Hose burst check valve (HBSV) Refueling pump Auxiliary hydraulics Attachments: Arm: 13'3" (4.04 M) Arm: 8'8" (2.63 M) Heavy-duty Arm: 10'8" (3.25 M) Heavy-duty Load holding control Undercarriage: Steel shoes/triple-grouser: 27.6" (700 mm) Steel shoes/triple-grouser:

Order from Wholegood Attachments
-Third Party setion:
Case multi fit Coupler
Buckets
Rubber bumpers for upper
(order through Service Parts)

33.5" (850 mm)



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|-----------|--------------|--------------|
| CX350C STD | 80,000 LB | | \$432,996.00 |



(Ex Works Port of Entry) Factory Supplied Options

| Order Cede | Description | Weight | Footowy Data | Liet Dries |
|------------|-------------|--------|--------------|------------|
| Order Code | Description | weight | Factory Data | List Price |

BOOMS

SD E5311 BOOM

| _ | ${-}$ | D_ESSTI BO | OW | | |
|---|-------|------------|--|--|---------------|
| | | 481858 | Standard Boom | | No Charge |
| | | | 21'2" (6.45 M) Standard Boom | | |
| | | | For use with CX350C (Standard) Commercial Model | | |
| | | 461543 | Heavy-Duty Boom | | \$3,045.00 |
| | | | 21'2" (6.45 M) Heavy-Duty Boom | | |
| | | | For use with CX350C (Standard) Commercial Model | | |
| | | 781917 | No Boom | | (\$10,630.00) |
| | | | Less boom, hoist and arm cylinders and plumbing. | | |
| | | | Boom-foot and cylinder pins are provided. | | |

ARMS

SD_E5320 ARM/DIPPERSTICK

| 481245 | 10' 8" (3.25M) Standard Arm | | No Charge |
|---------|--|--|--------------|
| | For use with 21'2" Standard Boom (option 481858) | | |
| 781184 | 13'3" (4.04 M) Standard Arm | | \$3,195.00 |
| | For use with 21'2" Standard Boom (option 481858) | | |
| 461546 | 8'8" (2.63 M) Heavy-Duty Arm | | \$160.00 |
| | For use with either boom option 481858 or 461543 | | |
| 461545 | 10'8" (3.25 M) Heavy-Duty Arm | | \$2,630.00 |
| | For use with either boom option 481858 or 461543 | | |
| XE5320X | No Arm/Dipperstick | | (\$6,385.00) |
| | Less arm, bucket cylinder and linkage. | | |
| | For use with CX350C Standard Model only. | | |

TRACK SHOES

SD_E5199 TRACK SHOES

| | 9560003 | 27.6" (700mm) Steel Shoes | | (\$900.00) |
|--|---------|----------------------------|--|------------|
| | | Triple-Grouser Steel Shoes | | |
| | 9560005 | 31.5" (800mm) Steel Shoes | | No Charge |
| | | Triple-Grouser Steel Shoes | | |
| | 9560006 | 33.5" (850 mm) Steel Shoes | | \$530.00 |
| | | Triple-Grouser Steel Shoes | | |



| LANGUAGE | | |
|-----------------|--|---------------------------------------|
| | | |
| | | |
| | ERATOR'S MANUAL | |
| 781981 | English Language Literature | No Charge |
| 461540 | French Canadian Language | No Charge |
| 781980 | Spanish Language Literature | No Charge |
| | | |
| ADDITIONAL EQU | IPMENT CXC | |
| | | |
| ADDITIONAL OPTI | ONS | |
| 00 E5000 TD | AOV CHAIN CHIPE | |
| | ACK CHAIN GUIDE | No Charra |
| 461542 | Double Track Chain Guide | No Charge |
| CD FE442 CA | D CHARD (FORC) | |
| | B GUARD (FOPS) FOPS Top Cab Guard/Level 1 | No Chargo |
| 481070 | FOPS Top Cab Guard/Level 2 | No Charge \$1,290.00 |
| 401070 | 1 Of 3 Top Cab Odato/Level 2 | ψ1,230.00 |
| SD E5444 CA | B GUARD (FRONT) | |
| | No Front Guard | No Charge |
| 461142 | Front grill guard - 2 x 2 mesh | \$1,500.00 |
| 781986 | Front rock guard (OPG 1) | \$2,045.00 |
| | vertical bars (two piece/upper and lower) | φ2,010.00 |
| 461024 | Front rock guard (OPG 2) | \$2,295.00 |
| | vertical bars (one piece/full length) | V =,233.33 |
| 461552 | Vandal Guard | \$505.00 |
| | | , , , , , , , , , , , , , , , , , , , |
| SD_E5448 CA | TWALK | |
| | No Catwalk | No Charge |
| 461553 | Catwalk - Left and Right Sides | \$2,435.00 |
| | (Note: catwalk is not compliant with ISO standards) | |
| | | |
| SD_E5449 RA | IN DEFLECTOR | |
| XE5449X | No Rain Deflector | No Charge |
| 461555 | Rain Deflector | \$390.00 |
| | Not for use with Front grill guard - 2 x 2 mesh option 461142, | |
| | Front rock guard (OPG 1) option 781986, or | |
| | Front rock guard (OPG 2) option 461024. | |
| | | |
| SD_E5451 SU | | |
| | No Sun Visor | No Charge |
| 461554 | Sun Visor | \$125.00 |
| | W | |
| | XILIARY HYDRAULICS | 1 1 2 |
| XE6410X | No Optional Hydraulics | No Charge |



| 461865 | HAM ELCT PRO CNTRL | \$8,555.00 |
|--------|---|-------------|
| 401000 | | φο,555.00 |
| | Hammer Circuit Electrical Proportional Control | |
| | Joystick activated | |
| | Provides single direction flow; use for hammer application | |
| | Includes manually adjustable relief valve to set required pressures | |
| | Notes: | |
| 1 1 1 | 1) Not for use with other Auxiliary Hydraulic options, with the | |
| 1 1 1 | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com) | |
| 461869 | HAM/HF W/PRSR ELET PRO CNTRL | \$13,038.00 |
| 1 1 1 | Hammer/High Flow Circuit, with Pressure Control, Electrical | |
| 1 1 1 | Proportional Control | |
| | Includes in-cab Electronic Pressure Control feature | |
| | | |
| 1 1 1 | Joystick Activated | |
| 1 1 1 | Pressure Control feature allows hydraulic pressure setting | |
| 1 1 1 | from the cab monitor and maintaining pressure settings in | |
| | memory when multiple tools are used. | |
| | Provides single or dual pump, two-way flow, for use with | |
| | multiple applications: thumb/grapples/crushers. | |
| | Secondary Low-flow Auxiliary Hydraulics can be added | |
| | Includes in-cab electronically controlled pressure setting feature | |
| | Is switchable to single acting flow for hammer application. | |
| | Notes: | |
| | 1) Not for use with other Auxiliary Hydraulics options, with the | |
| | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com) | |



| | | (Ex Works Port of Entry) | |
|----------|--------------|--|------------|
| | 461871 | AUX, TMB ELEC PRO CNTRL | \$6,541.00 |
| | | Auxiliary Circuit, Thumb, Electrical Proportional Control | |
| | | Joystick activated | |
| | | Provides single pump, two-way flow; use for thumb application | |
| | | Hydraulic plumbing provided to the end of the boom only, | |
| | | no piping to the arm | |
| | | This system is not switchable to single acting flow | |
| | | | |
| | | Notes: | |
| | | 1) Not for use other Auxiliary Hydraulics options with the | |
| | | exception of Low Flow. | |
| | | 2) Heavy duty bucket linkage is standard equipment on | |
| | | C series excavators. | |
| | | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | | HKX (1-800-493-5487 or www.HKX.com). | |
| | | | |
| | SD_E6417 SE | CONDARY AUXILIARY HYDRAULICS | |
| | XE6417X | No Extra Auxiliary Hydraulics | No Charge |
| | 461863 | LF ELCT PRO CNTRL | \$8,415.00 |
| | | Low Flow Electrical Proportional Control | |
| | | Joystick Activated | |
| | | Provides low-flow for rotation or tilt of hydraulic tools. | |
| | | | |
| | | Notes: | |
| | | 1) May be used standalone or with any Case Excavator Auxiliary | |
| | | Hydraulics option. | |
| | | 2) For dealer installed auxiliary hydraulic kits contact: | |
| | | HKX (1-800-493-5487 or www.HKX.com). | |
| | | | |
| | SD_E6423 CC | NTROL PATTERN SELECTION | |
| \sqcup | XE6423X | No Control Pattern Valve | No Charge |
| | 461558 | Control Pattern Selector Valve | \$950.00 |
| | | | |
| | SD_E9730 SA | | |
| \vdash | | No Hose Burst Check Valve | No Charge |
| | 461559 | Hose Burst Check Valve (HBCV) | \$9,130.00 |
| | | boom and arm | |
| | 00 50540 015 | NE VIEW 0444ED4 | |
| | | DE VIEW CAMERA | |
| \vdash | | No Side View Camera | No Charge |
| | 461560 | Side View Camera | \$725.00 |
| | CD E0744 FD | EE SWING | |
| | SD_E9741 FR | No Free Swing | No Charge |
| H | 461568 | Free Swing | \$285.00 |
| | 401300 | 3 | \$205.00 |
| \Box | | switch activated | |



(Ex Works Port of Entry)

SD_E9874 REFUEL PUMP

| | XE9874X | No Refuel Pump | | No Charge |
|--|---------|----------------|--|------------|
| | 481257 | Refuel Pump | | \$1,050.00 |



(Ex Works Port of Entry) Factory Supplied Attachments

| Ord | ler Code | Description | Weight | Factory Data | List Price |
|--------|---------------|--|----------|--------------|------------|
| ase Pi | in On Buck | rets | | | |
| | 84404275 | 36" Heavy Duty Bucket with 4 teeth (1.13 cu. yd.) | 2,530 LB | | \$8,447.00 |
| | 84404276 | 42" Heavy Duty Bucket with 5 teeth (1.39 cu. yd.) | 2,670 LB | | \$9,087.00 |
| | 84404277 | 48" Heavy Duty Bucket with 5 teeth (1.64 cu. yd.) | 3,040 LB | | \$9,408.0 |
| | 84404278 | 42" Heavy Duty High Capacity Bucket with 5 teeth (1.52 cu. yd.) | 2,870 LB | | \$10,578.0 |
| | 84404279 | 48" Heavy Duty High Capacity Bucket with 5 teeth (1.85 cu. yd.) | 3,270 LB | | \$11,289.0 |
| | 84404280 | 54" Heavy Duty High Capacity Bucket with 6 teeth (2.12 cu. yd.) | 3,450 LB | | \$12,070.0 |
| | 84404282 | 36" Severe Duty Bucket with 4 teeth (1.13 cu. yd.) | 2,910 LB | | \$9,501.0 |
| П | 84404284 | 42" Severe Duty Bucket with 5 teeth (1.39 cu. yd.) | 3,075 LB | | \$10,622.0 |
| | 84404286 | 48" Severe Duty Bucket with 5 teeth (1.64 cu. yd.) | 3,500 LB | | \$11,577.0 |
| | 84405399 | 60" Heavy Duty Bucket with 6 teeth (2.42 cu. yd.) | 3,870 LB | | \$12,440.0 |
| ase C | oupler Bud | ckets | | · | |
| | 84404288 | 42" Heavy Duty Coupler Bucket with 5 teeth (1.73 cu. yd.) | 2,745 LB | | \$10,834.0 |
| | 84404289 | 48" Heavy Duty Coupler Bucket with 5 teeth (2.03 cu. yd.) | 3,200 LB | | \$11,627.0 |
| | 84404290 | 54" Heavy Duty Coupler Bucket with 6 teeth (2.33 cu. yd.) | 3,410 LB | | \$12,635.0 |
| ase M | lulti Fit Cou | upler | | | |
| | 447976A1 | Case Multi Fit Hydraulic Coupler Optimized for use with Case coupler buckets. Also can be used with a wide range of buckets from other manufacturers including pin-on types. Includes hydraulic installation kit and instructions. | 1,535 LB | | \$14,772.0 |



(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

```
ENGINE:
                                                    OPERATOR'S CAB (Continued):
  Isuzu AL-6UZ1X
                                                      Rubber floormat
 Tier 4 Interim Certified (CEGR)
                                                      Cab interior features:
  600 cubic in. displacement/9.8 liter
                                                        Cup holder
 Turbocharged/air cooled intercooler
                                                        Storage compartments
 Horsepower:
                                                        Warm/cool storage compartments
   Net: 362 HP (kW) @ 2000 RPM
                                                        Easy access fuse box
 High pressure common rail system
                                                        Interior dome light
 Auto engine warm-up
                                                        One touch lock front window
 FEA (Fuel Economy Assist System)
                                                        One key start & lock-up
 Engine Idle/Fuel Economy System:
                                                      Single pedal travel
   Auto Idle
                                                      Two-speed independent travel
   One-touch Idle
                                                      Straight travel
   Idle Shut-down
                                                      Travel alarm and horn
 Fuel Capacity:
                                                      Windshield wiper and washer
                                                      Programmable anti-theft system
    172 gallons (650 L)
 AEC (auto economy control)
                                                    ELECTRICAL:
 BEC (boom economy control)
 High Ambient Temperature Cooling
                                                      24-volt system
                                                      Two batteries (12 volt/92 Ah)
    Package
                                                      50 Amp Alternator
OPERATOR'S CAB:
                                                      Worklights (4 x 70 watt)
 ROPS protection
                                                        Boom mounted (1)
 FOPS - cage type (Level II)
                                                        Upper mounted (1)
 Pressurized cab area
                                                        Cab mounted (2)
 AC/heat/defrost w/climate control
                                                      Telematics Ready
  Electronics:
                                                        Wiring harness and 16-pin connector
   Color monitor (7 in/180 mm)
      with rearview camera view
                                                    HYDRAULICS:
   Rearview camera
                                                      Open-center system design
    AM/FM radio with antenna and
                                                      Selectable work modes (3)
                                                      Auto power boost
      2-speakers
   Aux-in port for personal electronics
                                                      Auto swing priority
    12-volt electric socket
                                                      SWC (swing relief control)
                                                      SSC (spool stroke control)
    24-volt cigarette lighter
                                                      5000 hour hydraulic oil change interval
 Air-suspension seat (cloth)
   KAB® adjustable deluxe seat
                                                      1000 hour hydraulic filter change
    Seat belt - 3"
                                                        interval
   Adjustable arm rests
    4-position tilting consoles
    Sliding cockpit (7 in/180 mm)
  Low-effort joystick controls
  Clear (poly carbonate) roof window
```

External rearview mirrors



(Ex Works Port of Entry) Standard Equipment

```
UNDERCARRIAGE:
                                                    OPTIONAL EQUIPMENT:
  X-pattern carbody
                                                      Cab and Operator's Station:
 Undercarriage:
                                                        Side view camera
    STD LC: 17'11" (5.45 M) length
                                                        Sun visor
  Track Gauge :
                                                        Front grill guard (2" x 2" mesh)
    Fixed side frame: 8'11"(2.72 M)
                                                        Front rock guard (OPG 1)
    Retractable side frame (min.):
                                                        Front rock guard (OPG 2)
      710" (2.39 M)
                                                        Vandal guard (not for use with FOPS
    Retractable side frame (max.):
                                                          top cab quard)
      9'6" (2.89 M)
                                                      Control pattern change selector
  Shoe:
                                                      Free swing
    STD: 35.4" (900 mm) triple grouser
                                                      Refueling pump
         9.0" pitch
                                                      Hydraulic CWT removal device
         50 shoes per side
                                                      Auxiliary hydraulics
  Carrier rollers (2 per side)
                                                      Attachments:
  Track rollers (9 per side)
                                                        Arm: 13'3" (4.00 M)
  Grease lubricated/strutted track chains
                                                        Arm: 15'11" (4.85 M)
 Hydraulic track adjustment
                                                        Arm: 8'4" (2.53 M) Heavy-duty
  Double track chain guides
                                                        Hose burst check valve (HBCV)
  SAHR disc parking break
                                                        Case multi fit Coupler
  Tapered upper track frame
                                                        Buckets
                                                        Load holding control
ATTACHMENTS:
                                                      Under carriage:
  Standard Version:
                                                        Steel shoes/triple-grouser:
    Boom: 22'11" (6.98 M)
                                                          29.5" (750 mm)
    Arm: 11'1" (3.38 M) Heavy-duty
                                                        Full length track chain guides
  Heavy-duty bucket linkage
                                                        Rubber bumpers for upper
 Auxiliary pipe brackets
                                                          (order through Service Parts)
  Attachment cushion valve
 Arm and boom regeneration
 Arm and boom holding valves
  Centralized grease bank
OTHER BASIC EQUIPMENT:
  CASE SiteWatch™ - on board
    telematics
```



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | | Weight | Factory Data | List Price |
|------------------|----------------------|------------|--------------|--------------|
| | UNDERCARRIAGE/CHASSI | | | |
| | s | | | |
| CX470C STD | Long Chassis | 103,635 LB | | \$613,514.00 |
| CX470C RTC | Retractable Chassis | | | \$641,015.00 |



(Ex Works Port of Entry) Factory Supplied Options

| Order Code | Description | Weight | Factory Data | List Price |
|-------------|--|--------|--------------|---------------------|
| | | | | |
| BOOMS | | | | |
| | | | | |
| | | | | |
| SD_E5311 BC | OOM | | | |
| 481858 | Standard Boom | | | No Charge |
| | 22'11" (6.98 M) Standard Boom | | | |
| | For use with CX470C (Standard and RTC) Commercial Model | | | |
| 781917 | No Boom | | | (\$18,675.00) |
| | Less boom, hoist and arm cylinders and plumbing. | | | |
| | Boom-foot and cylinder pins are provided. | | | |
| | | | | |
| ARMS | | | | |
| | | | | |
| | | | | |
| SD_E5320 AF | RM/DIPPERSTICK | | | |
| 461549 | 11'1" (3.38 M) Heavy-duty Arm | | | No Charge |
| | For use with 22'11" Standard Boom (option 481858) | | | _ |
| 461548 | 8'4" (2.53 M) Heavy-duty Arm | | | (\$125.00) |
| | For use with 22'11" Standard Boom (option 481858) | | | , , |
| 781184 | 13'3" (4.04 M) Standard Arm | | | \$565.00 |
| | For use with 22'11" Standard Boom (option 481858) | | | |
| 461544 | 15'11" (4.85 M) Standard Arm | | | \$3,620.00 |
| | For use with 22'11" Standard Boom (option 481858) | | | *-,- |
| XE5320X | | | | (\$11,010.00) |
| | Less arm, bucket cylinder and linkage | | | (+ : :, = : = : =) |
| | 1 2000 tilling and till till till till till till till til | | I | |
| TRACK SHOES | | | | |
| TRACK SHOES | | | | |
| | | | | |
| CD FE100 TF | DACK SHOES | | | |
| SD_E5199 TF | | | | No Chargo |
| 9560007 | 35.4" (900mm) Steel Shoes | | | No Charge |
| 0500004 | Triple-Grouser Steel Shoes | + | | (CA 045 00) |
| 9560004 | 29.5" (750mm) Steel Shoes | | | (\$1,245.00) |
| | Triple-Grouser Steel Shoes | | 1 | |
| | | | | |
| LANGUAGE | | | | |
| | | | | |
| | | | | |
| | PERATOR'S MANUAL | | | |
| 781981 | English Language Literature | | | No Charge |
| 1 1 404540 | I English Control Cont | 1 | | |

461540 French Canadian Language

No Charge



| | (Ex Works Port of Entry) | |
|----------------|---|-------------|
| 781980 | Spanish Language Literature | No Charge |
| | | |
| ADDITIONAL EQ | UIPMENT CXC | |
| | | |
| ADDITIONAL OPT | TIONS | |
| | | |
| | RACK CHAIN GUIDE | |
| 461542 | Double Track Chain Guide | No Charge |
| 481264 | Full Length Track Chain Guards | \$4,800.00 |
| CD E5202 II | VPDALILIC OWT DEMOVAL DEVICE | |
| | YDRAULIC CWT REMOVAL DEVICE No Hyd CWT Removal Device | No Charge |
| 481263 | Hydraulic CWT Removal Device | \$21,900.00 |
| 401200 | Trydraulic OVV Thermoval Device | Ψ21,000.00 |
| SD F5444 C | AB GUARD (FRONT) | |
| | No Front Guard | No Charge |
| 461142 | Front grill guard - 2 x 2 mesh | \$1,500.00 |
| 781986 | Front rock guard (OPG 1) | \$2,045.00 |
| | vertical bars (two piece/upper and lower) | |
| 461024 | Front rock guard (OPG 2) | \$2,295.00 |
| | vertical bars (one piece/full length) | |
| 461552 | Vandal Guard | \$505.00 |
| | | |
| SD_E5448 C | | |
| T I | No Catwalk | No Charge |
| 461553 | Catwalk - Left and Right Sides | \$2,435.00 |
| | (Note: catwalk is not compliant with ISO standards) | |
| SD_E5451 S | UN VISOR | |
| | No Sun Visor | No Charge |
| 461554 | Sun Visor | \$125.00 |
| 1 1 401004 | Guri Visor | Ψ120.00 |
| SD E6410 A | UXILIARY HYDRAULICS | |
| | No Optional Hydraulics | No Charge |
| 461865 | HAM ELCT PRO CNTRL | \$9,406.00 |
| | Hammer Circuit Electrical Proportional Control | |
| | Joystick activated | |
| | Provides single direction flow; use for hammer application | |
| | Includes manually adjustable relief valve to set required pressures | |
| | | |
| | Notes: | |
| | 1) Not for use with other Auxiliary Hydraulic options, with the | |
| | exception of Low Flow. | |
| | 2) Heavy duty bucket linkage is standard equipment on | |
| | C series excavators. | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com) | |



| \$12,918.00 |
|-------------|
| ÷ .=, |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| \$7,060.00 |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| _ |

| CD EC447 | CECONDARY | ALIVII IA DV LIVDD ALII ICC | |
|----------|-----------|-----------------------------|--|
| SD E041/ | SECUNDARI | AUXILIARY HYDRAULICS | |

| | | XE6417X | No Extra Auxiliary Hydraulics | | | No Charge | |
|--|--|---------|-------------------------------|--|--|-----------|--|
|--|--|---------|-------------------------------|--|--|-----------|--|

\$285.00

No Charge

\$1,050.00



CX470C CRAWLER EXCAVATOR US PRICE LIST

| 461863 LF ELCT PRO CNTRL Low Flow Electrical Proportional Control Joystick Activated Provides low-flow for rotation or tilt of hydraulic tools. Notes: 1) May be used standalone or with any Case Excavator Auxiliary | |
|---|------|
| Low Flow Electrical Proportional Control Joystick Activated Provides low-flow for rotation or tilt of hydraulic tools. Notes: | 6.00 |
| Provides low-flow for rotation or tilt of hydraulic tools. Notes: | |
| Notes: | |
| | |
| | |
| 1) May be used standalone or with any Case Excavator Auxiliary | |
| | |
| Hydraulics option. | |
| 2) For dealer installed auxiliary hydraulic kits contact: | |
| HKX (1-800-493-5487 or www.HKX.com). | |
| SD_E6423 CONTROL PATTERN SELECTION | |
| XE6423X No Control Pattern Valve | arge |
| 461558 Control Pattern Selector Valve \$9 | 0.00 |
| SD_E9730 SAFETY VALVE | |
| XE9730X No Hose Burst Check Valve No C | arge |
| 461559 Hose Burst Check Valve (HBCV) \$9,1 | 0.00 |
| boom and arm | |
| SD_E9740 SIDE VIEW CAMERA | |
| XE9740X No Side View Camera No C | arge |
| 461560 Side View Camera \$7 | 5.00 |
| SD_E9741 FREE SWING | |
| XE9741X No Free Swing No C | arge |

461568

SD_E9874 REFUEL PUMP

Free Swing

XE9874X No Refuel Pump

481257 Refuel Pump

switch activated

| Page | 131 | οf | 162 |
|------|-----|----|-----|



(This page intentionally left blank)



(Ex Works Port of Entry) Factory Supplied Attachments

| 0 | rder Code | Description | Weight | Factory Data | List Price |
|------|---------------|--|----------|--------------|-------------|
| Case | Pin On Buck | kets | | | |
| | 84404291 | 48" Heavy Duty Bucket with 5 teeth (2.03 cu. yd.) | 3,430 LB | | \$10,877.00 |
| | 84404292 | 54" Heavy Duty Bucket with 6 teeth (2.33 cu. yd.) | 3,650 LB | | \$11,606.00 |
| | 84404293 | 60" Heavy Duty Bucket with 6 teeth (2.63 cu. yd.) | 3,975 LB | | \$12,535.00 |
| | 84404294 | 48" Extra Heavy Duty Bucket with 5 teeth (2.61 cu. yd.) | 4,060 LB | | \$12,167.00 |
| | 84404295 | 54" Extra Heavy Duty Bucket with 6 teeth (2.99 cu. yd.) | 4,350 LB | | \$12,546.00 |
| | 84404296 | 60" Extra Heavy Duty Bucket with 6 teeth (3.37 cu. yd.) | 4,630 LB | | \$13,550.00 |
| | 84404297 | 48" Severe Duty Bucket with 5 teeth (2.03 cu. yd.) | 3,850 LB | | \$14,662.00 |
| | 84404298 | 54" Severe Duty Bucket with 6 teeth (2.33 cu. yd.) | 4,100 LB | | \$15,835.00 |
| | 84404299 | 60" Severe Duty Bucket with 6 teeth (2.63 cu. yd.) | 4,450 LB | | \$17,104.00 |
| Case | Multi Fit Cou | upler | | | |
| | 449716A1 | Case Multi Fit Hydraulic Coupler Optimized for use with Case coupler buckets. Also can be used with a wide range of buckets from other manufacturers including pin-on types. Includes hydraulic installation kit and instructions. | 2,430 LB | | \$18,698.00 |



(This page intentionally left blank)



CX470C MASS EXCAVATION CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

ENGINE: OPERATOR'S CAB (continued): Isuzu AL-6UZ1X Rubber floormat Tier 4 Interim Certified (CEGR) Cab interior features: 600 cubic in. displacement/9.8 liter Cup holder Turbocharged/air cooled intercooler Storage compartments Horsepower: Warm/cool storage compartments Net: 362 HP kW) @ 2000 RPM Easy access fuse box High pressure common rail system Interior dome light Auto engine warm-up One touch lock front window One key start & lock-up FEA (Fuel Economy Assist System) Engine Idle/Fuel Economy System: Single pedal travel Auto Idle Two-speed independent travel One-touch Idle Straight travel Travel alarm and horn Idle Shut-down Windshield wiper and washer Fuel Capacity: Programmable anti-theft system 172 gallons (650 L) AEC (auto economy control) Worklights (2) BEC (boom economy control) High Ambient Temperature Cooling ELECTRICAL: 24-volt system Package Two batteries (12 volt/92 Ah) OPERATOR'S CAB: 50 Amp Alternator ROPS protection Worklights (4 x 70 watt) FOPS - cage type (Level II) Boom mounted (1) Pressurized cab area Upper Mounted (1) AC/heat/defrost w/climate control Cab mounted (2) Electronics: Telematics Ready Color monitor (7 in/180 mm) Wiring harness and 16-pin connector with Rearview camera view HYDRAULICS: Rearview camera AM/FM radio with antenna and Open-center system design 2-speakers Selectable work modes (3) Aux-in port for personal electronics Auto power boost 12-volt electric socket Auto swing priority 24-volt cigarette lighter SWC (swing relief control) Air-suspension seat (cloth) SSC (spool stroke control) 5000 hour hydraulic oil change interval KAB® adjustable deluxe seat Seat belt - 3" 1000 hour hydraulic filter change Adjustable arm rests interval 4-position tilting consoles Sliding cockpit (7 in/180 mm) Low-effort joystick controls Clear (poly carbonate) roof window External rearview mirrors



CX470C MASS EXCAVATION CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

```
UNDERCARRIAGE:
 X-pattern carbody
 Undercarriage:
    STD LC: 17'11" (5.45 M) length
 Track Gauge :
   Fixed side frame: 8'11"(2.72 M)
   Retractable sideframe (min.):
     710" (2.39 M)
   Retractable sideframe (max.):
     9'6" (2.89 M)
  Shoe:
    STD: 35.4" (900 mm) triple grouser
         9.0" pitch
         50 shoes per side
 Carrier rollers (2 per side)
 Track rollers (9 per side)
 Grease lubricated/strutted track chains
 Hydraulic track adjustment
 Double track chain guides
 SAHR disc parking break
  Tapered upper track frame
ATTACHMENTS:
 Standard Version:
    Boom: 21'6" (6.55 M) Mass Ex.
      Boom
   Arm: 84" (2.53 M) Mass Ex. Arm
 Heavy-duty bucket linkage
 Auxiliary pipe brackets
 Attachment cushion valve
 Arm and boom regeneration
 Arm and boom holding valves
 Centralized grease bank
OTHER BASIC EQUIPMENT:
 CASE SiteWatch™ - on board
   telematics
```

```
OPTIONAL EQUIPMENT:
  Cab and Operator's Station:
    Side view camera
    Sun visor
    Front grill guard (2" x 2" mesh)
    Front rock guard (OPG 1)
    Front rock guard (OPG 2)
    Vandal guard (not for use with FOPS
      top cab quard)
  Control pattern change selector
 Free swing
  Refueling pump
 Hydraulic CWT removal device
 Auxiliary hydraulics
 Attachments:
    Hose burst check valve (HBCV)
    Case multi fit Coupler
    Buckets
    Load holding control
  Under carriage:
    Steel shoes/triple-grouser:
      29.5" (750 mm)
      Full length track chain guides
    Rubber bumpers for upper
      (order through Service Parts)
```



CX470C MASS EXCAVATION CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | UNDERCARRIAGE/CHASSI | Weight | Factory Data | List Price |
|------------------|----------------------|--------|--------------|--------------|
| CX470C ME | Long Chassis | | | \$628,845.00 |
| CX470C RTC ME | Retractable Chassis | | | \$656,336.00 |



CX470C MASS EXCAVATION CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Factory Supplied Options

| i description opinion | | | | | |
|-----------------------|--|----------|--------------|---------------|--|
| Order Code | Description | Weight | Factory Data | List Price | |
| | · · · · · · | <u>-</u> | | | |
| | | | | | |
| BOOMS | | | | | |
| | | | | | |
| SD_E5311 B0 | OOM | | | | |
| 461028 | Mass Excavation Boom | | | No Charge | |
| 401020 | 21' 6" (6.55 M) Mass Excavation Boom | | | 140 Onlarge | |
| | For use with CX470C (Standard ME and RTC ME) | | | | |
| | commercial model. | | | | |
| ļ ļ | Commercial model. | ļ | <u> </u> | | |
| ARMS | | | | | |
| | | | | | |
| | | | | | |
| SD_E5320 A | RM/DIPPERSTICK | | | | |
| 461572 | 8' 4" (2.53 M) Mass Ex. Arm | | | No Charge | |
| | For use with 21'6" Mass Ex. Boom | | | | |
| XE5320X | No Arm/Dipperstick | | | (\$21,040.00) | |
| | Less arm, bucket cylinder and linkage. | | | | |
| | | | | | |
| TRACK SHOES | | | | | |
| | | | | | |
| | | | | | |
| SD_E5199 TF | RACK SHOES | | | | |
| 9560007 | 35.4" (900mm) Steel Shoes | | | No Charge | |
| | Triple-Grouser Steel Shoes | | | | |
| 9560004 | 29.5" (750mm) Steel Shoes | | | (\$1,245.00) | |
| | Triple-Grouser Steel Shoes | | | | |
| | | , | | | |
| LANGUAGE | | | | | |
| | | | | | |
| | | | | | |
| SD_47083 OF | PERATOR'S MANUAL | | | | |
| 781981 | English Language Literature | | | No Charge | |
| 461540 | French Canadian Language | | | No Charge | |
| 781980 | Spanish Language Literature | | | No Charge | |
| | | | | | |
| ADDITIONAL EQ | UIPMENT CXC | | | | |
| | | | | | |
| ADDITIONAL OPT | IONS | | | | |
| | | | | | |
| | RACK CHAIN GUIDE | <u> </u> | , | | |
| 461542 | Double Track Chain Guide | | | No Charge | |
| | | | | | |



CX470C MASS EXCAVATION CRAWLER EXCAVATOR US PRICE LIST

| | (Ex Works Port of Entry) | | | | | |
|---------------|--------------------------|---|---|----------|------|--|
| | 481264 | Full Length Track Chain Guards | | \$4,800 | 0.00 | |
| | | | | | | |
| | | TORAULIC CWT REMOVAL DEVICE | | | | |
| $\perp \perp$ | | No Hyd CWT Removal Device | | No Cha | | |
| | 481263 | Hydraulic CWT Removal Device | | \$21,900 |).00 | |
| | 05 55444 04 | D CHARD (FRONT) | | | | |
| | | B GUARD (FRONT) | 1 | No Obs | | |
| \vdash | | No Front Guard | | No Cha | _ | |
| \vdash | 461142 | Front grill guard - 2 x 2 mesh | | \$1,560 | | |
| | 781986 | Front rock guard (OPG 1) | | \$2,045 | 3.00 | |
| \vdash | 101001 | vertical bars (two piece/upper and lower) | | 40.000 | | |
| | 461024 | Front rock guard (OPG 2) | | \$2,295 | 5.00 | |
| \vdash | | vertical bars (one piece/full length) | | | | |
| | 461552 | Vandal Guard | | \$505 | 5.00 | |
| | SD E5448 CA | TMALK | | | | |
| | XE5448X | | | No Cha | rge | |
| | 461553 | Catwalk - Left and Right Sides | | \$2,435 | | |
| | 401333 | (Note: catwalk is not compliant with ISO standards) | | φ2,430 | ,.00 | |
| ш | | (Note: Catwark is not compliant with 150 standards) | | <u> </u> | — | |
| | SD_E5451 SU | IN VISOR | | | | |
| | | No Sun Visor | | No Cha | arge | |
| | 461554 | Sun Visor | | \$125 | - | |
| | | | | • | | |
| | SD_E6410 AU | IXILIARY HYDRAULICS | | | | |
| | XE6410X | No Optional Hydraulics | | No Cha | arge | |
| | 461865 | HAM ELCT PRO CNTRL | | \$9,406 | 3.00 | |
| | | Hammer Circuit Electrical Proportional Control | | | | |
| | | Joystick activated | | | | |
| | | Provides single direction flow; use for hammer application | | | | |
| | | Includes manually adjustable relief valve to set required pressures | | | | |
| | | ,,,,,,,, . | | | | |
| | | Notes: | | | | |
| | | 1) Not for use with other Auxiliary Hydraulic options, with the | | | | |
| | | exception of Low Flow. | | | | |
| | | 2) Heavy duty bucket linkage is standard equipment on | | | | |
| | | C series excavators. | | | | |
| | | | | | | |
| 1 1 | | 3) For dealer installed auxiliary hydraulic kits contact: | | | | |

HKX (1-800-493-5487 or www.HKX.com)



CX470C MASS EXCAVATION CRAWLER EXCAVATOR US PRICE LIST

| | (EX WORKS PORT OF ENTRY) | | |
|--------|---|---|-------------|
| 461868 | HAM/HF ELET PRO CNTRL | | \$12,918.00 |
| | Hammer/High Flow Circuit, Electrical Proportional Control | | |
| | | | |
| | Does not include the in-cab Electronic Pressure Control feature | | |
| | | | |
| | Joystick activated | | |
| | Provides single or dual pump, two-way flow, for use with | | |
| | multiple applications: thumb/grapples/crushers | | |
| | Secondary Low-flow Auxiliary Hydraulics can be added | | |
| | Includes manually adjustable relief valve to set required | | |
| | pressures | | |
| | Is switchable to single acting flow for hammer applications | | |
| | | | |
| | Notes: | | |
| | 1) Not for use with other Auxiliary Hydraulics options with the | | |
| | exception of Low Flow. | | |
| | 2) Heavy duty bucket linkage is standard equipment | | |
| | on C Series excavators. | | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | | |
| | HKX (1-800-493-5487 or www.HKX.com) | | |
| 461871 | AUX, TMB ELEC PRO CNTRL | | \$7,060.00 |
| | Auxiliary Circuit, Thumb, Electrical Proportional Control | | |
| | | | |
| | Joystick activated | | |
| | Provides single pump, two-way flow; use for thumb application | | |
| | Hydraulic plumbing provided to the end of the boom only, | | |
| | no piping to the arm | | |
| | This system is not switchable to single acting flow | | |
| | | | |
| | Notes: | | |
| | 1) Not for use other Auxiliary Hydraulics options with the | | |
| | exception of Low Flow. | | |
| | 2) Heavy duty bucket linkage is standard equipment on | | |
| | C series excavators. | | |
| | 3) For dealer installed auxiliary hydraulic kits contact: | | |
| | HKX (1-800-493-5487 or www.HKX.com). | | |
| • | | • | |

| SD E6417 | SECONDARY AUXILIARY HYDRAULICS |
|----------|--------------------------------|
|----------|--------------------------------|

| _ | OD_EO+17 OEOONDAKT AOMEIAKT TITOKAOEIOO | | | | | | |
|---|---|---------|--------------------|------------|--|--|-----------|
| | | XE6417X | No Extra Auxiliary | Hydraulics | | | No Charge |

No Charge

\$1,050.00



CX470C MASS EXCAVATION CRAWLER EXCAVATOR US PRICE LIST

| | (Ex Works Port of Entry) | |
|------------|---|-------------|
| 461863 | LF ELCT PRO CNTRL | \$10,376.00 |
| | Low Flow Electrical Proportional Control | |
| | Joystick Activated | |
| | Provides low-flow for rotation or tilt of hydraulic tools. | |
| | Notes: | |
| | May be used standalone or with any Case Excavator Auxiliary | |
| | Hydraulics option. | |
| | 2) For dealer installed auxiliary hydraulic kits contact: | |
| | HKX (1-800-493-5487 or www.HKX.com). | |
| SD_E6423 C | CONTROL PATTERN SELECTION | |
| XE6423 | X No Control Pattern Valve | No Charge |
| 461558 | Control Pattern Selector Valve | \$950.00 |
| SD_E9730 S | AFETY VALVE | |
| XE9730 | No Hose Burst Check Valve | No Charge |
| 461559 | Hose Burst Check Valve (HBCV) | \$9,130.00 |
| | boom and arm | |
| SD_E9740 S | IDE VIEW CAMERA | |
| XE9740 | No Side View Camera | No Charge |
| 461560 | Side View Camera | \$725.00 |
| SD_E9741 F | REE SWING | |
| XE9741 | X No Free Swing | No Charge |
| 461568 | Free Swing | \$285.00 |
| | switch activated | |
| SD F9874 F | REFUEL PUMP | |
| 1 1 | | |

XE9874X No Refuel Pump

481257 Refuel Pump



(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AH-6WG1XYSS turbocharged
EGR with cooler
6 Cylinder liquid cooled diesel
957 cu. in. (15.7L) displacement
Common rail Injection
Charge air cooling
Tier III certified
Horsepower:
- Net 463 (345) at 1800 RPM
Fuel Tank Capacity: 238 gal. (US)
(900 L)

Long Life Anti-freeze (protect to - 34°F) Automatic system warm-up

Neutral safety start

Auto idle warm-up/one-touch auto idle

Auto power boost
Cold idle start
Dual element air filter
Automatic engine derate
Emergency engine shutdown
Reversible cooling fan

OPERATOR'S CAB:

4-point iso-mounted cab

Pressurized cab

- Climate control: AC/Heat/Defrost
- KAB® adjustable deluxe seat with 3" seat-belt
- AM/FM radio with dual speakers
- Floor mats
- 12-volt outlet
- LCD monitor
- In-cab light

Cab roof skylight

Safety glass:

- Two-piece front window
- Front windshield wiper with washer

Waterproof/illuminated membrane switches

OPERATOR'S CAB (COND'T):

Low-effort pilot controls

One-touch idle

Right-side rear-view mirror

Programmable anti-theft protection

ELECTRICAL:

24 Volt system Alternator: 50 AMP

Batteries: 2

Electronic Systems Monitor
Work lights (70 watt)
Left side - boom mounted
Right side - platform mounted

UPPER STRUCTURE:

500 hour greasing interval - turntable
 bearing
Steel belly pan quarding

UNDERCARRIAGE:

X-pattern car-body
Undercarriage:

- HD: LC/long undercarriage: 1711" (5.45M)

- RETSF: LC/long undercarriage: 1711" (5.45M)

Track gauge:

- HD: 9'0''(2.75M)

- RETSF: 710" (2.60M) to 9'6"

(2.89M)

Shoes:

- 3-bar/36" (900MM) (50 per side) Hydraulic adjustable track tension Tapered upper track frame Sealed outer flange rollers Front track guides Lower under covers

TRACK DRIVE:

Two-speed independent hydrostatic travel SAHR disc parking brake Reinforced drive motor guards



(Ex Works Port of Entry) Standard Equipment

HYDRAULICS:

Open center system 2 variable flow piston pumps Variable throttle positioning Three work modes

SP - Speed priority

H - Heavy

A - Automatic

Neutral pump destroke Two pump merge boom lift circuits Two pump merge arm circuits Regeneration circuits for boom lower, arm close and bucket curl Auxiliary hydraulic valve Boom & arm anti-drift valves Attachment cushion control Swing priority system

return oil 5000 hour hydraulic oil change interval 1000 hour hydraulic filter change

Superfine^M filtration system - 100% of

ATTACHMENTS:

interval

Arm: 11'8"(3.55 m) Boom: 25'3" (7.70 M)

MISCELLANEOUS:

Parts catalogue Single key lock-up Travel alarm and horn Centralized lube bank Rubber bumpers for upper sides (order through Service Parts)

OTHER BASIC EQUIPMENT:

CASE SiteWatch™ - on board telematics required on order. See Factory Supplied Attachments page for attachment code.

OPTIONAL EQUIPMENT:

Attachments:

Arm:

- 136" (4.11M)

- 165"(5.00M)

Control pattern change selector Auxiliary hydraulics Steel shoes:

- 3-bar/36"

- 2-bar/26"

Order from Factory Supplied Attachments:

Please consult excavator attachments weight limits prior to selecting a coupler and large bucket. Excessive bucket and coupler weight will negatively impact machine performance.



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|------------|--------------|--------------|
| CX700B HD | 153,400 LB | | \$798,376.00 |



(Ex Works Port of Entry) **Factory Supplied Options**

| Order Code | Description | Weight | Factory Data | List Price |
|-------------|--|----------|--------------|---------------|
| | · | | | |
| DOOMS | | | | |
| BOOMS | | | | |
| | | | | |
| SD_E5311 B | OOM | | | |
| 781917 | No Boom | | | (\$27,897.00) |
| | Less boom, hoist and arm cylinders, and plumbing. Boom | | | (+ ,===, |
| | foot and cylinder pins are retained. | | | |
| 423334 | 25'3" (7.7 M) Reach Boom | | | No Charge |
| | | • | | |
| ARMS | | | | |
| _ | | | | |
| | | | | |
| SD_E5320 A | RM/DIPPERSTICK | | | |
| 481294 | Less Arm | | | (\$14,499.00) |
| | This option is less arm, bucket cylinder and linkage. | | | |
| 781929 | 11'8" (3.55 M) Arm | | | No Charge |
| | For use with 25'3" (7.7 M) Reach Boom - 423334 | | | |
| 781677 | 13'6" (4.11 M) Arm | | | \$1,792.00 |
| | For use with 25'3" (7.7 M) Reach Boom - 423334 | | | |
| 781930 | 16'5" (5.0 M) Arm | 9,585 LB | | \$4,109.00 |
| | For use with 25'3" (7.7 M) Reach Boom - 423334 | | | |
| | | | | |
| TRACK SHOES | | | | |
| | | | | |
| | | | | |
| SD_E5199 TI | RACK SHOES | | | |
| 423165 | 30"(750 mm) Steel Shoes, 2-bar | 1,764 LB | | (\$7,765.00) |
| 423173 | 26" (650 mm)Steel Shoes, 2-bar | 2,646 LB | | (\$7,247.00) |
| 9560007 | 35.4" (900mm) Steel Shoes | 4,100 LB | | No Charge |
| | | | | |
| LANGUAGE | | | | |
| | | | | |
| | | | | |
| SD_47083 O | PERATOR'S MANUAL | | | |
| 786819 | English Literature | 5 LB | | No Charge |
| | le | | 1 | |

786829

786830

French Canadian Literature

Spanish Literature

No Charge

No Charge



| UCKETS | | | |
|-----------------|--|--------|------------|
| | | | |
| SD F6300 FX | (CAVATOR BUCKET(S) | | |
| 423469 | No Bucket | | No Char |
| | To order a bucket(s), refer to the Direct Ship Attachment | | 1.0 0.1.0. |
| | section of the price book. | | |
| | Social of the price social | l l | |
| DDITIONAL EQI | JIPMENT CXC | | |
| ADDITIONAL OPT | IONS | | |
| ADDITIONAL OF I | IONO | | |
| SD_E5402 OF | PERATOR SEAT | | |
| XE5402X | Standard Seat | | No Char |
| 781277 | Air Suspension Seat | | \$457. |
| SD_E5441 CA | AR CHAPDS | | |
| | No Cab Guards | | No Char |
| 423323 | Vandal Guard | 50 LB | \$492. |
| 420020 | (Not for use with FOPS Top Cab Guard option 423310) | | ψ432. |
| 423313 | Front Screen - 2" by 2" mesh | 70 LB | \$1,453. |
| 423312 | Front Grill | 70 LB | \$2,546 |
| | Vertical bars with 6" spacing | | 4=,5 151 |
| • | . • | | |
| | AB GUARD (FOPS) | | |
| XE5443X | FOPS Top Cab Guard/Level 1 | | No Char |
| 423310 | FOPS Top Cab Guard/Level 2 | 223 LB | \$1,256. |
| | Not for use with Vandal Guard option 423323 | | |
| SD E5449 RA | AIN DEFLECTOR | | |
| | No Rain Deflector | | No Char |
| 423322 | Rain Deflector | | \$381. |
| | Not for use with Front Grill Guard or Front Rock Guard options | | |
| | listed in the Cab Guard Section | | |
| CD E5450 C | AD TOD CHA DOOF | | |
| | AB TOP SUN ROOF No cab roof skylight | | No Char |
| 781356 | Cab roof skylight | | \$964. |
| 701330 | | | φ904. |
| | opening cover, steel, tilts open 18" | | |
| SD_E5451 SU | JN VISOR | | |
| XE5451X | No Sun Visor | | No Char |
| 742882 | Sun Visor | | \$122. |
| | | | |
| | JXILIARY HYDRAULICS | - | N. Ol |
| XE6410X | No Optional Hydraulics | | No Char |



| | | (Ex Works Fort of Entry) | | |
|----------|--------|---|--------|-----------------|
| | 423308 | Single Acting/Joystick Active (Not for use with options 481294, 423315, & 423314) | 421 LB | \$ 11,237.00 |
| | | | | |
| | | Provides single pump flow plumbing to end of arm and return | | |
| | | to tank through additional filter. Includes remote adjustable | | |
| | | relief valve to match attachment pressure requirements. | | |
| | | - Order 2 of code 284600A1, Adapter fittings, from Parts to | | |
| | | connect 3/4" BSPP to SAE-12 Male JIC. | | |
| | | - Includes heavy duty bucket linkage. Recommended for | | |
| | | heavy hammer use and thumb applications. | | |
| | | - For dealer installed hydraulic kits contact HKX at | | |
| \vdash | | 800-493-5487 or www.hkx.com | | |
| | 423315 | Double Acting, Bi-directional | 434 LB | \$ 15,498.00 |
| | | (Not for use with options 481294, 423308 & 423314) | | |
| | | Provides single or dual pump bi-directional flow to end of | | |
| | | arm. Includes plumbing and valving to operate single | | |
| | | direction flow with return to tank through additional filter | | |
| | | (included). Includes remote relief valve for single direction | | |
| | | operations. This kit allows the use of two different types of | | |
| | | attachments on an excavator, such as a breaker and a | | |
| | | grapple. | | |
| | | - Order 2 of code 284600A1, Adapter fittings, from Parts to | | |
| | | connect 3/4" BSPP to SAE - 12 Male JIC. | | |
| | | - Includes heavy duty bucket linkage. Recommended for | | |
| | | heavy hammer use and thumb applications. | | |
| | | - For dealer installed hydraulic kits contact HKX at | | |
| Ш | | 800-493-5487 or www.hkx.com | | |
| | 423314 | Double Acting, General Purpose | 340 LB | \$8,915.00 |
| | | (Not for use with 481294, 423308 & 423315) | | |
| | | Recommended for use with a thumb kit. Plumbing to the end | | |
| | | of the boom, no hydraulics provided on the arm. Actuated by | | |
| | | trigger switches in the right and left hand controls. Right | | |
| | | controls one-way flow, left controls opposite flow. Right hand | | |
| | | switch is the same switch that controls power boost. | | |
| | | - Order 2 code 284600A1, Adapter fittings, from Parts to | | |
| | | connect 3/4" BSPP to SAE-12 Male JIC. | | |
| | | - For dealer installed hydraulic kits contact HKX at | | |
| | | 800-493-5487 or www.hkx.com | | |

| SD_E5206 | TRACK CHAIN GUIDE |
|----------|-------------------|
|----------|-------------------|

| г | | | | |
|-----|------------|------------------|--|-------------|
| - 1 | VEE000V | 1 N T 1 O 1 I | | |
| - 1 | | l No Track Guide | | No Charge I |
| | 1 / 1/2/0/ | | | |

\$1,474.00



CX700B CRAWLER EXCAVATOR US PRICE LIST

423311 Control Pattern Selector valve

| | US PRICE LIST | | |
|----------------|---|-------------|-------------|
| | (Ex Works Port of Entry) | | |
| 481264 | Full Length Track Chain Guards | 728 LB | \$8,738.00 |
| | Three sections | | |
| | | | |
| | YDRAULIC CWT REMOVAL DEVICE | | |
| 1 1 | No Hyd CWT Removal Device | | No Charge |
| 481263 | Hydraulic CWT Removal Device | 967 LB | \$25,634.00 |
| SD E6417 S | ECONDARY AUXILIARY HYDRAULICS | | |
| XE6417 | | | No Charge |
| 423329 | Secondary Auxiliary Hydraulics | | \$11,140.00 |
| | Secondary auxiliary hydraulics – low flow (joystick operated, | | |
| | provides rotation or tilt for hydraulic attachments such as | | |
| | shears and tilt buckets). Order two of code 284600A, adaptor | | |
| | fittings, from parts to connect ¾"BSPP to SAE-12 male JIC. | | |
| | Includes heavy duty bucket linkage. Recommended for heavy | | |
| | hammer use and thumb applications | | |
| • | | - | • |
| SD_E6422 H | OIST CYLINDER ONLY | | |
| XE6422 | No Boom Hoist Cylinders Only | | No Charge |
| | Option is for use with any boom or no choice boom option | | |
| 423316 | Boom hoist cylinders (2) | 557 LB | \$6,242.00 |
| | For units ordered with No Boom option 781917 | | |
| | | | |
| | ONTROL PATTERN SELECTION | | |
| XE6423 | No Control Pattern Valve | | No Charge |
| | | | |

30 LB



(This page intentionally left blank)



(Ex Works Port of Entry) Factory Supplied Attachments

| Order Code | Description | Weight | Factory Data | List Price |
|------------------|--|----------|--------------|-------------|
| IUST ORDER TE | LEMATICS | | | |
| 84557015 | CASE SiteWatch™ - on board telematics To order Service Subscription contact Service Parts. | | | \$1.00 |
| eavy Duty - High | n Capacity | | | |
| 47526701 | 72" Heavy Duty - High Capacity Bucket with 7 teeth, 4.20 cu. yd. (1.65 cu. m.) | 7,250 LB | | \$16,400.00 |
| 47526702 | 42" Heavy Duty, High Capacity Bucket with 4 teeth, 2.57 cu. yd. (1.96 cu. m.) | 5,500 LB | | \$17,711.00 |
| 47526713 | 48" Heavy Duty, High Capacity Bucket with 5 teeth, 2.99 cu. yd. (2.29 cu. m.) | 5,830 LB | | \$19,129.00 |
| 47526717 | 54" Heavy Duty, High Capacity Bucket with 5 teeth, 3.41 cu. yd. (2.61 cu. m.) | 6,300 LB | | \$20,661.00 |
| 47526718 | 60" Heavy Duty, High Capacity Bucket with 6 teeth, 3.84 cu. yd. (2.94 cu. m.) | 6,660 LB | | \$22,314.00 |
| 47526724 | 66" Heavy Duty, High Capacity Bucket with 6 teeth, 4.27 cu. yd. (3.26 cu. m.) | 7,100 LB | | \$24,096.00 |
| 47526727 | 72" Heavy Duty, High Capacity Bucket with 7 teeth, 4.69 cu. yd. (3.59 cu. m.) | 7,460 LB | | \$26,023.00 |
| eavy Duty - Star | ndard Capacity | | | |
| 47526679 | 36" Heavy Duty, Standard Capacity Bucket with 4 teeth, 1.94 cu. yd. (1.48 cu. m.) | 4,800 LB | | \$15,472.00 |
| 47526680 | 42" Heavy Duty, Standard Capacity Bucket with 5 teeth, 2.31 cu. yd. (1.77 cu. m.) | 5,300 LB | | \$16,709.00 |
| 47526684 | 48" Heavy Duty, Standard Capacity Bucket with 5 teeth, 2.68 cu. yd. (2.05 cu. m.) | 5,600 LB | | \$18,049.00 |
| 47526687 | 54" Heavy Duty, Standard Capacity Bucket with 6 teeth, 3.05 cu. yd. (2.33 cu. m.) | 6,000 LB | | \$19,491.00 |
| 47526690 | 60" Heavy Duty, Standard Capacity Bucket with 6 teeth, 3.44 cu. yd. (2.63 cu. m.) | 6,400 LB | | \$21,051.00 |
| 47526691 | 66" Heavy Duty, Standard Capacity Bucket with 7 teeth, 3.82 cu. yd. (2.92 cu. m.) | 6,825 LB | | \$22,733.00 |
| 47526699 | 72" Heavy Duty, Standard Capacity Bucket with 7 teeth, 4.20 cu. yd. (3.21 cu. m.) | 7,250 LB | | \$24,553.00 |
| evere Duty | | | | |
| 47526731 | 36" Severe Duty Bucket with 4 teeth, 1.94 cu. yd. (1.48 cu. m.) | 5,300 LB | | \$18,051.00 |
| 47526742 | 42" Severe Duty Bucket with 5 teeth, 2.31 cu. yd. (1.77 cu. m.) | 5,800 LB | | \$19,467.00 |
| 47526748 | 48" Severe Duty Bucket with 5 teeth, 2.68 cu. yd. (2.05 cu. m.) | 6,100 LB | | \$20,913.00 |
| 47526751 | 54" Severe Duty Bucket with 6 teeth, 3.05 cu. yd. (2.33 cu. m.) | 6,500 LB | | \$22,757.00 |
| 47526753 | 60" Severe Duty Bucket with 6 teeth, 3.44 cu. yd. (2.63 cu. m.) | 6,900 LB | | \$24,511.00 |



| | 47526763 | 66" Severe Duty Bucket | 7,325 LB | \$26,591.00 |
|--|----------|--|----------|-------------|
| | | with 7 teeth, 3.82 cu. yd. (2.92 cu. m.) | | |



(Ex Works Port of Entry) Standard Equipment

ENGINE

Isuzu AH - 6WG1XYSS turbocharged EGR with cooler 6 Cyl. liquid cooled diesel 957 cu. in. (15.7L) displacement Common rail injection Charged air cooling Tier III certified

Horsepower:

- Net 532 (397) at 1800 RPM
Fuel Tank Capacity: 238 gal. (US)
 (900 L)

Long Life Anti-freeze (protect to -34°F)

Automatic system warm-up

Auto idle warm-up/one-touch auto idle

Neutral safety start Auto power boost Cold idle start

Dual element air filter Automatic engine derate Emergency engine shutdown Spark arresting muffler Reversible cooling fan

OPERATOR'S CAB:

4-point iso-mounted cab

Pressurized cab

- Climate control: AC/Heat/Defrost
- KAB® adjustable deluxe seat with 3" seat-belt
- AM/FM radio with dual speakers
- Floor mats
- 12-volt outlet
- LCD monitor
- In-cab light

Cab roof skylight

Safety glass:

- Two-piece front window
- Front windshield wiper with washer

Waterproof/illuminated membrane switches

OPERATOR'S CAB (COND'T):

Low-effort pilot controls

One-touch idle

Right-side rear-view mirror

Programmable anti-theft protection

ELECTRICAL:

24 Volt system
Alternator: 50 AMP

Batteries: 2

Electronic Systems Monitor
Work lights (70 watt)
Left side - boom mounted

Right side - platform mounted

UPPER STRUCTURE:

500 hour greasing interval - turntable bearing

Steel belly pan guarding

UNDERCARRIAGE:

X-pattern car-body
Undercarriage:

- LC/long undercarriage: 2010" (6.36 M)

Track gauge:

Shoes:

- 2-bar/30" (750 mm) (51 per side) Hydraulic adjustable track tension Tapered upper track frame Sealed outer flange rollers Front track guides Lower under covers

TRACK DRIVE:

Two-speed independent hydrostatic travel
SAHR disc parking brake

Reinforced drive motor guards



(Ex Works Port of Entry) Standard Equipment

HYDRAULICS:

Open center system
Two variable flow piston pumps
Variable throttle positioning
Three work modes

SP - Speed priority

H - Heavy

A - Automatic

Neutral pump destroke
Two pump merge boom lift circuits
Two pump merge arm circuits
Regeneration circuits for boom
lower, arm close and bucket curl
Auxiliary hydraulic valve
Boom & arm anti-drift valves

Attachment cushion for boom and arm Swing priority system

Superfine[™] filtration system - 100% of return oil

5000 hour hydraulic oil change interval 1000 hour hydraulic filter change interval

ATTACHMENTS:

Boom: 277" (8.40M) Arm: 120" (3.66M)

MISCELLANEOUS:

Parts catalogue
Single key lock-up
Travel alarm and horn
Centralized lube bank
Rubber bumpers for upper sides
(order through Service Parts)

OPTIONAL EQUIPMENT:

Attachments:

Boom:

- 239" (7.25M) Mass Excavation

Arm:

- 147" (4.44M)

- 185" (5.62M)

- 9'9" (2.98M) Mass Excavation

Control pattern change selector

Auxiliary hydraulics

Steel shoes:

- 3-bar/36"

- 2-bar/26"



(Ex Works Port of Entry) Models

| COMMERCIAL MODEL | Weight | Factory Data | List Price |
|------------------|------------|--------------|----------------|
| CX800B HD | 175,210 LB | | \$1,100,782.00 |



(Ex Works Port of Entry)

Factory Supplied Options

| Order Code Description Weight Factory Data List Price |
|---|
|---|

BOOMS

SD_E5311 BOOM

| | 423140 | 27'7" (8.4 M) Reach Boom | 21,641 LB | No Charge |
|--|--------|--|-----------|---------------|
| | 423143 | 23'9" (7.25 M) Mass Ex Boom | 1,195 LB | \$8,298.00 |
| | 781917 | No Boom | | (\$38,576.00) |
| | | Less boom, hoist and arm cylinders, and plumbing. Boom | | |
| | | foot and cylinder pins are retained. | | |

ARMS

SD_E5320 ARM/DIPPERSTICK

| 481850 | 12' (3.66 M) Standard Arm | 8,818 LB | No Charge |
|--------|---|-----------|---------------|
| | For use with 27'7" (8.4 M) Reach Boom - 423140 | | |
| 481846 | 9'9" (2.98 M) Arm | 8,399 LB | \$9,528.00 |
| | For use with 23'9" (7.25 M) Mass Ex Boom - 423143 | | |
| 423158 | 14'7" (4.44 M) Arm | 9,145 LB | \$1,986.00 |
| | For use with 27'7" (8.4 M) Reach Boom - 423140 | | |
| 481247 | 18'5" (5.62 M) Arm | 10,714 LB | \$11,204.00 |
| | For use with 27'7" (8.4 M) Reach Boom - 423140 | | |
| 481294 | Less Arm | | (\$19,304.00) |
| | This option is less arm, bucket cylinder and linkage. | | |

TRACK SHOES

SD_E5199 TRACK SHOES

| | 423173 | 26" (650 mm)Steel Shoes, 2-bar | 2,646 LB | (\$828.00) |
|--|---------|--------------------------------|----------|------------|
| | 423165 | 30"(750 mm) Steel Shoes, 2-bar | 1,764 LB | No Charge |
| | 9560007 | 35.4" (900mm) Steel Shoes | 4,100 LB | \$5,402.00 |

LANGUAGE

SD_47083 OPERATOR'S MANUAL

| | 786819 | English Literature | 5 LB | No Charge |
|--|--------|----------------------------|------|-----------|
| | 786829 | French Canadian Literature | | No Charge |
| | 786830 | Spanish Literature | | No Charge |



| UCKETS | | | |
|-----------------|--|------------|----------|
| | | | |
| SD E6300 EX | CAVATOR BUCKET(S) | | |
| 423469 | No Bucket | | No Charg |
| | To order a bucket(s), refer to the Direct Ship Attachment | | · · |
| | section of the price book. | | |
| 1 | | | ' |
| DDITIONAL EQU | JIPMENT CXC | | |
| ADDITIONAL OPTI | ONC | | |
| ADDITIONAL OPTI | ONO | | |
| SD_E5402 OF | PERATOR SEAT | | |
| XE5402X | Standard Seat | | No Char |
| 781277 | Air Suspension Seat | | \$457. |
| CD E5444 CA | D CHARDS | | |
| SD_E5441 CA | No Cab Guards | | No Char |
| 423323 | Vandal Guard | 50 LB | \$492. |
| 423323 | Not for use with FOPS Top Cab Guard option 423310 | 30 LB | φ492. |
| 423313 | Front Screen - 2" by 2" mesh | 70 LB | \$1,453. |
| 423312 | Front Grill | 70 LB | \$2,546 |
| 720012 | Vertical bars with 6" spacing | 1028 | Ψ2,040. |
| | To the state of th | | |
| SD_E5443 CA | B GUARD (FOPS) | | |
| XE5443X | FOPS Top Cab Guard/Level 1 | | No Char |
| 423310 | FOPS Top Cab Guard/Level 2 | 223 LB | \$1,256. |
| | Not for use with Vandal Guard option 423323 | | |
| OD 55440 DA | IN DEEL COTOD | | |
| | IN DEFLECTOR No Rain Deflector | | No Char |
| 423322 | Rain Deflector | | \$381. |
| 720022 | Not for use with Front Grill Guard or Front Rock Guard options | | ψοσ1. |
| | listed in the Cab Guard Section | | |
| 1 | instea in the oab oddra occion | _ L | _ |
| SD_E5450 CA | B TOP SUN ROOF | | |
| XE5450X | No cab roof skylight | | No Char |
| 781356 | Cab roof skylight | | \$964. |
| | opening cover, steel, tilts open 18" | | |
| | | | |
| SD_E5451 SL | | | |
| _ | No Sun Visor | | No Char |
| 742882 | Sun Visor | | \$122. |
| CD EC440 AL | IVII IA DV LIVDD ALII ICC | | |
| | IXILIARY HYDRAULICS No Optional Hydraulics | | No Char |
| AE0410X | I NO Optional Hydraulics | | No Char |



| | | (Ex Works Fort of Entry) | | |
|---|--------|---|--------|-------------|
| | 423308 | Single Acting/Joystick Active (Not for use with options 481294, 423315, & 423314) | 421 LB | \$12,838.00 |
| | | | | |
| | | Provides single pump flow plumbing to end of arm and return | | |
| | | to tank through additional filter. Includes remote adjustable | | |
| | | relief valve to match attachment pressure requirements. | | |
| | | - Order 2 of code 284600A1, Adapter fittings, from Parts to | | |
| | | connect 3/4" BSPP to SAE-12 Male JIC. | | |
| | | - Includes heavy duty bucket linkage. Recommended for | | |
| | | heavy hammer use and thumb applications. | | |
| | | - For dealer installed hydraulic kits contact HKX at | | |
| | | 800-493-5487 or www.hkx.com | | |
| | 423315 | Double Acting, Bi-directional | 434 LB | \$17,720.00 |
| | | (Not for use with options 481294, 423308 & 423314) | | |
| | | Provides single or dual pump bi-directional flow to end of | | |
| | | arm. Includes plumbing and valving to operate single | | |
| | | direction flow with return to tank through additional filter | | |
| | | (included). Includes remote relief valve for single direction | | |
| | | operations. This kit allows the use of two different types of | | |
| | | attachments on an excavator, such as a breaker and a | | |
| | | grapple. | | |
| | | - Order 2 of code 284600A1, Adapter fittings, from Parts to | | |
| | | connect 3/4" BSPP to SAE - 12 Male JIC. | | |
| | | - Includes heavy duty bucket linkage. Recommended for | | |
| | | heavy hammer use and thumb applications. | | |
| | | - For dealer installed hydraulic kits contact HKX at | | |
| Ш | | 800-493-5487 or www.hkx.com | | |
| | 423314 | Double Acting, General Purpose | 340 LB | \$9,897.00 |
| | | (Not for use with 481294, 423308 & 423315) | | |
| | | Recommended for use with a thumb kit. Plumbing to the end | | |
| | | of the boom, no hydraulics provided on the arm. Actuated by | | |
| | | trigger switches in the right and left hand controls. Right | | |
| | | controls one-way flow, left controls opposite flow. Right hand | | |
| | | switch is the same switch that controls power boost. | | |
| | | - Order 2 code 284600A1, Adapter fittings, from Parts to | | |
| | | connect 3/4" BSPP to SAE-12 Male JIC. | | |
| | | - For dealer installed hydraulic kits contact HKX at | | |
| | | 800-493-5487 or www.hkx.com | | |

| SD E5206 | TRACK CHAIN GUIDE |
|----------|-------------------|
|----------|-------------------|

| | XE5206X l | No Track Guide | | No Charge I |
|--|-----------|----------------|--|-------------|

\$1,474.00



CX800B CRAWLER EXCAVATOR US PRICE LIST

| | | US PRICE LIST | | |
|---|-------------|---|--------|-------------|
| | | (Ex Works Port of Entry) | | |
| | 481264 | Full Length Track Chain Guards | 728 LB | \$8,738.00 |
| | | Three sections | | |
| | | | | |
| S | D_E5302 HY | DRAULIC CWT REMOVAL DEVICE | | |
| | XE5302X | No Hyd CWT Removal Device | | No Charge |
| | 481263 | Hydraulic CWT Removal Device | 967 LB | \$27,417.00 |
| S | SD_E6417 SE | CONDARY AUXILIARY HYDRAULICS | | |
| | XE6417X | No Extra Auxiliary Hydraulics | | No Charge |
| | 423329 | Secondary Auxiliary Hydraulics | | \$12,838.00 |
| | | Secondary auxiliary hydraulics – low flow (joystick operated, | | |
| | | provides rotation or tilt for hydraulic attachments such as | | |
| | | shears and tilt buckets). Order two of code 284600A, adaptor | | |
| | | fittings, from parts to connect ¾"BSPP to SAE-12 male JIC. | | |
| | | Includes heavy duty bucket linkage. Recommended for heavy | | |
| | | hammer use and thumb applications | | |
| | • | | • | • |
| S | | DIST CYLINDER ONLY | | |
| | XE6422X | No Boom Hoist Cylinders Only | | No Charge |
| | | Option is for use with any boom or no choice boom option | | |
| | 423316 | Boom hoist cylinders (2) | 557 LB | \$8,445.00 |
| | | For units ordered with No Boom option 781917 | | |
| c | SD E6423 CC | ONTROL PATTERN SELECTION | | |
| П | | No Control Pattern Valve | | No Charge |
| + | /LU-20/ | 110 Control 1 attorn valvo | | 140 Onargo |

30 LB

423311 Control Pattern Selector valve



(This page intentionally left blank)



(Ex Works Port of Entry) Factory Supplied Attachments

| Order Code | Description | Weight | Factory Data | List Price | | | |
|----------------------|--|----------|--------------|-------------|--|--|--|
| UST ORDER TELEMATICS | | | | | | | |
| 84557015 | CASE SiteWatch™ - on board telematics To order Service Subscription contact Service Parts. | | | \$1.00 | | | |
| eavy Duty | | | | | | | |
| 47526854 | 42" Heavy Duty, Standard Capacity Bucket with 4 teeth, 2.85 cu. yd. (2.18 cu. m.) | 6,100 LB | | \$18,190.00 | | | |
| 47526856 | 48" Heavy Duty, Standard Capacity Bucket with 4 teeth, 3.31 cu. yd. (2.53 cu. m.) | 6,500 LB | | \$19,666.00 | | | |
| 47526859 | 54" Heavy Duty, Standard Capacity Bucket with 5 teeth, 3.78 cu. yd. (2.89 cu. m.) | 7,000 LB | | \$21,261.00 | | | |
| 47526872 | 60" Heavy Duty, Standard Capacity Bucket with 5 teeth, 4.26 cu. yd. (3.26 cu. m.) | 7,400 LB | | \$22,984.00 | | | |
| 47526878 | 66" Heavy Duty, Standard Capacity Bucket with 6 teeth, 4.74 cu. yd. (3.62 cu. m.) | 7,900 LB | | \$24,843.00 | | | |
| 47526883 | 72" Heavy Duty, Standard Capacity Bucket with 6 teeth, 5.21 cu. yd. (3.98 cu. m.) | 8,150 LB | | \$25,509.00 | | | |
| 47526889 | 78" Heavy Duty, Standard Capacity Bucket with 7 teeth, 5.69 cu. yd. (4.35 cu. m.) | 8,650 LB | | \$26,540.00 | | | |
| 47526892 | 84" Heavy Duty, Standard Capacity Bucket with 7 teeth, 6.17 cu. yd. (4.72 cu. m.) | 9,100 LB | | \$27,573.00 | | | |
| evere Duty | | | | | | | |
| 47526903 | 42" Severe Duty Bucket with 4 teeth, 2.85 cu. yd. (2.18 cu. m.) | 7,100 LB | | \$20,331.00 | | | |
| 47526907 | 48" Severe Duty Bucket with 4 teeth, 3.31 cu. yd. (2.53 cu. m.) | 7,550 LB | | \$21,921.00 | | | |
| 47526912 | 54" Severe Duty Bucket with 5 teeth, 3.78 cu. yd. (2.89 cu. m.) | 8,120 LB | | \$25,125.00 | | | |
| 47526916 | 60" Severe Duty Bucket with 5 teeth, 4.26 cu. yd. (3.26 cu. m.) | 8,600 LB | | \$27,173.00 | | | |
| 47526929 | 66" Severe Duty Bucket with 6 teeth, 4.74 cu. yd. (3.62 cu. m.) | 9,200 LB | | \$29,394.00 | | | |



(This page intentionally left blank)